

Moscow ML Library Documentation

Version 2.00 of June 2000

Sergei Romanenko, Russian Academy of Sciences, Moscow, Russia
 Claudio Russo, Cambridge University, Cambridge, United Kingdom
 Peter Sestoft, Royal Veterinary and Agricultural University, Copenhagen, Denmark

This document

This manual describes the Moscow ML library, which includes parts of the SML Basis Library and several extensions. The manual has been generated automatically from the commented signature files.

Alternative formats of this document

Hypertext on the World-Wide Web

The manual is available at <http://www.dina.kvl.dk/~sestoft/mosml.lib/> for online browsing.

Hypertext in the Moscow ML distribution

The manual is available for offline browsing at <mosml/doc/mosml.lib/index.html> in the distribution.

On-line help in the Moscow ML interactive system

The manual is available also in interactive mosml sessions. Type `help "lib"`; for an overview of built-in function libraries. Type `help "fromstring"`; for help on a particular identifier, such as `fromString`. This will produce a menu of all library structures which contain the identifier `fromstring` (disregarding the lowercase/uppercase distinction):

```
-----
1 | val Bool.fromString
2 | val Char.fromString
3 | val Date.fromString
4 | val Int.fromString
5 | val Path.fromString
6 | val Real.fromString
7 | val String.fromString
8 | val Time.fromString
9 | val Word.fromString
10 | val Word8.fromString
-----
```

Choosing a number from this menu will invoke the help browser on the desired structure, e.g. `Int`.

The Moscow ML home page is <http://www.dina.kvl.dk/~sestoft/mosml.html>

String 120
 StringCvt 122
 Substring 124
 Susp 128
 Array 3
 TextIO 6
 Time 9
 Timer 10
 Unix 13
 Vector 14
 Weak 16
 Word 17
 Word8 18
 Word8Array 21
 Word8Vector 24
 Index 25

Contents

AppleScript 2
 Array 3
 Array2 6
 Arraysort 9
 BinIO 10
 Binarymap 13
 Binaryset 14
 Bool 16
 Byte 17
 Callback 18
 Char 21
 CharArray 24
 CharVector 25
 CommandLine 26
 Date 27
 Dynarray 30
 Dynlib 31
 FileSys 33
 Gdbm 36
 Gdimage 38
 General 41
 Help 45
 Int 46
 Inmap 48
 Inset 49
 Lexing 51
 List 53
 ListPair 55
 Listsort 56
 Location 57
 Math 59
 Meta 61
 Mosml 65
 Mosmlegi 66
 Mosmlcookie 69
 Msp 70
 Mysql 76
 NI93 80
 Nonstdio 82
 OS 83
 Option 84
 Pp 85
 Parsing 88
 Path 90
 Polygdbm 93
 Polyhash 95
 Postgres 97
 Process 101
 Random 102
 Real 103
 Regex 105
 SML90 109
 Signal 110
 Socket 112
 Splaymap 117
 Splayset 118

Module AppleScript

```
AppleScript -- Apple MacOS scripting
```

```
type OSaID
type OSaerr = int
exception AppleScriptErr of OSaerr * string
val as_compile      : string -> OSaID
val as_dispose      : OSaID -> unit
val as_run_script   : OSaID -> string
val as_run_text     : string -> string
```

These Mac specific functions provide the capability to compile and run AppleScript programs.

The exception AppleScriptErr is raised in the event of an error.

[as_compile str] compiles AppleScript source code text, returning an abstract token of type OSaID. This token may be used to run the script. The token may be used repeatedly until it is returned with as_dispose or until mosml exits.

[as_dispose tok] disposes of the resources associated with the OSaID token so that they may be reused by the AppleScript system. AppleScriptErr is raised upon any attempt to reuse a disposed token.

[as_run_script tok] runs the script associated with the token. This typically involves AppleEvent communication with other programs running on the Mac, or networked Macs. The AppleScript result is returned as a string.

[as_run_text str] compiles and runs the AppleScript source code text, disposing all resources allocated in the process, and returns the AppleScript result as a string.

References:

Inside Macintosh: Interapplication Communication, Chapter 10
 AppleScript Language Guide English Edition,
 available at <http://applescript.apple.com/support.html>

Module Array

```
Array -- SML Basis Library
```

```
prim_EType 'a array
val maxLen  : int
val array   : int * 'a -> 'a array
val tabulate : int * (int -> 'a) -> 'a array
val fromList : 'a list -> 'a array
val length   : 'a array -> int
val sub      : 'a array * int -> 'a
val update   : 'a array * int * 'a -> unit
val extract  : 'a array * int * int option -> 'a Vector.vector
val copy     : {src: 'a array, si: int, len: int option,
               dst: 'a array, di: int} -> unit
val copyVec  : {src: 'a vector, si: int, len: int option,
               dst: 'a array, di: int} -> unit
val app      : ('a -> unit) -> 'a array -> unit
val foldl    : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldr    : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val modify   : ('a -> 'a) -> 'a array -> unit
val appi     : (int * 'a -> unit) -> 'a array * int * int option -> unit
val foldli   : (int * 'a * 'b -> 'b) -> 'b -> 'a array * int * int option -> 'b
val foldri   : (int * 'a * 'b -> 'b) -> 'b -> 'a array * int * int option -> 'b
val modifyi  : (int * 'a -> 'a) -> 'a array * int * int option -> unit
```

['ty array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type 'ty. Type 'ty array admits equality even if 'ty does not. Arrays a1 and a2 are equal if both were created by the same call to a primitive (array, tabulate, fromList).

Some functions work on a *slice* of an array:

The slice (a, i, SOME n) denotes the subarray a[i..i+n-1]. That is, a[i] is the first element of the slice, and n is the length of the slice. Valid only if 0 <= i <= i+n <= length a.

The slice (a, i, NONE) denotes the subarray a[i..length a-1]. That is, the slice denotes the suffix of the array starting at i. Valid only if 0 <= i <= length a. Equivalent to (a, i, SOME(length a - i)).

slice	meaning
(a, 0, NONE)	the whole array
(a, 0, SOME n)	a left subarray (prefix) a[0..n-1]
(a, i, NONE)	a right subarray (suffix) a[i..len-1]
(a, i, SOME n)	a general slice a[i..i+n-1]

[maxLen] is the maximal number of elements in an array.

[array(n, x)] returns a new array of length n whose elements are all x. Raises Size if n < 0 or n > maxLen.

[tabulate(n, f)] returns a new array of length n whose elements are f 0, f 1, ..., f (n-1), created from left to right. Raises Size if n < 0 or n > maxLen.

[fromList xs] returns an array whose elements are those of xs. Raises Size if length xs > maxLen.

[length a] returns the number of elements in a.

[sub(a, i)] returns the i'th element of a, counting from 0. Raises Subscript if i < 0 or i >= length a. To make 'sub' infix, use

```

the declaration      infix 9 sub
[update(a, i, x)] destructively replaces the i'th element of a by x.
Raises Subscript if i<0 or i>length a.
[extract(a, i, NONE)] returns a vector of the elements a[i..length a-1]
of a. Raises Subscript if i<0 or i>length a.
[extract(a, i, SOME len)] returns a vector of the elements a[i..i+len-1]
of a. Raises Subscript if i<0 or i+len>length a or
len>Vector.maxLen.
[copy(src, si, len, dst, di)] destructively copies the slice
(src, si, len) to dst, starting at index di. More precisely:
If len=NONE and n=length src, it copies src[si..n-1] to dst[di..di+n-si].
If len=SOME k, it copies src[si..si+k-1] to dst[di..di+k-1].
Works also if src and dst are the same and the segments overlap.
Raises Subscript if si < 0 or di < 0,
or if len=NONE and di + length src - si > length dst,
or if len=SOME k and k < 0 or si + k > length src or di + k > length dst.
[copyVec(src, si, len, dst, di)] destructively copies the slice
(src, si, len) to dst, starting at index di. More precisely:
If len=NONE and n=length src, it copies src[si..n-1] to dst[di..di+n-si].
If len=SOME k, it copies src[si..si+k-1] to dst[di..di+k-1].
Works also if src and dst are the same and the segments overlap.
Raises Subscript if si < 0 or di < 0,
or if len=NONE and di + length src - si > length dst,
or if len=SOME k and k < 0 or si + k > length src or di + k > length dst.
[foldl f e a] folds function f over a from left to right. That is,
computes f(a[0], f(a[1], ..., f(a[len-2], f(a[len-1], e) ...)),
where len is the length of a.
[foldr f e a] folds function f over a from right to left. That is,
computes f(a[0], f(a[1], ..., f(a[len-2], f(a[len-1], e) ...)),
where len is the length of a.
[app f a] applies f to a[j] for j=0,1,...,length a-1.
[modify f a] applies f to a[j] and updates a[j] with the result
f(a[j]) for j=0,1,...,length a-1.
The following iterators generalize the above ones in two ways:
. the index j is also being passed to the function being iterated;
. the iterators work on a slice (subarray) of an array.
[foldl f e (a, i, SOME n)] folds function f over the subarray
a[i..i+n-1] from left to right. That is, computes
f(i+n-1, a[i+n-1], f(..., f(i+1, a[i+1]), f(i, a[i], e) ...)).
Raises Subscript if i<0 or n<0 or i+n > length a.
[foldl f e (a, i, NONE)] folds function f over the subarray
a[i..len-1] from left to right, where len = length a. That is,
computes f(len-1, a[len-1], f(..., f(i+1, a[i+1]), f(i, a[i], e) ...)).
Raises Subscript if i<0 or i > length a.
[foldr f e (a, i, SOME n)] folds function f over the subarray
a[i..i+n-1] from right to left. That is, computes
f(i, a[i], f(i+1, a[i+1], ..., f(i+n-1, a[i+n-1], e) ...)).
Raises Subscript if i<0 or n<0 or i+n > length a.
[foldr f e (a, i, NONE)] folds function f over the subarray
a[i..len-1] from right to left, where len = length a. That is,
computes f(i, a[i], f(i+1, a[i+1], ..., f(len-1, a[len-1], e) ...)).
Raises Subscript if i<0 or i > length a.
[appi f (a, i, SOME n)] applies f to successive pairs (j, a[j]) for
j=i,i+1,...,i+n-1. Raises Subscript if i<0 or n<0 or i+n > length a.

```

```

[appi f (a, i, NONE)] applies f to successive pairs (j, a[j]) for
j=i,i+1,...,len-1, where len = length a. Raises Subscript if i<0
or i > length a.
[modify f (a, i, SOME n)] applies f to (j, a[j]) and updates a[j]
with the result f(j, a[j]) for j=i,i+1,...,i+n-1. Raises Subscript
if i<0 or n<0 or i+n > length a.
[modify f (a, i, NONE)] applies f to (j, a[j]) and updates a[j]
with the result f(j, a[j]) for j=i,i+1,...,len-1. Raises Subscript
if i<0 or i > length a.

```

Module Array2

Array2 -- SML Basis Library

```

datatype traversal = RowMajor | ColMajor

val array      : int * int * 'a -> 'a array
val fromList  : 'a list list -> 'a array
val tabulate  : traversal -> int * int * (int * int -> 'a) -> 'a array

val dimensions : 'a array -> int * int
val nCols     : 'a array -> int
val nRows     : 'a array -> int

val sub       : 'a array * int * int -> 'a
val update    : 'a array * int * int * 'a -> unit
val row       : 'a array * int -> 'a Vector.vector
val column    : 'a array * int -> 'a Vector.vector

type 'a region = { base : 'a array, row : int, col : int,
                  nRows : int option, nCols : int option}

val copy      : { src : 'a region, dst : 'a array,
                 dst_row : int, dst_col : int } -> unit

val app       : traversal -> ('a -> unit) -> 'a array -> unit
val modify    : traversal -> ('a -> 'a) -> 'a array -> unit
val fold      : traversal -> ('a * 'b -> 'b) -> 'b -> 'a array -> 'b

val appi      : traversal -> (int * int * 'a -> unit) -> 'a region -> unit
val modifyi   : traversal -> (int * int * 'a -> 'a) -> 'a region -> unit
val foldi     : traversal -> (int * int * 'a * 'b -> 'b) -> 'b
                -> 'a region -> 'b

```

['ty array] is the type of two-dimensional, mutable, zero-based constant-time-access arrays with elements of type 'ty. Type 'ty array admits equality even if 'ty does not. Arrays a1 and a2 are equal if both were created by the same call to one of the primitives array, fromList, and tabulate.

[traversal] is the type of traversal orders: row major or column major.

[RowMajor] specifies that an operation must be done in row-major order, that is, one row at a time, from top to bottom, and from left to right within each row. Row-major traversal visits the elements of an (m,n)-array with m rows and n columns in this order:

```
(0,0), (0,1), (0,2), ..., (0,n-1),
(1,0), (1,1), (1,2), ..., (1,n-1),
...
```

that is, in order of lexicographically increasing (i, j). In Moscow ML, row-major traversal is usually faster than column-major traversal.

[ColMajor] specifies that an operation must be done in column-major order, that is, one column at a time, from left to right, and from top to bottom within each column. Column-major traversal visits the elements of an (m,n)-array with m rows and n columns in this order:

```
(0,0), (1,0), (2,0), ..., (m-1,0),
(0,1), (1,1), (2,1), ..., (m-1,1),
...
```

that is, in order of lexicographically increasing (j, i).

[array(m, n, x)] returns a new m * n matrix whose elements are all x. Raises Size if n < 0 or m < 0.

[fromList xss] returns a new array whose first row has elements

xsl, second row has elements xss2, ..., where xss = [xsl.xs2, ..., xsm]. Raises Size if the lists in xss do not all have the same length.

[tabulate RowMajor (m, n, f)] returns a new m-by-n array whose elements are f(0,0), f(0,1), ..., f(0, n-1), f(1,0), f(1,1), ..., f(1, n-1), ...,

f(m-1,0), ..., f(m-1, n-1) created in row-major order: f(0,0), f(0,1), ..., f(1,0), f(1,1), ..., Raises Size if n < 0 or m < 0.

[tabulate ColMajor (m, n, f)] returns a new m-by-n array whose elements are as above, but created in the column-major order: f(0,0), f(1,0), ..., f(0, 1), f(1, 1), ... Raises Size if n < 0 or m < 0.

[dimensions a] returns the dimensions (m, n) of a, where m is the number of rows and n the number of columns.

[nCols a] returns the number of n of columns of a.

[nRows a] returns the number of m of rows of a.

[sub(a, i, j)] returns the i'th row's j'th element, counting from 0. Raises Subscript if i < 0 or j < 0 or i >= m or j >= n where (m,n) = dimensions a.

[update(a, i, j, x)] destructively replaces the (i,j)'th element of a by x. Raises Subscript if i < 0 or j < 0 or i >= m or j >= n where (m,n) = dimensions a.

[row (a, i)] returns a vector containing the elements of the ith row of a. Raises Subscript if i < 0 or i >= height a.

[column (a, j)] returns a vector containing the elements of the jth column of a. Raises Subscript if j < 0 or j >= width a.

[app RowMajor f a] applies f to the elements a[0,0], a[0,1], ..., a[0, n-1], a[1,0], ..., a[m-1, n-1] of a, where (m, n) = dimensions a. [app ColMajor f a] applies f to the elements a[0,0], a[1,0], ..., a[n-1,0], a[0,1], a[1,1], ..., a[m-1, n-1] of a, where (m, n) = dimensions a.

[modify RowMajor f a] applies f to the elements a[0,0], a[0,1], ..., a[0, n-1], a[1,0], ..., a[m-1, n-1] of a, updating each element with the result of the application, where (m, n) = dimensions a.

[modify ColMajor f a] applies f to the elements a[0,0], a[1,0], ..., a[n-1,0] a[0,1], a[1,1], ..., a[m-1, n-1] of a, updating each element with the result of the application, where (m, n) = dimensions a.

[fold RowMajor f b a] folds f left-right and top-down over the elements of a in row-major order. That is, computes f(a[m-1, n-1], f(a[m-1, n-2], ..., f(a[0,1], f(a[0,0], b)) ...)) where (m, n) = dimensions a.

[fold ColMajor f b a] folds f left-right and top-down over the elements of a in column-major order. That is, computes f(a[m-1, n-1], f(a[m-2, n-1], ..., f(a[1,0], f(a[0,0], b)) ...)) where (m, n) = dimensions a.

The following iterators generalize the above ones in two ways:

- * the indexes i and j are also being passed to the function;
- * the iterators work on a region (submatrix) of a matrix.

[region] is the type of records {base, row, col, nRows, nCols} determining the region or submatrix of array base whose upper left corner has index (row, col).

If `nrows = SOME r`, then the region has `r` rows: `row, row+1, ..., row+r-1`. If `nrows = NONE`, then the region extends to the bottom of the matrix. The field `ncols` similarly determines the number of columns.

A region is valid for an array with dimensions `(m, n)` if

```
(1) either nrows = NONE and 0 <= row <= m
    or nrows = SOME r and 0 <= row <= row + r <= m
and (2) either ncols = NONE and 0 <= col <= n
    or ncols = SOME c and 0 <= col <= col + c <= n.
```

`[appi RowMajor f reg]` applies `f` to `(i, j, a[i, j])` in order of lexicographically increasing `(i, j)` within the region `reg`. Raises `Subscript` if `reg` is not valid. Note that `app tr f a` is equivalent to `appi tr (f o #3) {base=a, row=0, col=0, nrows=NONE, ncols=NONE}`

`[appi ColMajor f reg]` applies `f` to `(i, j, a[i, j])` in order of lexicographically increasing `(j, i)` within the region `reg`. Raises `Subscript` if `reg` is not valid.

`[modifyi RowMajor f reg]` applies `f` to `(i, j, a[i, j])` in order of lexicographically increasing `(i, j)` within the region `reg`. Raises `Subscript` if `reg` is not valid. Note that `modify tr f a` is equivalent to `modifyi (f o #3) {base=a, row=0, col=0, nrows=NONE, ncols=NONE}`.

`[modifyi ColMajor f reg]` applies `f` to `(i, j, a[i, j])` in order of lexicographically increasing `(j, i)` within the region `reg`. Raises `Subscript` if `reg` is not valid.

`[foldi RowMajor f b a]` folds `f` over `(i, j, a[i, j])` in row-major order within the region `reg`, that is, for lexicographically increasing `(i, j)` in the region. Raises `Subscript` if `reg` is not valid.

`[foldi ColMajor f b a]` folds `f` over `(i, j, a[i, j])` in column-major order within the region `reg`, that is, for lexicographically increasing `(j, i)` in the region. Raises `Subscript` if `reg` is not valid.

`[copy { src, dst, dst_col }]` copies the region determined by `src` to array `dst` such that the upper leftmost corner of `src` is copied to `dst[dst_row, dst_col]`. Works correctly even when `src` and `dst` are the same and the source and destination regions overlap. Raises `Subscript` if the `src` region is invalid, or if `src` translated to `(dst_row, dst_col)` is invalid for `dst`.

Module Arraysort

`Arraysort` -- Quicksort for arrays, from *SML/NJ Library*

```
val sort : ('a * 'a -> order) -> 'a Array.array -> unit
val sorted : ('a * 'a -> order) -> 'a Array.array -> bool
```

`[sort order arr]` sorts array `arr` in-place, using ordering relation `order`.
`[sorted order arr]` returns true if the elements of array `arr` is appear in (weakly) increasing order, according to ordering `order`.

Module BinIO

BinIO -- SML Basis Library

```
type elem = Word8.word
type vector = Word8Vector.vector
```

Binary input

```
type instream
```

```
val openIn      : string -> instream
val closeIn    : instream -> unit
val input      : instream -> vector
val inputAll   : instream -> vector
val inputNoBlock : instream -> vector option
val input1     : instream -> elem option
val inputN     : instream * int -> vector
val eofOfStream : instream -> bool
val lookahead  : instream -> elem option
```

Binary output

```
type ostream
```

```
val openOut    : string -> ostream
val openAppend : string -> ostream
val closeOut   : ostream -> unit
val output     : ostream * vector -> unit
val output1    : ostream * elem -> unit
val flushOut   : ostream -> unit
```

This structure provides input/output functions on byte streams. The functions are state-based: reading from or writing to a stream changes the state of the stream. The streams are buffered: output to a stream may not immediately affect the underlying file or device.

[instream] is the type of state-based byte input streams.

[ostream] is the type of state-based byte output streams.

[elem] is the type Word8.word of bytes.

[vector] is the type of Word8Vector.vector (byte vectors).

BYTE INPUT:

[openIn s] creates a new instream associated with the file named s. Raises Io.Io if file s does not exist or is not accessible.

[closeIn istr] closes stream istr. Has no effect if istr is closed already. Further operations on istr will behave as if istr is at end of stream (that is, will return "" or NONE or true).

[input istr] reads some elements from istr, returning a vector v of those elements. The vector will be empty (size v = 0) if and only if istr is at end of stream or is closed. May block (not return until data are available in the external world).

[inputAll istr] reads and returns the vector v of all bytes remaining in istr up to end of stream.

[inputNoBlock istr] returns SOME(v) if some elements v can be read without blocking; returns SOME("") if it can be determined without blocking that istr is at end of stream; returns NONE otherwise. If istr does not support non-blocking input, raises Io.NonblockingNotSupported.

[input1 istr] returns SOME(e) if at least one element e of istr is

available; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds.

[inputN(istr, n)] returns the next n bytes from istr as a vector, if that many are available; returns all remaining bytes if end of stream is reached before n bytes are available; blocks if necessary until one of these conditions holds.

[eofOfStream istr] returns false if any elements are available in istr; returns true if istr is at end of stream or closed; blocks if necessary until one of these conditions holds.

[lookahead istr] returns SOME(e) where e is the next element in the stream; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds. Does not advance the stream.

BYTE OUTPUT:

[openOut s] creates a new ostream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, it is truncated (any existing contents are lost).

[openAppend s] creates a new ostream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, any existing contents are retained, and output goes at the end of the file.

[closeOut ostr] closes stream ostr; further operations on ostr (except for additional close operations) will raise exception Io.Io.

[output(ostr, v)] writes the byte vector v on ostream ostr.

[output1(ostr, e)] writes the byte e on ostream ostr.

[flushOut ostr] flushes the ostream ostr, so that all data written to ostr becomes available to the underlying file or device.

The functions below are not yet implemented:

[setPosIn(istr, i)] sets istr to the position i. Raises Io.Io if not supported on istr.

[getPosIn istr] returns the current position of istr. Raises Io.Io if not supported on istr.

[endPosIn istr] returns the last position of istr.

[getPosOut ostr] returns the current position in stream ostr. Raises Io.Io if not supported on ostr.

[endPosOut ostr] returns the ending position in stream ostr. Raises Io.Io if not supported on ostr.

[setPosOut(ostr, i)] sets the current position in stream to ostr to i. Raises Io.Io if not supported on ostr.

[mkInstream sistr] creates a state-based instream from the functional instream sistr.

[getInstream istr] returns the functional instream underlying the state-based instream istr.

[setInstream(istr, sistr)] redirects istr, so that subsequent input is taken from the functional instream sistr.

[mkOutstream sostr] creates a state-based ostream from the ostream sostr.

[getOutstream ostr] returns the outstream underlying the state-based outstream ostr.

[setOutstream(ostr, sostr)] redirects the outstream ostr so that subsequent output goes to sostr.

Module Binarymap

Binarymap -- applicative maps as balanced ordered binary trees
 From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories
 Original implementation due to Stephen Adams, Southampton, UK

```

type ('key, 'a) dict
exception NotFound

val mkDict   : ('key * 'key -> order) -> ('key, 'a) dict
val insert  : ('key, 'a) dict * 'key * 'a -> ('key, 'a) dict
val find    : ('key, 'a) dict * 'key -> 'a option
val peek    : ('key, 'a) dict * 'key -> 'a option
val remove  : ('key, 'a) dict * 'key -> ('key, 'a) dict * 'a
val numItems : ('key, 'a) dict -> int
val listItems : ('key, 'a) dict -> ('key * 'a) list
val app      : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val revapp   : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val foldr    : ('key * 'a * 'b -> 'b) -> ('key, 'a) dict -> 'b
val foldl    : ('key * 'a * 'b -> 'b) -> ('key, 'a) dict -> 'b
val map      : ('key * 'a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict
val transform : ('a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict

```

[('key, 'a) dict] is the type of applicative maps from domain type 'key to range type 'a, or equivalently, applicative dictionaries with keys of type 'key and values of type 'a. They are implemented as ordered balanced binary trees.

[mkDict ostr] returns a new, empty map whose keys have ordering ostr.

[insert(m, i, v)] extends (or modifies) map m to map i to v.

[find (m, k)] returns v if m maps k to v; otherwise raises NotFound.

[peek(m, k)] returns SOME v if m maps k to v; otherwise returns NONE.

[remove(m, k)] removes k from the domain of m and returns the modified map and the element v corresponding to k. Raises NotFound if k is not in the domain of m.

[numItems m] returns the number of entries in m (that is, the size of the domain of m).

[listItems m] returns a list of the entries (k, v) of keys k and the corresponding values v in m, in order of increasing key values.

[app f m] applies function f to the entries (k, v) in m, in increasing order of k (according to the ordering ostr used to create the map or dictionary).

[revapp f m] applies function f to the entries (k, v) in m, in decreasing order of k.

[foldl f e m] applies the folding function f to the entries (k, v) in m, in increasing order of k.

[foldr f e m] applies the folding function f to the entries (k, v) in m, in decreasing order of k.

[map f m] returns a new map whose entries have form (k, f(k,v)), where (k, v) is an entry in m.

[transform f m] returns a new map whose entries have form (k, f v), where (k, v) is an entry in m.

Module Binaryset

Binaryset -- sets implemented by ordered balanced binary trees
 From *SMJ/NJ lib 0.2*, copyright 1993 by AT&T Bell Laboratories
 Original implementation due to Stephen Adams, Southampton, UK

```

type 'item set
exception NotFound

val empty      : ('item * 'item -> order) -> 'item set
val singleton  : ('item * 'item -> order) -> 'item -> 'item set
val add        : 'item set * 'item -> 'item set
val addlist   : 'item set * 'item list -> 'item set
val retrieve   : 'item set * 'item -> 'item option
val peek      : 'item set * 'item -> bool
val isEmpty   : 'item set -> bool
val equal     : 'item set * 'item set -> bool
val isSubset  : 'item set * 'item set -> bool
val member    : 'item set * 'item -> bool
val delete    : 'item set * 'item -> 'item set
val numItems  : 'item set -> int
val union     : 'item set * 'item set -> 'item set
val intersection : 'item set * 'item set -> 'item set
val difference : 'item set * 'item set -> 'item set
val listItems : 'item set -> 'item list
val app       : ('item -> unit) -> 'item set -> unit
val revapp    : ('item -> unit) -> 'item set -> unit
val foldr     : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val foldl     : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val find      : ('item -> bool) -> 'item set -> 'item option

```

`('item set)` is the type of sets of ordered elements of type `'item`.
 The ordering relation on the elements is used in the representation
 of the set. The result of combining two sets with different
 underlying ordering relations is undefined. The implementation
 uses ordered balanced binary trees.

`[empty ordx]` creates a new empty set with the given ordering
 relation.

`[singleton ordx i]` creates the singleton set containing `i`, with the
 given ordering relation.

`[add(s, i)]` adds item `i` to set `s`.

`[addlist(s, xs)]` adds all items from the list `xs` to the set `s`.

`[retrieve(s, i)]` returns `i` if it is in `s`; raises `NotFound` otherwise.

`[peek(s, i)]` returns `SOME i` if `i` is in `s`; returns `NONE` otherwise.

`[isEmpty s]` returns true if and only if the set is empty.

`[equal(s1, s2)]` returns true if and only if the two sets have the
 same elements.

`[isSubset(s1, s2)]` returns true if and only if `s1` is a subset of `s2`.

`[member(s, i)]` returns true if and only if `i` is in `s`.

`[delete(s, i)]` removes item `i` from `s`. Raises `NotFound` if `i` is not in `s`.

`[numItems s]` returns the number of items in set `s`.

`[union(s1, s2)]` returns the union of `s1` and `s2`.

`[intersection(s1, s2)]` returns the intersection of `s1` and `s2`.

`[difference(s1, s2)]` returns the difference between `s1` and `s2` (that
 is, the set of elements in `s1` but not in `s2`).

`[listItems s]` returns a list of the items in set `s`, in increasing
 order.

`[app f s]` applies function `f` to the elements of `s`, in increasing
 order.

`[revapp f s]` applies function `f` to the elements of `s`, in decreasing
 order.

`[foldl f e s]` applies the folding function `f` to the entries of the
 set in increasing order.

`[foldr f e s]` applies the folding function `f` to the entries of the
 set in decreasing order.

`[find p s]` returns `SOME i`, where `i` is an item in `s` which satisfies
`p`, if one exists; otherwise returns `NONE`.

Module Bool

Bool -- *SML Basis Library*

```
datatype bool = datatype bool
val not      : bool -> bool
val toString : bool -> string
val fromString : string -> bool option
val scan : (char, 'a) StringCvt.reader -> (bool, 'a) StringCvt.reader
```

[bool] is the type of Boolean (logical) values: true and false.

[not b] is the logical negation of b.

[toString b] returns the string "false" or "true" according as b is false or true.

[fromString s] scans a boolean b from the string s, after possible initial whitespace (blanks, tabs, newlines). Returns (SOME b) if s has a prefix which is either "false" or "true"; the value b is the corresponding truth value; otherwise NONE is returned.

[scan getc src] scans a boolean b from the stream src, using the stream accessor getc. In case of success, returns SOME(b, rst) where b is the scanned boolean value and rst is the remainder of the stream; otherwise returns NONE.

Module Byte

Byte -- *SML Basis Library*

```
val byteToChar      : Word8.word -> Char.char
val charToByte     : Char.char -> Word8.word
val bytesToString  : Word8Vector.vector -> String.string
val stringToBytes   : String.string -> Word8Vector.vector
val unpackStringVec : Word8Vector.vector * int * int option -> string
val unpackString   : Word8Array.array * int * int option -> string
val packString     : Substring.substring * Word8Array.array * int -> unit
```

Conversions between bytes and characters, and between byte vectors and strings (character vectors).

[byteToChar w] is the character corresponding to the byte w.

[charToByte c] is the byte corresponding to character c.

[bytesToString v] is the string whose character codes are the bytes from vector v.

[stringToBytes s] is the byte vector of character codes of the string s.

In Moscow ML, all the above operations take constant time. That is, no copying is done.

[unpackStringVec (v, i, NONE)] is the string whose character codes are the bytes of v[i..length v-1]. Raises Subscript if i<0 or i>length v. Equivalent to bytesToString(Word8Vector.extract (v, i, NONE)).

[unpackStringVec (v, i, SOME n)] is the string whose character codes are the bytes of v[i..i+n-1]. Raises Subscript if i<0 or n<0 or i+n>length v. Equivalent to bytesToString(Word8Vector.extract (v, i, SOME n)).

[unpackString (a, i, NONE)] is the string whose character codes are the bytes of a[i..length a-1]. Raises Subscript if i<0 or i>length a. Equivalent to bytesToString(Word8Array.extract (v, i, NONE)).

[unpackString (a, i, SOME n)] is the string whose character codes are the bytes of a[i..i+n-1]. Raises Subscript if i<0 or n<0 or i+n>length a. Equivalent to bytesToString(Word8Array.extract (a, i, SOME n)).

[packString (ss, a, i)] copies the character codes of substring ss into the subarray a[i..i+n-1] where n = Substring.size ss. Raises Subscript if i<0 or i+n > length a. Equivalent to Word8Array.copyVec(src=s, si=si, len=SOME n, dst=a, di=i) when (s, si, n) = Substring.base ss.

Module Callback

Callback -- registering ML values with C, and accessing C values from ML

Registering ML values for access from C code:

```
val register      : string -> 'a -> unit
val unregister   : string -> unit
val isRegistered : string -> bool
```

Accessing C variables and functions from ML:

```
type cptr
val getcptr : string -> cptr
val var     : cptr -> 'b
val app1    : cptr -> 'a1 -> 'b
val app2    : cptr -> 'a1 -> 'a2 -> 'b
val app3    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'b
val app4    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'b
val app5    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'a5 -> 'b
```

REGISTERING ML VALUES FOR ACCESS FROM C CODE

This example shows how to register the ML function (fn n => 2*n) so that it may be called from C code.

- ```
(0) The ML side registers the function:
 Callback.register "myfun" (fn n => 2*n)

(1) The C side first obtains an ML value pointer:
 valueptr mvp = get_valueptr("myfun");
```

- ```
(2) The C side then uses the ML value pointer to obtain an ML
    value, and uses it:
    callback(get_value(mvp), Val_long(42));
```

Operation (1) involves a callback to ML, and hence may be slow. Calling `get_valueptr` may cause the garbage collector to run; hence other live ML values must be registered as GC roots. The garbage collector will never move the ML value pointer; hence it need not be registered as a GC root in the C code.

Operation (2) is very fast. If the garbage collector is invoked between the call of `get_value()` and the use of the ML value, then the value must be registered as a GC root. However, the idiom `callback(get_value(mvp), arg1);` is safe provided the evaluation of `arg1` does not provoke a garbage collection (e.g. if `arg1` is a variable).

The C function `get_valueptr` returns NULL if `nam` is not registered.

The C function `get_value` returns NULL if `nam` has been unregistered (and not reregistered) since `mvp` was obtained; it raises exception `Fail` if `mvp` itself is NULL. Every access to the ML value from C code should use the ML valueptr and `get_valueptr`, otherwise the C code will not know when the value has been unregistered and possibly deallocated.

```
The C functions (in mosml/src/runtime/callback.c)
void registervalue(char* nam, value mlval)
void unregistervalue(char* nam)
can be used just as Callback.register and Callback.unregister.
```

```
The C functions
value callbackptr (valueptr mvp, value arg1)
value callbackptr2(valueptr mvp, value arg1, value arg2)
value callbackptr3(valueptr mvp, value arg1, value arg2, value arg3)
can be used for callback via an ML value pointer; they will raise
```

exception `Fail` if the ML function indicated by `mvp` has been unregistered.

[register nam v] registers the ML value `v`, so that it can be retrieved from C code under the name `nam`. If `nam` has previously been registered and then unregistered, it will be reregistered with the new value. The new value immediately becomes visible to the C side, both via `get_valueptr` and via any ML value pointer previously obtained for `nam`. Raises exception `Fail` if `nam` has been registered and not yet unregistered.

[unregister nam] deletes the registration. This prevents C code from obtaining an ML value pointer for `nam` and from using an ML value pointer already obtained (but does not prevent C from attempting to use a stored ML value previously obtained with the help of the ML value pointer, which is unsafe anyway). Does nothing if `nam` is already unregistered. Raises exception `Fail` if `nam` has never been registered.

[isRegistered nam] returns true if `nam` has been registered and not yet unregistered.

ACCESSING REGISTERED C VARIABLES AND FUNCTIONS FROM ML

This example shows how to register the C function

```
value silly_cfun(value v)
{ return copy_double(42.42 * Double_val(v)); }
```

so that it may be called from ML.

- ```
(0) The C side registers the function:
 registercptr("mycfun", silly_cfun);
```

- ```
(1) The ML side obtains a C pointer and defines an ML function
    via that pointer:
    val sillycfun = appl (getcptr "mycfun") : real -> real
    The type ascription is needed to ensure any type safety whatsoever.
    Mistakes in the types will lead to crashes, as usual with C.
```

- ```
(2) To the ML side, the new ML function is indistinguishable from
 other ML functions
 val result = sillyfun(3.4)
```

```
The C function (in mosml/src/runtime/callback.c)
void registercptr(char* nam, void* cptr);
```

is used to register C pointers for access from ML. Only pointers to static C variables, and C functions, should be registered. There is no way to unregister a C pointer.

[cptr] is the type of pointers to C variables and C functions.

[getcptr nam] returns a pointer to the C variable or function registered (by the C side) under the name `nam`. Raises exception `Fail` if the name `nam` has not been registered.

[var cptr] returns the value of the C variable associated with `cptr`.

[appl cptr arg1] applies the C function associated with `cptr` to `arg1`.

[app2 cptr arg1 arg2] applies the C function associated with `cptr` to (`arg1`, `arg2`).

[app3 cptr arg1 arg2 arg3] applies the C function associated with `cptr` to (`arg1`, `arg2`, `arg3`).

[app4 cptr arg1 arg2 arg3 arg4] applies the C function associated with `cptr` to (`arg1`, `arg2`, `arg3`, `arg4`).

[app5 cptr arg1 arg2 arg3 arg4 arg5] applies the C function associated with cptr to (arg1, arg2, arg3, arg4, arg5).

## Module Char

Char -- *SML Basis Library*

```

type char = char

val minChar : char
val maxChar : char
val maxOrd : int

val chr : int -> char
val ord : char -> int
val succ : char -> char
val pred : char -> char

val isLower : char -> bool
val isUpper : char -> bool
val isDigit : char -> bool
val isAlpha : char -> bool
val isHexDigit : char -> bool
val isAlphaNum : char -> bool
val isPrint : char -> bool
val isSpace : char -> bool
val isPunct : char -> bool
val isGraph : char -> bool
val isAscii : char -> bool
val isCtrl : char -> bool

val toLower : char -> char
val toUpper : char -> char

val fromString : string -> char option
val toString : char -> string

val fromCString : string -> char option
val toCString : char -> string

val contains : string -> char -> bool
val notContains : string -> char -> bool

val < : char * char -> bool
val <= : char * char -> bool
val > : char * char -> bool
val >= : char * char -> bool
val compare : char * char -> order

[chr] is the type of characters.
[minChar] is the least character in the ordering <.
[maxChar] is the greatest character in the ordering <.
[maxOrd] is the greatest character code; equals ord(maxChar).
[chr i] returns the character whose code is i. Raises Chr if
i < 0 or i > maxOrd.
[ord c] returns the code of character c.
[succ c] returns the character immediately following c, or raises
Chr if c = maxChar.
[pred c] returns the character immediately preceding c, or raises
Chr if c = minChar.
[isLower c] returns true if c is a lowercase letter (a to z).
[isUpper c] returns true if c is an uppercase letter (A to Z).
[isDigit c] returns true if c is a decimal digit (0 to 9).

```

```

[isAlpha c] returns true if c is a letter (lowercase or uppercase).
[isHexDigit c] returns true if c is a hexadecimal digit (0 to 9 or a to f or A to F).
[isAlphaNum c] returns true if c is alphanumeric (a letter or a decimal digit).
[isPrint c] returns true if c is a printable character (space or visible)
[isSpace c] returns true if c is a whitespace character (blank, newline, tab, vertical tab, new page).
[isGraph c] returns true if c is a graphical character, that is, it is printable and not a whitespace character.
[isPunct c] returns true if c is a punctuation character, that is, graphical but not alphanumeric.
[isCtrl c] returns true if c is a control character, that is, if not (isPrint c).
[isAscii c] returns true if 0 <= ord c <= 127.
[toLowerCase] returns the lowercase letter corresponding to c, if c is a letter (a to z or A to Z); otherwise returns c.
[toUpperCase] returns the uppercase letter corresponding to c, if c is a letter (a to z or A to Z); otherwise returns c.
[contains s c] returns true if character c occurs in the string s; false otherwise. The function, when applied to s, builds a table and returns a function which uses table lookup to decide whether a given character is in the string or not. Hence it is relatively expensive to compute val p = contains s but very fast to compute p(c) for any given character.
[notContains s c] returns true if character c does not occur in the string s; false otherwise. Works by construction of a lookup table in the same way as the above function.
[fromString s] attempts to scan a character or ML escape sequence from the string s. Does not skip leading whitespace. For instance, fromString "\\065" equals #A.
[toString c] returns a string consisting of the character c, if c is printable, else an ML escape sequence corresponding to c. A printable character is mapped to a one-character string: bell, backspace, tab, newline, vertical tab, form feed, and carriage return are mapped to the two-character strings "\a", "\b", "\t", "\n", "\v", "\f", and "\r"; other characters with code less than 32 are mapped to three-character strings of the form "\\>Z", and characters with codes 127 through 255 are mapped to four-character strings of the form "\\ddd", where ddd are three decimal digits representing the character code. For instance,
toString #A" equals "A"
toString #"\" equals "\"
toString #\" equals "\"
toString (chr 0) equals "\0"
toString (chr 1) equals "\0A"
toString (chr 6) equals "\0F"
toString (chr 7) equals "\0a"
toString (chr 8) equals "\0b"
toString (chr 9) equals "\0t"
toString (chr 10) equals "\n"
toString (chr 11) equals "\v"
toString (chr 12) equals "\f"
toString (chr 13) equals "\r"
toString (chr 14) equals "\N"
toString (chr 127) equals "\127"
toString (chr 128) equals "\128"

```

```

[fromCString s] attempts to scan a character or C escape sequence from the string s. Does not skip leading whitespace. For instance, fromCString "\\065" equals #A.
[toCString c] returns a string consisting of the character c, if c is printable, else an C escape sequence corresponding to c. A printable character is mapped to a one-character string; bell, backspace, tab, newline, vertical tab, form feed, and carriage return are mapped to the two-character strings "\a", "\b", "\t", "\n", "\v", "\f", and "\r"; other characters are mapped to four-character strings of the form "\\ooo", where ooo are three octal digits representing the character code. For instance,
toString #A" equals "A"
toString #"\" equals "\"
toString #\" equals "\"
toString (chr 0) equals "\\000"
toString (chr 1) equals "\\001"
toString (chr 6) equals "\\006"
toString (chr 7) equals "\\a"
toString (chr 8) equals "\\b"
toString (chr 9) equals "\\t"
toString (chr 10) equals "\\n"
toString (chr 11) equals "\\v"
toString (chr 12) equals "\\f"
toString (chr 13) equals "\\r"
toString (chr 14) equals "\\016"
toString (chr 127) equals "\\177"
toString (chr 128) equals "\\200"
[<]
[<=]
[>]
[>=] compares character codes. For instance, c1 < c2 returns true if ord(c1) < ord(c2), and similarly for <=, >, >=.
[compare(c1, c2)] returns LESS, EQUAL, or GREATER, according as c1 is precedes, equals, or follows c2 in the ordering Char.<

```

## Module CharArray

CharArray -- SML Basis Library

```

datatype array
type elem = Char.char
type vector = CharVector.vector

val maxLen : int
val array : int * elem -> array
val tabulate : int * (int -> elem) -> array
val fromList : elem list -> array

val length : array -> int
val sub : array * int -> elem
val update : array * int * elem -> array
val extract : array * int * int option -> vector

val copy : {src: array, si: int, len: int option,
 dst: array, di: int} -> unit
val copyVec : {src: vector, si: int, len: int option,
 dst: array, di: int} -> unit

val app : (elem -> unit) -> array -> unit
val foldl : (elem * 'b -> 'b) -> 'b -> array -> 'b
val foldr : (elem * 'b -> 'b) -> 'b -> array -> 'b
val modify : (elem -> elem) -> array -> unit

val appi : (int * elem -> unit) -> array * int * int option -> unit
val foldli : (int * elem * 'b -> 'b) -> 'b -> array * int * int option -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> array * int * int option -> 'b
val modifyi : (int * elem -> elem) -> array * int * int option -> unit

```

[array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type Char.char, that is, characters. Arrays a1 and a2 are equal if both were created by the same call to a primitive, or if both are empty.

All operations are as for Array.array.

## Module CharVector

CharVector -- SML Basis Library

```

type vector = string
type elem = Char.char

val maxLen : int
val fromList : elem list -> vector
val tabulate : int * (int -> elem) -> vector

val length : vector -> int
val sub : vector * int -> elem
val extract : vector * int * int option -> vector
val concat : vector list -> vector

val app : (elem -> unit) -> vector -> unit
val map : (elem -> elem) -> vector -> vector
val foldl : (elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldr : (elem * 'b -> 'b) -> 'b -> vector -> 'b

val appi : (int * elem -> unit) -> vector * int * int option -> unit
val mapi : (int * elem -> elem) -> vector * int * int option -> vector
val foldli : (int * elem * 'b -> 'b) -> 'b -> vector * int * int option -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> vector * int * int option -> 'b

```

[vector] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type Char.char, that is, characters. Type vector admits equality, and vectors v1 and v2 are equal if they have the same length and their elements are equal. The type vector is the same as String.string.

All operations are as for Vector.vector.

## Module CommandLine

*CommandLine* -- *SML Basis Library*

```
val name : unit -> string
val arguments : unit -> string list
```

[name ()] returns the name used to start the current process.

[arguments ()] returns the command line arguments of the current process.  
Hence List.nth(arguments (), 0) is the first argument.

## Module Date

*Date* -- *SML Basis Library*

```
datatype weekday = Mon | Tue | Wed | Thu | Fri | Sat | Sun
datatype month = Jan | Feb | Mar | Apr | May | Jun
 | Jul | Aug | Sep | Oct | Nov | Dec
```

type date

exception Date

```
val date : {
 year : int,
 month : month,
 day : int,
 hour : int,
 minute : int,
 second : int,
 offset : Time.time option
} -> date
 e.g. 1999
 Jan, Feb, ...
 1-31
 0-23
 0-59
 0-61, permitting leap seconds
 time zone west of UTC
```

```
val year : date -> int
val month : date -> month
val day : date -> int
val hour : date -> int
val minute : date -> int
val second : date -> int
val weekday : date -> weekday
val yearDay : date -> int
val isDST : date -> bool option
val offset : date -> Time.time option
```

```
val compare : date * date -> order
```

```
val toString : date -> string
```

```
val fmt : string -> date -> string
```

```
val fromString : string -> date option
```

```
val scan : (char, 'a) StringCvt.reader -> (date, 'a) StringCvt.reader
```

```
val fromTimeLocal : Time.time -> date
```

```
val fromTimeUniv : Time.time -> date
```

```
val toTime : date -> Time.time
```

```
val localOffset : unit -> Time.time
```

These functions convert times to dates and vice versa, and format and scan dates.

[date] is the type of points in time in a given time zone. If the offset is NONE, then the date is in the local time zone. If the offset is SOME t, then t is the offset of the main time zone (ignoring daylight savings time) west of UTC.

When 0 hours <= t < 12 hours, the represented time is to the west of UTC and the local time is UTC-t.  
When 12 hours <= t < 23 hours, the represented time is to the East of UTC and the local time is UTC+(24-t).

[date { year, month, day, hour, minute, second, offset }] returns a canonical date value. Seconds outside the range 0..59 are converted to the equivalent minutes and added to the minutes argument; leap seconds are ignored. Similarly, excess minutes are converted to hours, hours to days, days to months, and months to years. Then the weekday and day number in the year are computed. Leap years are assumed in accordance with the Gregorian calendar, for any year after year 0 A.D.

If the offset is greater than one day (24 hours), then the excess days are added to the days, and the offset modulo 24 hours is used.

```

[year dt] returns the year of dt, e.g. 1999.
[month dt] returns the month of dt.
[day dt] returns the day of dt
[hour dt] returns the hour of dt.
[minute dt] returns the minute of dt.
[second dt] returns the second of dt.
[weekDay dt] returns the weekday of dt.
[yearDay dt] returns the number of the day in the year of dt.
January 1 is day 0, and December 31 is day 364 (and 365 in leap years).
[isDst dt] returns SOME(true) if daylight savings time is in effect
at the date dt; returns SOME(false) if not; and returns NONE if
this information is unavailable.
[offset dt] returns NONE if the date dt is in the local time zone;
returns SOME t where t is the offset west of UTC otherwise. Thus
SOME(Time.zeroTime) is UTC.
[compare(dt1, dt2)] returns LESS, EQUAL, or GREATER, according as
date dt1 precedes, equals, or follows dt2 in time.
Lexicographically compares the dates. Ignores timezone offset and
DST. Does not detect invalid dates.
[toString dt] returns a 24 character string representing the date dt
in the following format:
 Wed Mar 8 19:06:45 1995
The result may be wrong if the date is not representable as a
Time.time value. Raises Date if dt is an invalid date.
Corresponds to the ANSI C function 'asctime'.
[fmt fmsStr dt] formats the date dt according to the format string
fmsStr. The format string has the same meaning as with the ANSI C
function 'strftime'. These ANSI C format codes should work on all
platforms:
%a abbreviated weekday name (e.g. "Mon")
%A full weekday name (e.g. "Monday")
%b abbreviated month name (e.g. "Oct")
%B full month name (e.g. "October")
%c date and time (e.g. "Dec 2 06:55:15 1979")
%d day of month (01..31)
%H hour (00..23)
%I hour (01..12)
%j day of year (001..366)
%m month number (01..12)
%M minutes (00..59)
%p locale's equivalent of a.m./p.m.
%S seconds (00..61, allowing for leap seconds)
%U week number (00..53), with Sunday as the first day of week 01
%w day of week, with 0 representing Sunday (0..6)
%W week number (00..53), with Monday as the first day of week 01
%x locale's appropriate date representation
%Y year of century (00..99)
%y year including century (e.g. 1997)
%Z time zone name if it exists; otherwise the empty string
%% the percent character

```

Example: The current local date in ISO format (e.g. 1998-04-06) can be obtained by using:

```
fmt "%Y-%m-%d" (fromTimeLocal (Time.now ()))
```

[fromString s] scans a 24-character date from the string s, after possible initial whitespace (blanks, tabs, newlines). The format of the string must be as produced by toString. The fields isDst and offset in the resulting date will be NONE. No check of the

consistency of the date (weekday, date in the month, ...) is performed.

[scan getc src] scans a 24-character date from the stream src, using the stream accessor getc. Otherwise works as fromString. In case of success, returns SOME(date, rst) where date is the scanned date and rst is the remainder of the stream; otherwise returns NONE.

[fromTimeLocal t] returns the local date at (UTC) time t. The resulting date will have offset = NONE. The fields year, month, day, hour, minute, and second are as expected. The resulting isDst may be NONE if the system cannot determine whether daylight savings time is in effect at the given time. Corresponds to the ANSI C function 'localtime'.

[fromTimeUTC t] is similar to fromTime, but returns the UTC date at (UTC) time t. The resulting date will have offset = SOME Time.zeroTime. Corresponds to the ANSI C function 'gmtime'.

[toTime dt] returns the (UTC) time corresponding to the date dt. Uses the isDst time field if it is present (SOME \_) and cannot be calculated from the given date. May raise Date if the given date is invalid. Raises Time.time if the Date cannot be represented as a Time.time value. At least the dates in the interval 1970-2030 can be represented as Time.time values. Corresponds to the ANSI C function 'mktime'.

[localOffset ()] is the local time zone offset west of UTC. It holds that 0 hours <= localOffset () < 24 hours.

## Module Dynarray

*Dynarray* -- polymorphic dynamic arrays a la SML/NJ library

```

type 'a array
val array : int * 'a -> 'a array
val subarray : 'a array * int * int -> 'a array
val fromList : 'a list * 'a -> 'a array
val tabulate : int * (int -> 'a) * 'a -> 'a array
val sub : 'a array * int -> 'a
val update : 'a array * int * 'a -> unit
val default : 'a array -> 'a
val bound : 'a array -> int

['ty array] is the type of one-dimensional, mutable, zero-based
unbounded arrays with elements of type 'ty. Type 'ty array does
not admit equality.

[array(n, d)] returns a dynamic array, all of whose elements are
initialized to the default d. The parameter n is used as a hint of the
upper bound on non-default elements. Raises Size if n < 0.

[subarray(a, m, n)] returns a new array with the same default
value as a, and whose values in the range [0..n-m) equal the
values in a in the range [m..n]. Raises the exception Size if n < m.

[fromList(xs, d)] returns an array whose first elements are
those of [xs], and the rest are the default d.

[tabulate(n, f, d)] returns a new array whose first n elements
are f 0, f 1, ..., f (n-1), created from left to right, and whose
remaining elements are the default d. Raises Size if n < 0.

[sub(a, i)] returns the i'th element of a, counting from 0.
Raises Subscript if i < 0.

[update(a, i, x)] destructively replaces the i'th element of a by x.
Raises Subscript if i < 0.

[default a] returns the default value of the array a.

[bound a] returns an upper bound on the indices of non-default values.

```

## Module Dynlib

*Dynlib* -- dynamic linking with foreign functions

```

type dHandle
type symHandle

exception Closed

datatype flag = RTLD_LAZY | RTLD_NOW
val dlopen : { lib : string, flag : flag, global : bool } -> dHandle
val dlsym : dHandle -> string -> symHandle
val dlclose : dHandle -> unit

val var : symHandle -> 'b
val appl1 : symHandle -> 'a1 -> 'b
val appl2 : symHandle -> 'a1 -> 'a2 -> 'b
val appl3 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'b
val appl4 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'b
val appl5 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'a5 -> 'b

```

Structure Dynlib provides dynamic loading and calling of C functions, using the dlopen interface. A dynamic library is a collection of symbols (C variables and functions).

An ML value passed to or returned from a symbol has type 'value' as defined in `src/runtime/mlvalues.h`. The C functions should use the macros defined there to access and produce ML values. When writing a C function, remember that the garbage collector may be activated whenever you allocate an ML value. Also, remember that the garbage collector may move values from the young heap to the old one, so that a C pointer pointing into the ML heap may need to be updated. Use the `Push_roots` and `Pop_roots` macros to achieve this.

[`dHandle`] is the type of dynamic library handles. A dynamic library handle is created by opening a dynamic library using `dlopen`. This will load the library into the runtime system. The dynamic library handle is used for accessing symbols in that library. The library may be closed and removed from the runtime system using `dlclose`.

The same library may be opened more than once, resulting in different library handles. The physical library will be loaded only once, though, and will remain in the runtime system until all handles to the library have been closed.

[`symHandle`] is the type of symbol handles. A symbol handle is used to access a symbol (variable or function) in the dynamic library, using the functions `var`, `appl`, `appl2`, ..., `appl5`. Type safety is the responsibility of the programmer; the runtime system performs no type checking. Hence you are advised to add explicit types whenever you define an ML function in terms of `var`, `appl`, ..., `appl5`.

How to create a dynamically loadable library

-----

To compile `xyz.c` into `xyz.o` and then create a dynamic library `libxyz.so` from `xyz.o`:

```

Under Linux and OSF/1 (Digital Unix):
gcc -c -o xyz.o xyz.c
ld -shared -o libxyz.so xyz.o
Under Solaris (ignore the warnings from ld):
gcc -c -o xyz.o xyz.c
ld -G -B symbolic -z nodefs -o libxyz.so xyz.o
Under HP-UX:
gcc -fPIC -c -o xyz.o xyz.c
ld -b -B symbolic -E -o libxyz.so xyz.o

```



If "xyz.o" depends on another library "libabc.a" you may link the required functions into libxyz.so just by adding -labc or libabc.a to the above linker command.

If "xyz.o" depends on another dynamic library "libabc.so" you may specify this by adding -labc to the above linker command. Then Dynlib.dlopen will automatically load libabc.so before libxyz.so.

[dlopen { lib, flag, global }] will load and open the library in file 'lib', returning a handle to it. Libraries are usually specified just by file name, leaving out the directory path. Linux/Unix-specific information: Libraries are searched for in those directories mentioned in LD\_LIBRARY\_PATH, those mentioned in /etc/ld.so.cache, in /usr/lib and /lib. (Note that /etc/ld.so.cache is created from /etc/ld.so.conf by running ldconfig; you must be superuser to do that).

If 'global' is true, then the library's global symbols are made available for other libraries subsequently loaded.

[flag] is the type of library loading modes: RTLD\_LAZY and RTLD\_NOW.

[RTLD\_LAZY] specifies that only symbol relocations will be performed when calling dlopen, whereas function relocations will be performed later when a function is invoked for the first time (if ever). This is the normal situation.

[RTLD\_NOW] specifies that all function relocations must be performed immediately, also for functions that will never be called. This checks that all functions are defined, but may waste some time.

[disym dlh nam] returns a symbol handle for the symbol called 'nam' in the library associated with dlh. Raises Closed if dlh has been closed.

[dclose dlh] closes the library handle and deallocates the library if there are no more open handles to this library.

The following functions raise Closed if the associated handle has been closed.

[var sym] returns the value of the C variable associated with sym.

[app1 sym arg1] applies the C function associated with sym to arg1.

[app2 sym arg1 arg2] applies the C function associated with sym to (arg1, arg2).

[app3 sym arg1 arg2 arg3] applies the C function associated with sym to (arg1, arg2, arg3).

[app4 sym arg1 arg2 arg3 arg4] applies the C function associated with sym to (arg1, arg2, arg3, arg4).

[app5 sym arg1 arg2 arg3 arg4 arg5] applies the C function associated with sym to (arg1, arg2, arg3, arg4, arg5).

## Module FileSys

OS.FileSys -- SML Basis Library

```

type dirstream
val opendir : string -> dirstream
val readdir : dirstream -> string option
val rewindDir : dirstream -> unit
val closeDir : dirstream -> unit
val chdir : string -> unit
val getDir : unit -> string
val mkDir : string -> unit
val rmdir : string -> unit
val isDir : string -> bool
val realPath : string -> string
val fullPath : string -> string
val isLink : string -> bool
val readLink : string -> string
val modTime : string -> Time.time
val setTime : string * Time.time option -> unit
val remove : string -> unit
val rename : {old: string, new: string} -> unit
datatype access = A_READ | A_WRITE | A_EXEC
val access : string * access list -> bool
val fileSize : string -> int
val tmpName : unit -> string
eqtype file_id
val fileId : string -> file_id
val hash : file_id -> word
val compare : file_id * file_id -> order

```

These functions operate on the file system. They raise OS.SysErr in case of errors.

[opendir p] opens directory p and returns a directory stream for use by readdir, rewindDir, and closeDir. Subsequent calls to readdir will return the directory entries in some unspecified order.

[readDir dstr] returns SOME(s), consuming an entry s from the directory stream if it is non-empty; returns NONE if it is empty (when all directory entries have been read). Only entries distinct from the parent arc and the current arc (that is, .. and . in Unix, DOS, and Windows; see the Path structure) will be returned.

[rewindDir dstr] resets the directory stream as if it had just been opened.

[closeDir dstr] closes the directory stream. All subsequent operations on the stream will raise OS.SysErr.

[chdir p] changes the current working directory to p. This affects calls to the functions use, load, compile in the interactive system, as well as all functions defined in this library. If p specifies a volume name, then this command also changes the current volume (relevant under DOS, Windows, OS/2, etc.).

[getDir ()] returns the name of the current working directory.

[mkDir p] creates directory p on the file system.

[rmdir p] removes directory p from the file system.

```

[isDir p] tests whether p is a directory.

[fullPath p] returns a canonical form of path p, where all
occurrences of the arcs ".", ".", ".", "." have been expanded or
removed, and (under Unix) symbolic links have been fully expanded.
Raises SysErr if a directory on the path, or the file or directory
named, does not exist or is not accessible, or if there is a link
loop.

[realPath p] behaves as fullPath(p) if p is absolute. If p is
relative and on the same volume as the current working directory,
it returns a canonical path relative to the current working
directory, where superfluous occurrences of the arcs ".", ".", "."
have been removed, and (under Unix) symbolic links have been fully
expanded. Raises SysErr if a directory on the path, or the file or
directory named, does not exist or is not accessible, or if there
is a link loop. Raises Path if p is relative and on a different
volume than the current working directory.

[isLink p] returns true if p names a symbolic link. Raises SysErr
if the file does not exist or there is an access violation. On
operating systems without symbolic links, it returns false, or
raises SysErr if the file does not exist or there is an access
violation.

[readLink p] returns the contents of the symbolic link p. Raises
SysErr if p does not exist or is not a symbolic link, or there is
an access violation. On operating systems without symbolic links,
it raises SysErr.

[modTime p] returns the modification time of file p.

[setTime (p, tmopt)] sets the modification and access time of file
p. If tmopt is SOME t, then the time t is used; otherwise the
current time, that is, Time.now(), is used.

[remove p] deletes file p from the file system.

[rename {old, new}] changes the name of file 'old' to 'new'.

[access] is the type of access permissions:

[A_READ] specifies read access.
[A_WRITE] specifies write access.
[A_EXEC] specifies permission to execute the file (or directory).

[access (p, accs)] tests the access permissions of file p,
expanding symbolic links as necessary. If the list accs of
required access permission is empty, it tests whether p exists. If
accs contains A_READ, A_WRITE, or A_EXEC, respectively, it tests
whether the user process has read, write, or execute permission for
the file.
 Under Unix, the access test is done with the 'real' user
 id and group id (as opposed to the 'effective' user id and group
 id) of the user process. Hence access('file', [A_READ]) may return
 false, yet the file may be readable by the process, in case the
 effective user id or group id has been changed by setuid.

[fileSize p] return the size, in bytes, of the file p. Raises SysErr
if p does not exist or its directory is not accessible.

[tmpName ()] returns a file name suitable for creating a fresh
temporary file. Note that there is no guarantee that the file name
will be unique, since a file of that name may be created between
the call to tmpName and a subsequent call to openOut which creates
the file. The file name will be absolute, usually of the form
/tmp/xxxxxxx provided by POSIX tmpnam (3).

[file_id] is the type of unique identities of file system objects
(device ids and volume ids, but possibly insensitive to

```

```

volume changes on removable volumes, such as tapes and diskettes).
The set of file ids is equipped with a total linear order.

[fileId p] returns the file_id of the file system object named by
path p. It holds that fileId p1 = fileId p2 if and only if p1 and
p2 name the same file system object.

[hash fid] returns a hashvalue for fid, suitable for use in a
hashtable of file ids (and hence files).
If fid1 = fid2 then hash fid1 = hash fid2.

[compare (fid1, fid2)] returns LESS, EQUAL, or GREATER, according
as fid1 precedes, equals, or follows fid2 in the total linear order
on file ids. This is suitable for e.g. an ordered binary tree of
file ids (and hence files).

```

## Module Gdbm

Gdbm -- GNU gdbm persistent string hashtables -- requires Dynlib

```

type table
datatype openmode =
 READER
 | WRITER
 | WRCREAT
 | NEWDB
type datum = string
exception NotFound
exception AlreadyThere
exception NotWriter
exception Closed
exception GdbmError of string
val withtable : string * openmode -> (table -> 'a) -> 'a
val withtables : (string * openmode) list -> (table list -> 'a) -> 'a
val add : table -> datum * datum -> unit
val insert : table -> datum * datum -> unit
val find : table -> datum -> datum
val peek : table -> datum -> datum option
val haskey : table -> datum -> bool
val remove : table -> datum -> unit
val listkeys : table -> datum list
val numitems : table -> int
val listitems : table -> (datum * datum) list
val app : (datum * datum -> unit) -> table -> unit
val map : (datum * datum -> 'a) -> table -> 'a list
val fold : (datum * datum * 'a) -> 'a -> table -> 'a
val fastwrite : bool ref
val reorganize : table -> unit

```

[table] is the type of an opened table. A value of type table can be used only in the argument f to the withtable function. This makes sure that the table is closed after use.

[openmode] is the type of opening modes. Read-only access (READER) is non-exclusive; read/write access (WRITER, WRCREAT, NEWDB) is exclusive.

[withtable (nam, mod) f] first opens the table db in file nam with mode mod, then applies f to db, then closes db. Makes sure to close db even if an exception is raised during the evaluation of f(db). Raises GdbmError with an informative message in case the table cannot be opened. E.g. the table cannot be opened for reading if already opened for writing, and cannot be opened for writing if already opened for reading.

A table is only guaranteed to work properly if created by withtable using open modes WRCREAT or NEWDB. If you create a table by creating and then opening an empty file, then numItems, listKeys, listItems, etc. will raise an exception.

```

[withtables nammod f], where nammod = [(nam1, mod1), ..., (namn, modn)],
is equivalent to
withtable (nam1, mod1) (fn db1 =>
 withtable (nam2, mod2) (fn db2 =>
 ... f (db1, db2, ...)))

```

That is, first opens the databases db1, db2, ... in that order in files nam1, nam2, ... with modes mod1, mod2, ..., then applies f to [db1, db2, ...], and finally closes [db1, db2, ...]. Makes sure to close all databases even if an exception is raised during the opening of db1, db2, ... or during the evaluation of f([db1, db2, ...]).

[add db (k,v)] adds the pair (k, v) to db. Raises AlreadyThere if there is a pair (k, \_) in db already. Raises NotWriter if db is not opened in write mode.

[insert db (k, v)] adds the pair (k, v) to db, replacing any pair (k, \_) at k if present. Raises NotWriter if db is not opened in write mode.

[find db k] returns v if the pair (k, v) is in db; otherwise raises NotFound.

[peek db k] returns SOME v if the pair (k, v) is in db; otherwise returns NONE.

[haskey db k] returns true if there is a pair (k, \_) in db; otherwise returns false.

[remove db k] deletes the pair (k, \_) from the table if present; otherwise raises NotFound. Raises NotWriter if db is not opened in write mode.

[listKeys db] returns a list of all keys in db in an unspecified order.

[numItems db] is the number of (key, value) pairs in db. Equivalent to length(listKeys db).

[listItems db] returns a list of all (key, value) pairs in db in some order. Equivalent to

```
List.map (fn key => (key, find(db,key))) (listKeys db)
```

[app f db] is equivalent to List.app f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the effect is unpredictable.

[map f db] is equivalent to List.map f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fold f a db] is equivalent to List.foldr (fn ((k, v), r) => f(k, v, r)) a (listItems db) provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fastwrite] can be set to speed up writes to a table. By default, !fastwrite is false and every write to a table will be followed by file system synchronization. This is safe, but slow if you perform thousands of writes. However, if !fastwrite is true when calling withtable, then writes may not be followed by synchronization, which may speed up writes considerably. In any case, the file system is synchronized before withtable returns.

[reorganize db] has no visible effect, but may be called after a lot of deletions to shrink the size of the table file.

## Module Gdimage

*Gdimage* -- creating PNG images -- requires Dynlib

```

type image
type color

datatype style =
 | Colors of color
 | Transparents

datatype mode =
 | Color of color
 | Transparent
 | Brushed of image
 | Styled of style vector
 | StyledBrushed of bool vector * image
 | Tiled of image

datatype font =
 | Tiny
 | Small
 | MediumBold
 | Large
 | Giant

type rgb = int * int * int RGB color components, 0..255
type xy = int * int points (x, y) and sizes (w, h)

val image : xy -> rgb -> image
val fromPng : string -> image
val toPng : image -> string -> unit
val stdoutPng : image -> unit
val size : image -> xy

val color : image -> rgb -> color
val rgb : image -> color -> rgb
val htmlColors : image -> {
 aqua : color, black : color, blue : color,
 fuchsia : color, gray : color,
 green : color, lime : color, maroon : color,
 navy : color, olive : color, purple : color,
 red : color, silver : color, teal : color,
 white : color, yellow : color }

val getTransparent : image -> color option
val setTransparent : image -> color -> unit
val noTransparent : image -> unit

val drawPixel : image -> mode -> xy -> unit
val drawLine : image -> mode -> xy * xy -> unit
val drawRect : image -> mode -> xy * xy -> unit
val fillRect : image -> mode -> xy * xy -> unit
val drawPolygon : image -> mode -> xy vector -> unit
val fillPolygon : image -> mode -> xy vector -> unit
val drawArc : image -> mode -> { c : xy, wh : xy, from : int, to : int }
-> unit
val fill : image -> mode -> xy -> unit
val fillBorder : image -> mode -> xy -> color -> unit

val copy : { src : image, srcxy : xy, srcwh : xy,
 dst : image, dstxy : xy } -> unit
val copy/Resize : { src : image, srcxy : xy, srcwh : xy,
 dst : image, dstxy : xy, dstwh : xy } -> unit

val char : image -> color -> font -> char -> unit
val charUp : image -> color -> font -> xy -> char -> unit
val string : image -> color -> font -> xy -> string -> unit
val stringUp : image -> color -> font -> xy -> string -> unit
val charsize : font -> xy

```

This is an interface to version 1.7.3 of Thomas Boutell's gd image package for creating PNG images.

[image] is the type of images being drawn. They can be created from scratch, imported from PNG files, and exported to PNG files.

All functions correctly clip to the actual size of the image.

[color] is the type of colors. Currently there can be at most 256 different colors in an image.

[style] is the type of drawing styles. A style is either a color, or transparent.

[mode] is the type of drawing modes for line drawing and filling.

It may be one of

Color c where c is a color

Transparent

Brushed img

Styled stys

StyledBrushed (vis, img)

for line drawing, using the given image as brush, cyclically switching it on and off according to the given bool vector

for filling, using the given image as a tile

Tiled img

[font] is the type of fonts: Tiny, Small, MediumBold, Large, Giant

[rgb] is the type of (r, g, b) triples, where the components indicate color intensity as an integer value in the range 0..255.

[xy] is the type of pairs, used for (x, y) coordinates and to indicate dimensions (width, height). The origin (0, 0) is the upper-left-hand corner of the image. The x coordinates increase to the right; the y coordinates increase downwards.

[image (w, h) rgb] creates a new empty image with size (w, h) and the background color rgb. Raises Fail if the image cannot be created.

[fromPng filename] reads an image from the given PNG file. Raises Fail if the file does not exist or does not contain a PNG image.

[size img] returns (w, h) where w is the width and h the height of img.

[toPng img filename] write the image to the given file in PNG format.

[stdoutPng img] writes the image to standard output in PNG format, preceded by the HTTP header "Content-type: image/png\n\n". Useful in CGI scripts.

[color img rgb] returns the color code corresponding to rgb in the color table of img. Reuses the color code if it has already been allocated; otherwise allocates the color. If possible, otherwise returns an approximation to the color rgb.

[htmlColors im] returns a record containing the 16 standard HTML colors: aqua, black, blue, fuchsia, gray, green, lime, maroon, navy, olive, purple, red, silver, teal, white, yellow. This call will allocate all these colors in the color table of the image, even if you do not use all of them.

[rgb img color] returns (r, g, b) where r, g, b are the component intensities of the given color in the color table of img.

[getTransparent img] returns SOME c where c is the 'transparent' color of the image, if any; otherwise returns NONE.

[setTransparent img col] makes the given color transparent in the

image.

[noTransparent img] makes all colors non-transparent in the image. This is useful for images that are to be used as tiles for filling. Such images are not allowed to have a transparent color.

[drawPixel img mode xy] draws the pixel in img at xy using the given mode.

[drawLine img mode {xy1, xy2}] draws a line in img from xy1 to xy2 using the given mode.

[drawRect img mode {xy1, xy2}] draws a rectangle in img with opposing corners xy1 and xy2 using the given mode.

[fillRect img mode {xy1, xy2}] draws a filled rectangle in img with opposing corners xy1 and xy2 using the given mode.

[drawPolygon img mode xys] draws a polygon in img with corners as given by the vector xys of coordinates using the given mode.

[fillPolygon img mode xys] draws a filled polygon in img with corners as given by the vector xys of coordinates using the given mode.

[drawArc img mode { c, wh, from, to }] draw part of an ellipse in img, with center c, width and height wh, using the given 'from' and 'to' angles, given in degrees (0..360).

[fill img mode xy] fills the region in img around xy which has the same color as the point at img, using the given mode.

[fillBorder img mode xy col] fills the region in img around xy which is delimited by the color col, using the given mode.

[copy { src, srcxy, srcwh, dst, dstxy }] copies part of the image src into the image dst, without rescaling. More precisely, copies the subimage of src whose upper left-hand corner is srcxy and whose size is srcwh, into the subimage of dst whose upper left-hand corner is dstxy. The images src and dst may be the same, but if the subimages overlap, then the result is unpredictable.

[copyResize { src, srcxy, srcwh, dst, dstxy, dstwh }] copies part of the image src into the image dst, rescaling to the given size dstwh of the destination subimage. Otherwise works as copy.

[char img col font xy ch] draws the character ch left-right (to be read from south) in img at xy using the given color.

[charUp img col font xy ch] draws the character ch bottom-up (to be read from east) in img at xy using the given color.

[string img col font xy s] draws the string s left-right (to be read from south) in img at xy using the given color.

[stringUp img col font xy s] draws the string s bottom-up (to be read from east) in img at xy using the given color.

[charsize font] returns (w, h) where w is the width and h the height, in pixels, of each character in the given font.

## Module General

*SML Basis Library and Moscow ML top-level declarations*

*SML Basis Library types*

```
type exn
datatype unit
datatype order = LESS | EQUAL | GREATER
```

*Additional Moscow ML top-level types*

```
datatype bool = false | true
datatype char
datatype int
datatype 'a option = NONE | SOME of 'a
type ppstream
datatype real
datatype string
type substring
type syserror
type 'a vector
datatype word8
datatype 'a list = nil | op :: of 'a * 'a list
datatype 'a ref = ref of 'a
datatype 'a frag = QUOTE of string | ANTIQUOTE of 'a
```

*SML Basis Library exceptions*

```
exception Bind
exception Chr
exception Div
exception Domain
exception Fail of string
exception Match
exception Overflow
exception Subscript
exception Size

Additional Moscow ML top-level exceptions

exception Graphic of string
exception Interrupt
exception Invalid_argument of string
exception Io of {function : string, name : string, cause : exn }
exception Out_of_memory
exception SysErr of string * syserror option
```

*SML Basis Library values*

```
val ! : 'a ref -> 'a
val := : 'a ref * 'a -> unit
val o : ('b -> 'c) * ('a -> 'b) -> ('a -> 'c)
val ignore : 'a -> unit
val before : 'a * 'b -> 'a
val exnName : exn -> string
val exnMessage : exn -> string

Additional Moscow ML top-level values

val not : bool -> bool
val ^ : string * string -> string
val = : "a * "a -> bool
val <> : "a * "a -> bool
val ceil : real -> int
val floor : real -> int
val real : int -> real
 : round towards plus infinity
 : round towards minus infinity
 : equals Real.FromInt
```

```

val round : real -> int
val trunc : real -> int

val vector : 'a list -> 'a vector

Below, numtxt is int, Word.word, Word8.word, real, char, string:

val < : numtxt * numtxt -> bool
val = : numtxt * numtxt -> bool
val > : numtxt * numtxt -> bool
val >= : numtxt * numtxt -> bool

val makestring : numtxt -> string

Below, realint is int or real:

val ~ : realint -> realint
val abs : realint -> realint
raises Overflow

Below, num is int, Word.word, Word8.word, or real:

val + : num * num -> num
val - : num * num -> num
val * : num * num -> num
val / : real * real -> real
raises Overflow

Below, wordint is int, Word.word or Word8.word:

val div : wordint * wordint -> wordint
val mod : wordint * wordint -> wordint
raises Div

```

[exn] is the type of exceptions.

[unit] is the type containing the empty tuple () which equals the empty record {}.

[order] is used as the return type of comparison functions.

[bool] is the type of booleans: false and true. Equals Bool.bool.

[char] is the type of characters such as #"A". Equals Char.char.

[int] is the type of integers. Equals Int.int.

[option] is the type of optional values. Equals Option.option.

[ppstream] is the type of pretty-printing streams. see structure PP. Pretty-printers may be installed in the top-level by function Meta.installPP; see the Moscow ML Owner's Manual.

[real] is the type of floating-point numbers. Equals Real.real.

[string] is the type of character strings. Equals String.string.

[substring] is the type of substrings. Equals Substring.substring.

[syserror] is the abstract type of system error codes. Equals OS.syserror.

[vector] is the type of immutable vectors. Equals Vector.vector.

[word] is the type of unsigned words. Equals Word.word.

[word8] is the type of unsigned bytes. Equals Word8.word.

['a list] is the type of lists of elements of type 'a. Equals List.list.

['a ref] is the type of mutable references to values of type 'a.

['a frag] is the type of quotation fragments, resulting from the

parsing of quotations ' ... ' and antiquotations. See the Moscow ML Owner's Manual.

[Bind] is the exception raised when the right-hand side value in a valbind does not match the left-hand side pattern.

[Chr] signals an attempt to produce an unrepresentable character.

[Div] signals an attempt to divide by zero.

[Domain] signals an attempt to apply a function outside its domain of definition; such as computing Math.sqrt(-1).

[Fail] signals the failure of some function, usually in the Moscow ML specific library structures.

[Match] signals the failure to match a value against the patterns in a case, handle, or function application.

[Overflow] signals the attempt to compute an unrepresentable number.

[Subscript] signals the attempt to use an illegal index in an array, dynarray, list, string, substring, vector or weak array.

[Size] signals the attempt to create an array, string or vector that is too large for the implementation.

[Graphic] signals the failure of Graphics primitives (DOS only).

[Interrupt] signals user interrupt of the computation.

[Invalid\_argument] signals the failure of a function in the runtime system.

[Io { function, name, cause }] signals the failure of an input/output operation (function) when operating on a file (name). The third field (cause) may give a reason for the failure.

[Out\_of\_memory] signals an attempt to create a data structure too large for the implementation, or the failure to extend the heap or stack.

[SysErr (msg, err)] signals a system error, described by msg. A system error code may be given by err. If so, it will usually hold that msg = OS.errorMsg err.

SMU Basis Library values

[! rf] returns the value pointed to by reference rf.

[:=(rf, e)] evaluates rf and e, then makes the reference rf point to the value of e. Since := has infix status, this is usually written rf := e

[o(f, g)] computes the functional composition of f and g, that is, fn x => f(g x). Since o has infix status, this is usually written f o g

[ignore e] evaluates e, discards its value, and returns () : unit.

[before(e1, e2)] evaluates e1, then evaluates e2, then returns the value of e1. Since before has infix status, this is usually written e1 before e2

[exnName exn] returns a name for the exception constructor in exn. Never raises an exception itself. The name returned may be that of any exception constructor aliasing with exn. For instance, let exception E1; exception E2 = E1 in exnName E2 end may evaluate to "E1" or "E2".

[exnMessage exn] formats and returns a message corresponding to

exception `exp`. For the exceptions defined in the SML Basis Library, the message will include the argument carried by the exception.

Additional Moscow ML top-level values

`[not b]` returns the logical negation of `b`.

`[^]` is the string concatenation operator.

`[=]` is the polymorphic equality predicate.

`[<]` is the polymorphic inequality predicate.

`[ceil r]` is the smallest integer  $\geq r$  (rounds towards plus infinity). May raise `Overflow`.

`[floor r]` is the largest integer  $\leq r$  (rounds towards minus infinity). May raise `Overflow`.

`[real i]` is the floating-point number representing integer `i`. Equivalent to `Real.fromInt`.

`[round r]` is the integer nearest to `r`, using the default rounding mode. May raise `Overflow`.

`[trunc r]` is the numerically largest integer between `r` and zero (rounds towards zero). May raise `Overflow`.

`[vector [x1, ..., xn]]` returns the vector `#[x1, ..., xn]`.

```
[< (x1, x2)]
[<= (x1, x2)]
[> (x1, x2)]
[>= (x1, x2)]
```

These are the standard comparison operators for arguments of type `int`, `Word.word`, `Word8.word`, `real`, `char` or `string`.

`[makestring v]` returns a representation of value `v` as a string, for `v` of type `int`, `Word.word`, `Word8.word`, `real`, `char` or `string`.

`[~ x]` is the numeric negation of `x` (which can be `real` or `int`). May raise `Overflow`.

`[abs x]` is the absolute value of `x` (which can be `real` or `int`). May raise `Overflow`.

```
[+ (e1, e2)]
[- (e1, e2)]
[* (e1, e2)]
```

These are the standard arithmetic operations for arguments of type `int`, `Word.word`, `Word8.word`, and `real`. They are unsigned in the case of `Word.word` and `Word8.word`. May raise `Overflow`.

`[/ (e1, e2)]` is the floating-point result of dividing `e1` by `e2`. May raise `Div` and `Overflow`.

`[div(e1, e2)]` is the integral quotient of dividing `e1` by `e2` for arguments of type `int`, `Word.word`, and `Word8.word`. See `Int.div` and `Word.div` for more details. May raise `Div`, `Overflow`.

`[mod(e1, e2)]` is the remainder when dividing `e1` by `e2`, for arguments of type `int`, `Word.word`, and `Word8.word`. See `Int.mod` and `Word.mod` for more details. May raise `Div`.

## Module Help

`Help` -- on-line help functions

```
val help : string -> unit
val displayLines : int ref
val helpdirs : string list ref
val indexfiles : string list ref
val specialfiles : {term : string, file : string, title : string} list ref
val welcome : string vector ref
val browser : (string -> unit) ref
val defaultBrowser : string -> unit
```

`[help s]` provides on-line help on the topic indicated by string `s`.

`help "lib";` gives an overview of the Moscow ML library.  
`help "id";` provides help on identifier `id` (case-insensitive).

If exactly one identifier in the library matches `id` (case-insensitive), then the browser opens the signature defining that identifier, positioning the first occurrence of `id` at the center of the screen.

If more than one identifier matches `id` (case-insensitive), then a small menu lists the signatures containing the identifier. To invoke the browser, just type in the number of the desired signature.

The browser accepts the following commands, which must be followed by a newline:

```
d move down by half a screen
u move up by half a screen
t move to top of file
b move to bottom of file
/str cyclically search for string str in help file (case-insensitive)
n search for next occurrence of str
q quit the browser
```

A newline by itself moves down one screen (24 lines).

`[helpdirs]` is a reference to a list of additional directories to be searched for help files. The directories are searched in order, after the `-stdlib` directory.

`[indexfiles]` is a reference to a list of full paths of help term index files. Setting `'indexfiles'` affects subsequent invocations of `'help'`. (Every invocation of `'help'` reads the index files anew).

`[specialfiles]` is a reference to a list of `{term, file, title}` records, each of which maps a search term to the specified file with the specified title (in the browser). The string in the `'term'` field should be all lowercase, since the argument passed to `'help'` will be converted to lowercase.

`[welcome]` is a reference to the text shown in response to the query `help ""`. This is a vector of lines of text.

`[browser]` is a reference to the function that gets invoked on the text of the help file. Initially set to `defaultBrowser`.

`[defaultBrowser]` is the default (built-in) help browser.

`[displayLines]` is a reference to the size of the display (window) assumed by the `defaultBrowser`; initially 24 lines. Set it to the actual size of your window for best results.

## Module Int

Int -- SML Basis Library

type int = int

val precision : int option  
val minInt : int option  
val maxInt : int option

val ~ : int -> int  
val \* : int \* int -> int  
val div : int \* int -> int  
val mod : int \* int -> int  
val quot : int \* int -> int  
val rem : int \* int -> int  
val + : int \* int -> int  
val - : int \* int -> int  
val > : int \* int -> bool  
val >= : int \* int -> bool  
val < : int \* int -> bool  
val <= : int \* int -> bool  
val abs : int -> int  
val min : int \* int -> int  
val max : int \* int -> int

val sign : int -> int  
val sameSign : int \* int -> bool  
val compare : int \* int -> order

val toInt : int -> int  
val fromInt : int -> int  
val toLarge : int -> int  
val fromLarge : int -> int

val scan : StringCvt.radix  
-> (char, 'a) StringCvt.reader -> (int, 'a) StringCvt.reader  
val fmt : StringCvt.radix -> int -> string  
val toString : int -> string  
val fromString : string -> int option Overflow

[precision] is SOME n, where n is the number of significant bits in an integer. In Moscow ML n is 31 in 32-bit architectures and 63 in 64-bit architectures.

[minInt] is SOME n, where n is the most negative integer.

[maxInt] is SOME n, where n is the most positive integer.

[~]

[\*]

[+]

[-] are the usual operations on integers. They raise Overflow if the result is not representable as an integer.

[abs] returns the absolute value of its argument. Raises Overflow if applied to the most negative integer.

[div] is integer division, rounding towards minus infinity.

Evaluating i div 0 raises Div. Evaluating i div ~1 raises

Overflow if i is the most negative integer.

[mod] is the remainder for div. If q = i div d and r = i mod d then it holds that qd + r = i, where either 0 <= r < d or d < r <= 0. Evaluating i mod 0 raises Div, whereas i mod ~1 = 0, for all i.

[quot] is integer division, rounding towards zero. Evaluating quot(i, 0) raises Div. Evaluating quot(i, ~1) raises Overflow if i is the most negative integer.

[rem(i, d)] is the remainder for quot. That is, if q = quot(i, d) and r = rem(i, d) then d \* q + r = i, where r is zero or has the same sign as i. If made infix, the recommended fixity for quot and rem is

```
infix 7 quot rem
```

[min(x, y)] is the smaller of x and y.

[max(x, y)] is the larger of x and y.

[sign x] is ~1, 0, or 1, according as x is negative, zero, or positive.

[<]

[<=]

[>]

[>=] are the usual comparisons on integers.

[compare(x, y)] returns LESS, EQUAL, or GREATER, according as x is less than, equal to, or greater than y.

[sameSign(x, y)] is true iff sign x = sign y.

[toInt x] is x (because this is the default int type in Moscow ML).

[fromInt x] is x (because this is the default int type in Moscow ML).

[toLarge x] is x (because this is the largest int type in Moscow ML).

[fromLarge x] is x (because this is the largest int type in Moscow ML).

[fmt radix i] returns a string representing i, in the radix (base) specified by radix.

| radix | description                  | output format |
|-------|------------------------------|---------------|
| BIN   | signed binary (base 2)       | ~?[01]+       |
| OCT   | signed octal (base 8)        | ~?[0-7]+      |
| DEC   | signed decimal (base 10)     | ~?[0-9]+      |
| HEX   | signed hexadecimal (base 16) | ~?[0-9A-F]+   |

[toString i] returns a string representing i in signed decimal format. Equivalent to (fmt DEC i).

[fromString s] returns SOME(i) if a decimal integer numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. A decimal integer numeral must have form, after possible initial whitespace:

```
[+~]?[0-9]+
```

[scan radix getc charsrc] attempts to scan an integer numeral from the character source charsrc, using the accessor getc, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns SOME(i, rest) where i is the value of the number scanned, and rest is the unused part of the character source. A numeral must have form, after possible initial whitespace:

| radix | input format      |
|-------|-------------------|
| BIN   | [+~]?[0-1]+       |
| OCT   | [+~]?[0-7]+       |
| DEC   | [+~]?[0-9]+       |
| HEX   | [+~]?[0-9A-FA-F]+ |



## Module Intmap

*Intmap* -- *Applicative maps with integer keys*  
 From *SWL/NJ lib 0.2*, copyright 1993 by AT&T Bell Laboratories  
 Original implementation due to Stephen Adams, Southampton, UK

```

type 'a intmap
exception NotFound

val empty : 'a intmap
val insert : 'a intmap * int * 'a -> 'a intmap
val retrieve : 'a intmap * int -> 'a option
val peek : 'a intmap * int -> 'a option
val remove : 'a intmap * int -> 'a intmap * 'a
val numItems : 'a intmap -> int
val listItems : 'a intmap -> (int * 'a) list
val app : (int * 'a -> unit) -> 'a intmap -> unit
val revapp : (int * 'a -> unit) -> 'a intmap -> unit
val foldr : (int * 'a * 'b -> 'b) -> 'b -> 'a intmap -> 'b
val foldl : (int * 'a * 'b -> 'b) -> 'b -> 'a intmap -> 'b
val map : (int * 'a -> 'b) -> 'a intmap -> 'b intmap
val transform : ('a -> 'b) -> 'a intmap -> 'b intmap

['a intmap] is the type of applicative maps from int to 'a.
[empty] creates a new empty map.
[insert(m, i, v)] extends (or modifies) map m to map i to v.
[retrieve(m, i)] returns v if m maps i to v; otherwise raises
NotFound.
[peek(m, i)] returns SOME v if m maps i to v; otherwise NONE.
[remove(m, i)] removes i from the domain of m and returns the
modified map and the element v corresponding to i. Raises NotFound
if i is not in the domain of m.
[numItems m] returns the number of entries in m (that is, the size
of the domain of m).
[listItems m] returns a list of the entries (i, v) of integers i and
the corresponding values v in m, in increasing order of i.
[app f m] applies function f to the entries (i, v) in m, in
increasing order of i.
[revapp f m] applies function f to the entries (i, v) in m, in
decreasing order of i.
[foldl f e m] applies the folding function f to the entries (i, v)
in m, in increasing order of i.
[foldr f e m] applies the folding function f to the entries (i, v)
in m, in decreasing order of i.
[map f m] returns a new map whose entries have form (i, f(i,v)),
where (i, v) is an entry in m.
[transform f m] returns a new map whose entries have form (i, f(i,v)),
where (i, v) is an entry in m.

```

## Module Intset

*Intset* -- *applicatives sets of integers*  
 From *SWL/NJ lib 0.2*, copyright 1993 by AT&T Bell Laboratories  
 Original implementation due to Stephen Adams, Southampton, UK

```

type intset
exception NotFound

val empty : intset
val singleton : int -> intset
val add : intset * int -> intset
val addList : intset * int list -> intset
val isEmpty : intset -> bool
val isEqual : intset * intset -> bool
val isSubset : intset * intset -> bool
val member : intset * int -> bool
val delete : intset * int -> intset
val numItems : intset -> int
val union : intset * intset -> intset
val intersection : intset * intset -> intset
val difference : intset * intset -> intset
val listItems : intset -> int list
val app : (int -> unit) -> intset -> unit
val revapp : (int -> unit) -> intset -> unit
val foldr : (int * 'b -> 'b) -> 'b -> intset -> 'b
val foldl : (int * 'b -> 'b) -> 'b -> intset -> 'b
val find : (int -> bool) -> intset -> int option

[intset] is the type of sets of integers.
[empty] is the empty set of integers.
[singleton i] is the singleton set containing i.
[add(s, i)] adds item i to set s.
[addList(s, xs)] adds all items from the list xs to the set s.
[isEmpty s] returns true if and only if the set is empty.
[isEqual(s1, s2)] returns true if and only if the two sets have the
same elements.
[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.
[member(s, i)] returns true if and only if i is in s.
[delete(s, i)] removes item i from s. Raises NotFound if i is not in s.
[numItems s] returns the number of items in set s.
[union(s1, s2)] returns the union of s1 and s2.
[intersection(s1, s2)] returns the intersection of s1 and s2.
[difference(s1, s2)] returns the difference between s1 and s2 (that
is, the set of elements in s1 but not in s2).
[listItems s] returns a list of the items in set s, in increasing
order.
[app f s] applies function f to the elements of s, in increasing
order.
[revapp f s] applies function f to the elements of s, in decreasing
order.
[foldl f e s] applies the folding function f to the entries of the
set in increasing order.

```

[foldr f e s] applies the folding function f to the entries of the set in decreasing order.  
 [find p s] returns SOME i, where i is an item in s which satisfies p, if one exists; otherwise returns NONE.

## Module Lexing

*Lexing -- run-time library for lexers generated by mosmllex  
 Closely based on the library for camllex. Copyright 1993 INRIA, France*

local open Obj in

```

type lexbuf
val createLexerString : string -> lexbuf
val createLexer : (CharArray.array -> int -> int) -> lexbuf
val getLexeme : lexbuf -> string
val getLexemeChar : lexbuf -> int -> char
val getLexemeStart : lexbuf -> int
val getLexemeEnd : lexbuf -> int

For internal use in generated lexers:

val dummyAction : lexbuf -> obj
val backtrack : lexbuf -> 'a
val prim_val_getNextChar : lexbuf -> char = 1 "get_next_char"
val prim_val_getLexBuffer : lexbuf -> string = 1 "field1"
val prim_val_getLexAbsPos : lexbuf -> int = 1 "field2"
val prim_val_getLexStartPos : lexbuf -> int = 1 "field3"
val prim_val_getLexCurrPos : lexbuf -> int = 1 "field4"
val prim_val_getLexLastPos : lexbuf -> int = 1 "field5"
val prim_val_getLexLastAction : lexbuf -> obj = 1 "field6"
val prim_val_setLexAbsPos : lexbuf -> int -> unit = 2 "setfield2"
val prim_val_setLexStartPos : lexbuf -> int -> unit = 2 "setfield3"
val prim_val_setLexCurrPos : lexbuf -> int -> unit = 2 "setfield4"
val prim_val_setLexLastPos : lexbuf -> int -> unit = 2 "setfield5"
val prim_val_setLexLastAction : lexbuf -> obj -> unit = 2 "setfield6"
end

```

These functions are for use in mosmllex-generated lexers. For further information, see the Moscow ML Owner's Manual. For examples, see mosml/examples/lex yacc and mosml/examples/calcc.

[lexbuf] is the type of lexer buffers. A lexer buffer is the argument passed to the scanning functions defined by the mosmllex-generated scanners. The lexer buffer holds the current state of the scanner, plus a function to refill the buffer from the input.

[createLexerString s] returns a lexer buffer which reads from the given string s. Reading starts from the first character in the string. An end-of-input condition is generated when the end of the string is reached.

[createLexer f] returns a lexer buffer that will use the given function f for reading additional input. When the lexer needs more characters, it will call the given function as (f carr n), where carr is a character array, and n is an integer. The function should put at most characters or in carr, starting at character number 0, and return the number of characters actually stored. A return value of 0 means end of input.

A lexer definition (input to mosmllex) consists of fragments of this form

```

parse
 lhs1 { rhs1 }
 | lhs2 { rhs2 }
 | lhs3 { rhs3 }
 ...

```

where the lhs are regular expressions matching some string of

characters, and the rhs are corresponding semantic actions, written in ML. The following functions can be used in the semantic actions:

[getLexeme lexbuf] returns the string matched by the left-hand side regular expression.

[getLexemeChar lexbuf i] returns character number *i* in the matched string.

[getLexemeStart lexbuf] returns the start position of the matched string (in the input stream). The first character in the stream has position 0.

[getLexemeEnd lexbuf] returns the end position, plus one, of the matched string (in the input stream). The first character in the stream has position 0.

## Module List

List -- *SML Basis Library*

datatype list = datatype list

exception Empty

```
val null : 'a list -> bool
val hd : 'a list -> 'a
val tl : 'a list -> 'a list
val last : 'a list -> 'a
```

```
val nth : 'a list * int -> 'a
val take : 'a list * int -> 'a list
val drop : 'a list * int -> 'a list
```

```
val length : 'a list -> int
```

```
val rev : 'a list -> 'a list
```

```
val @ : 'a list * 'a list -> 'a list
```

```
val concat : 'a list list -> 'a list
```

```
val revAppend : 'a list * 'a list -> 'a list
```

```
val app : ('a -> unit) -> 'a list -> unit
```

```
val map : ('a -> 'b) -> 'a list -> 'b list
```

```
val mapPartial : ('a -> 'b option) -> 'a list -> 'b list
```

```
val find : ('a -> bool) -> 'a list -> 'a option
```

```
val filter : ('a -> bool) -> 'a list -> 'a list
```

```
val partition : ('a -> bool) -> 'a list -> ('a list * 'a list)
```

```
val foldr : ('a * 'b -> 'b) -> 'b -> 'a list -> 'b
```

```
val foldl : ('a * 'b -> 'b) -> 'b -> 'a list -> 'b
```

```
val exists : ('a -> bool) -> 'a list -> bool
```

```
val all : ('a -> bool) -> 'a list -> bool
```

```
val tabulate : int * (int -> 'a) -> 'a list
```

```
val getItem : 'a list -> ('a * 'a list) option
```

---

[*'a list*] is the type of lists of elements of type *'a*.

[null xs] is true iff xs is nil.

[hd xs] returns the first element of xs. Raises Empty if xs is nil.

[tl xs] returns all but the first element of xs. Raises Empty if xs is nil.

[last xs] returns the last element of xs. Raises Empty if xs is nil.

[nth(xs, i)] returns the *i*'th element of xs, counting from 0. Raises Subscript if *i*<0 or *i*>length xs.

[take(xs, i)] returns the first *i* elements of xs. Raises Subscript if *i*<0 or *i*>length xs.

[drop(xs, i)] returns what is left after dropping the first *i* elements of xs. Raises Subscript if *i*<0 or *i*>length xs. It holds that take(xs, i) @ drop(xs, i) = xs when 0 ≤ *i* ≤ length xs.

[length xs] returns the number of elements in xs.

[rev xs] returns the list of xs's elements, reversed.

[xs @ ys] returns the list which is the concatenation of xs and ys.

[concat xss] returns the list which is the concatenation of all the

```

lists in xs.

[revAppend(xs, ys)] is equivalent to rev xs @ ys, but more efficient.

[app f xs] applies f to the elements of xs, from left to right.

[map f xs] applies f to each element x of xs, from left to right, and returns the list of f's results.

[mapPartial f xs] applies f to each element x of xs, from left to right, and returns the list of those y's for which f(x) evaluated to SOME y.

[find p xs] applies f to each element x of xs, from left to right until p(x) evaluates to true; returns SOME x if such an x exists otherwise NONE.

[filter p xs] applies p to each element x of xs, from left to right, and returns the sublist of those x for which p(x) evaluated to true.

[partition p xs] applies p to each element x of xs, from left to right, and returns a pair (pos, neg) where pos is the sublist of those x for which p(x) evaluated to true, and neg is the sublist of those for which p(x) evaluated to false.

[foldr op% e xs] evaluates x1 % (x2 % (... % (x(n-1) % (xn % e)) ...)) where xs = [x1, x2, ..., x(n-1), xn], and % is taken to be infix.

[foldl op% e xs] evaluates xn % (x(n-1) % (... % (x2 % (x1 % e)))) where xs = [x1, x2, ..., x(n-1), xn], and % is taken to be infix.

[exists p xs] applies p to each element x of xs, from left to right until p(x) evaluates to true; returns true if such an x exists, otherwise false.

[all p xs] applies p to each element x of xs, from left to right until p(x) evaluates to false; returns false if such an x exists, otherwise true.

[tabulate(n, f)] returns a list of length n whose elements are f(0), f(1), ..., f(n-1), created from left to right. Raises Size if n<0.

[getItem xs] attempts to extract an element from the list xs. It returns NONE if xs is empty, and returns SOME (x, xr) if xs=x::xr. This can be used for scanning booleans, integers, reals, and so on from a list of characters. For instance, to scan a decimal integer from a list cs of characters, compute

Int.scan StringCvt.DEC List.getItem cs

```

## Module ListPair

ListPair -- SML Basis Library

```

val zip : 'a list * 'b list -> ('a * 'b) list
val unzip : ('a * 'b) list -> 'a list * 'b list
val map : ('a * 'b -> 'c) -> 'a list * 'b list -> 'c list
val app : ('a * 'b -> unit) -> 'a list * 'b list -> unit
val all : ('a * 'b -> bool) -> 'a list * 'b list -> bool
val exists : ('a * 'b -> bool) -> 'a list * 'b list -> bool
val foldr : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c
val foldl : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c

```

These functions process pairs of lists. No exception is raised when the lists are found to be of unequal length. Instead the excess elements from the longer list are disregarded.

[zip (xs, ys)] returns the list of pairs of corresponding elements from xs and ys.

[unzip xys] returns a pair (xs, ys), where xs is the list of first components of xys, and ys is the list of second components from xys. Hence zip (unzip xys) has the same result and effect as xys.

[map f (xs, ys)] applies function f to the pairs of corresponding elements of xs and ys and returns the list of results. Hence map f (xs, ys) has the same result and effect as List.map f (zip (xs, ys)).

[app f (xs, ys)] applies function f to the pairs of corresponding elements of xs and ys and returns (). Hence app f (xs, ys) has the same result and effect as List.app f (zip (xs, ys)).

[all p (xs, ys)] applies predicate p to the pairs of corresponding elements of xs and ys until p evaluates to false or one or both lists is exhausted; returns true if p is true of all such pairs; otherwise false. Hence all p (xs, ys) has the same result and effect as Lisp.all p (zip (xs, ys)).

[exists p (xs, ys)] applies predicate p to the pairs of corresponding elements of xs and ys until p evaluates to true or one or both lists is exhausted; returns true if p is true of any such pair; otherwise false. Hence exists p (xs, ys) has the same result and effect as Lisp.exists p (zip (xs, ys)).

```

[foldr f e (xs, ys)] evaluates f(x1, y1, f(x2, y2, f(..., f(xn, yn, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
 ys = [y1, y2, ..., y(n-1), yn, ...],
and n = min(length xs, length ys).
Equivalent to List.foldr (fn (x, y), r) => f(x, y, r) e (zip(xs, ys)).

```

```

[foldl f e (xs, ys)] evaluates f(xn, yn, f(..., f(x2, y2, f(x1, y1, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
 ys = [y1, y2, ..., y(n-1), yn, ...],
and n = min(length xs, length ys).
Equivalent to List.foldl (fn (x, y), r) => f(x, y, r) e (zip(xs, ys)).

```

## Module Listsort

*Listsort*

```
val sort : ('a * 'a -> order) -> 'a list -> 'a list
val sorted : ('a * 'a -> order) -> 'a list -> bool
```

[sort ordr xs] sorts the list xs in nondecreasing order, using the given ordering. Uses Richard O'Keefe's smooth applicative merge sort.

[sorted ordr xs] checks that the list xs is sorted in nondecreasing order, in the given ordering.

## Module Location

*Location* -- error reporting for mosmllex and mosmlyac  
 Based on src/compiler/location from the Caml Light 0.6 distribution

```
datatype location = Source file positions
 loc of int Position of the first character
 * int Position of the character following the last one

val errLocation : string * BasicIO.instream * Lexing.lexbuf -> Location
 -> unit
val errMsg : string * BasicIO.instream * Lexing.lexbuf -> Location
 -> string -> 'a
val errPrompt : string -> unit
val nilLocation : Location
val getCurrentLocation : unit -> Location
val mkLoc : 'a -> Location * 'a
val xLR : Location * 'a -> Location
val xL : Location * 'a -> int
val xR : Location * 'a -> int
val xxLR : Location * 'a -> Location * 'b -> Location
val xxRL : Location * 'a -> Location * 'b -> Location
```

These functions support error reporting in lexers and parsers generated with mosmllex and mosmlyac. The directory mosml/examples/lex yacc/ contains an example of their use.

[errLocation (file, stream, lexbuf) loc] prints the part of the lexer input which is indicated by location loc.

If file <> "" then it is assumed to be the name of the file from which the lexer reads, the stream is assumed to be an open input stream associated with this file, and lexbuf is the lexer buffer used to read from the stream. Under MS DOS (and presumably Windows, OS/2, and MacOS), the stream must have been opened in binary mode (with Nonstdio.open\_bin), or else the positioning in the file will be wrong (due to the translation of CRLF into newline in text files).

If file = "" then the lexer is assumed to read from some source other than a stream, and the lexbuf (rather than the instream) is used to obtain the location indicated, if possible. In this case the stream is immaterial; it will not be used.

[errMsg (file, stream, lexbuf) loc msg] calls errLocation to print the indicated part of the lexer input, then prints the error message msg and raises exception Fail.

[errPrompt msg] prints "! ", the string msg, and a newline on standard output.

[nilLocation] is the undefined location.

[getCurrentLocation ()] can be called within the semantic action part of a grammar rule (only) and returns the location of the string matching the left-hand side of the rule.

[mkLoc a] can be called within the semantic action part of a grammar rule (only), and returns a pair (loc, a) of the current location and the value a. This is typically used to decorate abstract syntax tree nodes with location information, for use in subsequent error reports.

[xLR loc\_a] returns the location of the decorated value loc\_a.

[xL loc\_a] returns the left end position of loc\_a.

[xR loc\_a] returns the right end position of loc\_a.

[xxLR loc\_a loc\_b] returns the location extending from the left end of loc\_a to the right end of loc\_b.

[xxRL loc\_a loc\_b] returns the location extending from the right end of loc\_a to the left end of loc\_b.

## Module Math

Math -- *SML Basis Library*

```

type real = real

val pi : real
val e : real

val sqrt : real -> real
val sin : real -> real
val cos : real -> real
val tan : real -> real
val atan : real -> real
val asin : real -> real
val acos : real -> real
val atan2 : real * real -> real
val exp : real -> real
val pow : real * real -> real
val ln : real -> real
val log10 : real -> real
val sinh : real -> real
val cosh : real -> real
val tanh : real -> real

[pi] is the circumference of the circle with diameter 1, that is,
3.14159265358979323846.

[e] is the base of the natural logarithm: 2.7182818284590452354.

[sqrt x] is the square root of x. Raises Domain if x < 0.0.

[sin r] is the sine of r, where r is in radians.

[cos r] is the cosine of r, where r is in radians.

[tan r] is the tangent of r, where r is in radians. Raises Domain if
r is a multiple of pi/2.

[atan t] is the arc tangent of t, in the open interval] -pi/2, pi/2 [.

[asin t] is the arc sine of t, in the closed interval [-pi/2, pi/2].
Raises Domain if abs x > 1.

[acos t] is the arc cosine of t, in the closed interval [0, pi].
Raises Domain if abs x > 1.

[atan2(y, x)] is the arc tangent of y/x, in the interval] -pi, pi],
except that atan2(y, 0) = sign y * pi/2. The quadrant of the result
is the same as the quadrant of the point (x, y).
Hence sign(cos(atan2(y, x))) = sign x
and sign(sin(atan2(y, x))) = sign y.

[exp x] is e to the x'th power.

[pow (x, y)] is x to the y'th power, defined when
y >= 0 and (y integral or x >= 0)
or y < 0 and ((y integral and x < 0.0) or x > 0).

We define pow(0, 0) = 1.

[ln x] is the natural logarithm of x (that is, with base e).
Raises Domain if x <= 0.0.

[log10 x] is the base-10 logarithm of x. Raises Domain if x <= 0.0.

[sinh x] returns the hyperbolic sine of x, mathematically defined as
(exp x - exp (-x)) / 2. Raises Overflow if x is too large.

[cosh x] returns the hyperbolic cosine of x, mathematically defined as
(exp x + exp (-x)) / 2. Raises Overflow if x is too large.

```

[tanh x] returns the hyperbolic tangent of x, mathematically defined as  $(\sinh x) / (\cosh x)$ . Raises Domain if x is too large.

## Module Meta

Meta -- functions available only in interactive Moscow ML sessions

```

val printVal : 'a -> 'a
val printDepth : int ref
val printLength : int ref
val installPP : (ppstream -> 'a -> unit) -> unit

val liberal : unit -> unit
val conservative : unit -> unit
val orthodox : unit -> unit

val use : string -> unit
val compile : string -> unit
val compileTopLevel : string list -> string -> unit
val compileStructure : string list -> string -> unit

val load : string -> unit
val loadOne : string -> unit
val loaded : unit -> string list
val loadPath : string list ref

val quietdec : bool ref
val verbose : bool ref

val quotation : bool ref
val valuepoly : bool ref

val quit : unit -> 'a

```

These values and functions are available in the Moscow ML interactive system only.

```

[printVal e] prints the value of expression e to standard output exactly as it would be printed at top-level, and returns the value of e. Output is flushed immediately. This function is provided as a simple debugging aid. The effect of printVal is similar to that of 'print' in Edinburgh ML or Umeaa ML. For string arguments, the effect of SML/NJ print can be achieved by the function TextIO.print : string -> unit.

[printDepth] determines the depth (in terms of nested constructors, records, tuples, lists, and vectors) to which values are printed by the top-level value printer and the function printVal. The components of the value whose depth is greater than printDepth are printed as '#'. The initial value of printDepth is 20. This value can be changed at any moment, by evaluating, for example,
 printDepth := 17;

[printLength] determines the way in which list values are printed by the top-level value printer and the function printVal. If the length of a list is greater than printLength, then only the first printLength elements are printed, and the remaining elements are printed as '...'. The initial value of printLength is 200. This value can be changed at any moment, by evaluating, for example,
 printLength := 500;

[quit ()] quits Moscow ML immediately.

[installPP pp] installs the prettyprinter pp : ppstream -> ty -> unit at type ty. The type ty must be a nullary (parameter-less) type constructor representing a datatype, either built-in (such as bool) or user-defined. Whenever a value of type ty is about to be printed by the interactive system, or function printVal is invoked on an argument of type ty, the pretty-printer pp will be invoked to print it. See library unit pp for more information.

[use "f"] causes ML declarations to be read from file f as if they were entered from the console. A file loaded by use may, in turn, evaluate calls to use. For best results, use 'use' only at top

```

level, or at top level within a use'd file.

[liberal ()] sets liberal mode for the compilation functions: accept (without warnings) all extensions to the SML Modules language. The extensions are: higher-order modules (functions defined within structures and functors); first-order modules (structures can be packed as values, and values can be unpacked as structures); and recursively defined modules (signatures and structures). The liberal, conservative, and orthodox modes affect the functions compile, compileStructure, and compileTopLevel. The liberal mode may be set also by the mosml option -liberal.

[conservative ()] sets conservative mode for the compilation functions: accept all extensions to the SML Modules language, but issue a warning for each use. The conservative mode may be set also by the mosml option -conservative. This is the default.

[orthodox ()] sets orthodox mode for the compilation functions: reject all uses of the extensions to the SML Modules language. That is, accept only SML Modules syntax. The orthodox mode may be set also by the mosml option -orthodox.

[compile "U.sig"] will compile and elaborate the specifications in file U.sig in structure mode, producing a compiled signature U in file U.ui. This function is backwards compatible with Moscow ML 1.44 and earlier. Equivalent to compileStructure [] "U.sig".

[compile "U.sml"] will elaborate and compile the declarations in file U.sml in structure mode, producing a compiled structure U in bytecode file U.uo. If there is an explicit signature file U.sig, then file U.ui must exist, and the unit body must match the signature. If there is no U.sig, then an inferred signature file U.ui will be produced also. No evaluation takes place. This function is backwards compatible with Moscow ML 1.44 and earlier. Equivalent to compileStructure [] "U.sml".

The declared identifiers will be reported if verbose is true (see below); otherwise compilation will be silent. In any case, compilation warnings are reported, and compilation errors about the compilation and raise the exception Fail with a string argument.

[compileStructure opunits "U.sig"] compiles the specifications in file U.sig as if they form a signature declaration  
signature U = sig ... contents of U.sig ... end  
The contents of opunits is added to the compilation context in which the specifications in U.sig are compiled. The result is a compiled signature file U.ui. This  
corresponds to invoking the batch compiler as follows:  
mosmic -c U1.ui ... Un.ui -structure U.sig  
where opunits equals ["U1", ..., "Un"].

[compileStructure opunits "U.sml"] compiles the declarations in file U.sml as if they formed a structure declaration  
structure U = struct ... contents of U.sml ... end  
The contents of opunits is added to the compilation context in which the declarations in U.sml are compiled. If U.ui exists already and represents a signature called U, then the compiled declarations are matched against it. The result is a bytecode file U.uo. If no file U.ui existed, then also a file U.ui is created, containing the inferred signature of structure U. This  
corresponds to invoking the batch compiler as follows:  
mosmic -c U1.ui ... Un.ui -structure U.sml  
where opunits equals ["U1", ..., "Un"].

[compileTopLevel opunits "U.sig"] compiles the specifications in file U.sig, in a context in which all declarations from opunits are visible, creating a compiled signature file U.ui. This  
corresponds to invoking the batch compiler as follows:  
mosmic -c U1.ui ... Un.ui -toplevel U.sig  
where opunits equals ["U1", ..., "Un"].

[compileTopLevel opunits "U.sml"] compiles the declarations in

file U.sml, in a context in which all declarations from opunits are visible, creating a bytecode file U.uo. If U.ui exists already, then the compiled declarations are matched against it; otherwise the file U.ui is created. This corresponds to invoking the batch compiler as follows

```
mosmic -c U1.ui ... Un.ui -toplevel U.sml
```

where opunits equals ["U1", ..., "Un"].  
[load "U"] will load and evaluate the compiled unit body from file U.uo. The resulting values are not reported, but exceptions are reported, and cause evaluation and loading to stop. If U is already loaded, then load "U" has no effect. If any other unit is mentioned by U but not yet loaded, then it will be loaded automatically before U.

After loading a unit, it can be opened with 'open U'. Opening it at top-level will list the identifiers declared in the unit.

When loading U, it is checked that the signatures of units mentioned by U agree with the signatures used when compiling U, and it is checked that the signature of U has not been modified since U was compiled; these checks are necessary for type safety. The exception Fail is raised if these signature checks fail, or if the file containing U or a unit mentioned by U does not exist.

[loadOne "U"] is similar to 'load "U"', but raises exception Fail if U is already loaded or if some unit mentioned by U is not yet loaded. That is, it does not automatically load any units mentioned by U. It performs the same signature checks as 'load'.  
[loaded ()] returns a list of the names of all compiled units that have been loaded so far. The names appear in some random order.

[loadPath] determines the load path: which directories will be searched for interface files (.ui files), bytecode files (.uo files), and source files (.sml files). This variable affects the load, loadOne, and use functions. The current directory is always searched first, followed by the directories in loadPath, in order. By default, only the standard library directory is in the list, but if additional directories are specified using option -I, then these directories are prepended to loadPath.

[quietdec] when true, turns off the interactive system's prompt and responses, except warnings and error messages. Useful for writing scripts in SML. The default value is false; can be set to true with the -quietdec command line option.

[verbose] determines whether the signature inferred by a call to compile will be printed. The printed signature follows the syntax of Moscow ML signatures, so the output of compile "U.sml" can be edited to subsequently create file U.sig. The default value is ref false.

[quotation] determines whether quotations and antiquotations are permitted in declarations entered at top-level and in files compiled with compile. A quotation is a piece of text surrounded by backquote characters `a b c` and is used to embed object language phrases in ML programs; see the Moscow ML Owner's Manual for a brief explanation of quotations. When quotation is false, the backquote character is an ordinary symbol which can be used in ML symbolic identifiers. When quotation is true, the backquote character is illegal in symbolic identifiers, and a quotation `a b c` will be recognized by the parser and evaluated to an object of type `a General.frag list. False by default.

[valuepoly] determines whether value polymorphism is used or not in the type checker. With value polymorphism (the default), there is no distinction between imperative ('a) and applicative ('a) type variables, and type variables are generalized only in bindings to non-expansive expressions. Non-generalized type variables are left free, to be instantiated when the bound identifier is used. An expression is non-expansive if it is a variable, a special



constant, a function, a tuple or record of non-expansive expressions, a parenthesized or typed non-expansive expression, or the application of an exception or value constructor (other than `ref`) to a non-expansive expression. If `valuepoly` is `false`, then the type checker will distinguish imperative and applicative type variables, generalize all applicative type variables, and generalize imperative type variables only in non-expansive expressions. True by default.

## Module Mosml

*Mosml* -- some Moscow ML specific functions

```
val argv : unit -> string list
val time : ('a -> 'b) -> ('a -> 'b)
val listDir : string -> string list
val doubleVec : real -> Word8Vector.vector
val vecDouble : Word8Vector.vector -> real
val floatVec : real -> Word8Vector.vector
val vecFloat : Word8Vector.vector -> real
val md5sum : string -> string
```

```
datatype runresult =
 Success of string
 | Failure of string
```

```
val run : string -> string list -> string -> runresult
```

`[argv ()]` returns the command line strings of the current process. Hence `List.nth(argv (), 0)` is the command used to invoke the SML process, `List.nth(argv (), 1)` is its first argument, and so on. We recommend using the SML Basis Library `CommandLine` structure instead.

`[time f argv]` applies `f` to `argv` and returns the result; as a side effect, it prints the time (cpu, system, and real time) consumed by the evaluation.

`[listDir path]` returns the list of all files and subdirectories of the directory indicated by `path`. Raises `OS.SysErr` in case of failure.

`[doubleVec r]` returns an eight-element vector of `Word8.word`, which contains the real number in the IEEE 754 floating-point 'double format' bit layout stored in big-endian (high byte first) order.

`[vecDouble v]` accepts an eight-element vector `v` of `Word8.word`, and returns the real number obtained by taking `v` to be an IEEE 754 floating-point 'double format' number stored in big-endian (high byte first) order. Raises `Fail` if `v` is not an eight-element vector.

`[floatVec r]` returns a four-element vector of `Word8.word`, which contains the real number in the IEEE 754 floating-point 'float format' bit layout stored in big-endian (high byte first) order. Raises `Fail` if `r` is not representable as a 32-bit float.

`[vecFloat v]` accepts a four-element vector `v` of `Word8.word`, and returns the real number obtained by taking `v` to be an IEEE 754 floating-point 'float format' number stored in big-endian (high byte first) order. Raises `Fail` if `v` is not a four-element vector.

`[md5sum s]` computes the 128-bit MD5 checksum of string `s` and returns it as a 22 character `base64` string.

`[run cmd args inp]` executes the program `cmd` with command-line arguments `args` and standard input `inp`. Returns `Success s` where `s` is the program's (standard and error) output as a string, if it executed successfully; otherwise returns `Failure s` where `s` is its (standard and error) output as a string.

## Module Mosmlcgi

Mosmlcgi -- support for writing CGI scripts in Moscow ML

### 1. Accessing the fields or parameters of a CGI call

```
val cgi_fieldnames : string list
val cgi_field_strings : string -> string list;
val cgi_field_string : string -> string option;
val cgi_field_integer : string * int -> int;
```

### 2. Accessing parts in multipart/form-data; form-based file upload

```
val cgi_partnames : string list
type part
val cgi_part : string -> part option
val cgi_parts : string -> part list
val part_fieldnames : part -> string list
val part_type : part -> string option
val part_data : part -> string
val part_field_strings : part -> string -> string list
val part_field_string : part -> string -> string option
val part_field_integer : part -> string * int -> int
```

### 3. Administrative information

```
val cgi_server_software : string option
val cgi_server_name : string option
val cgi_gateway_interface : string option
val cgi_server_protocol : string option
val cgi_server_port : string option
val cgi_request_method : string option
val cgi_http_accept : string option
val cgi_http_user_agent : string option
val cgi_http_referer : string option
val cgi_path_info : string option
val cgi_path_translated : string option
val cgi_script_name : string option
val cgi_query_string : string option
val cgi_remote_host : string option
val cgi_remote_addr : string option
val cgi_remote_user : string option
val cgi_remote_ident : string option
val cgi_auth_type : string option
val cgi_content_type : string option
val cgi_content_length : string option
val cgi_annotation_server : string option
val cgi_http_cookie : string option
val cgi_http_forwarded : string option
val cgi_http_host : string option
val cgi_http_proxy_connection : string option
val cgi_script_filename : string option
val cgi_document_root : string option
val cgi_server_admin : string option
val cgi_api_version : string option
val cgi_the_request : string option
val cgi_request_uri : string option
val cgi_request_filename : string option
val cgi_is_subreq : string option
```

The Mosmlcgi library is for writing CGI programs in Moscow ML. A CGI program may be installed on a WWW server and is invoked in response to HTTP requests sent to the server from a web browser, typically from an HTML FORM element.

#### 1. Obtaining field values sent from an ordinary HTML form

[cgi\_fieldnames] is a list of the names of fields present in the CGI call message. If field name fnm is in cgi\_fieldnames, then cgi\_field\_string fnm <-> NONE.

[cgi\_field\_strings fnm] is a (possibly empty) list of the strings bound to field fnm.

[cgi\_field\_string fnm] returns SOME(s) where s is a string bound to field name fnm, if any; otherwise NONE. Equivalent to case cgi\_field\_strings fnm of  
 [] => NONE  
 | s :: \_ => SOME s

[cgi\_field\_integer (fnm, deflt)] attempts to parse an integer from field fnm. Returns i if cgi\_field\_string(fnm) = SOME(s) and an integer i can be parsed from a prefix of s; otherwise returns deflt.

2. Obtaining field values sent with ENCTYPE="multipart/form-data"  
 -----  
 [cgi\_partnames] is a list of the names of the parts of the multipart/form-data message.

The type part is the abstract type of parts of a message. Each part may have several fields. In this implementation, the field of a part cannot be a another part itself.

[cgi\_parts pnm] is a (possibly empty) list of the parts called pnm.

[cgi\_part pnm] is SOME(prt) where prt is a part called pnm, if any; otherwise NONE. Equivalent to case cgi\_parts pnm of  
 [] => NONE  
 | prt :: \_ => SOME prt

[part\_fieldnames prt] is the list of field names in part pnm.

[part\_type prt] is SOME(typ) if the part prt contains a specification 'Content-Type: typ'; otherwise NONE.

[part\_data prt] is the data contain in part prt; for instance, the contents of a file uploaded via form-based file upload.

[part\_field\_strings prt fnm] is a (possibly empty) list of the strings bound to field fnm in part prt.

[part\_field\_string prt fnm] returns SOME(s) where s is a string bound to field name fnm in part prt, if any; otherwise NONE. Equivalent to case part\_field\_strings prt fnm of  
 [] => NONE  
 | s :: \_ => SOME s

[part\_field\_integer prt (fnm, deflt)] attempts to parse an integer from field fnm of part prt. Returns i if part\_field\_string prt fnm = SOME(s) and an integer i can be parsed from a prefix of s; otherwise returns deflt.

### 3. Administrative and server information

Each of the following variables has the value SOME(s) if the corresponding CGI environment variable is bound to string s; otherwise NONE:

[cgi\_server\_software] is the value of SERVER\_SOFTWARE

[cgi\_server\_name] is the value of SERVER\_NAME

```

[cgi_gateway_interface] is the value of GATEWAY_INTERFACE
[cgi_server_protocol] is the value of SERVER_PROTOCOL
[cgi_server_port] is the value of SERVER_PORT
[cgi_request_method] is the value of REQUEST_METHOD
[cgi_http_accept] is the value of HTTP_ACCEPT
[cgi_http_user_agent] is the value of HTTP_USER_AGENT
[cgi_http_referer] is the value of HTTP_REFERER
[cgi_path_info] is the value of PATH_INFO
[cgi_path_translated] is the value of PATH_TRANSLATED
[cgi_script_name] is the value of SCRIPT_NAME
[cgi_query_string] is the value of QUERY_STRING
[cgi_remote_host] is the value of REMOTE_HOST
[cgi_remote_addr] is the value of REMOTE_ADDR
[cgi_remote_user] is the value of REMOTE_USER
[cgi_remote_ident] is the value of REMOTE_IDENT
[cgi_auth_type] is the value of AUTH_TYPE
[cgi_content_type] is the value of CONTENT_TYPE
[cgi_content_length] is the value of CONTENT_LENGTH, that is, the
length of the data transmitted in the CGI call.
[cgi_annotation_server] is the value of ANNOTATION_SERVER
[cgi_http_cookie] is the value of HTTP_COOKIE
[cgi_http_forwarded] is the value of HTTP_FORWARDED
[cgi_http_host] is the value of HTTP_HOST
[cgi_http_proxy_connection] is the value of HTTP_PROXY_CONNECTION
[cgi_script_filename] is the value of SCRIPT_FILENAME
[cgi_document_root] is the value of DOCUMENT_ROOT
[cgi_server_admin] is the value of SERVER_ADMIN
[cgi_api_version] is the value of API_VERSION
[cgi_the_request] is the value of THE_REQUEST
[cgi_request_uri] is the value of REQUEST_URI
[cgi_request_filename] is the value of REQUEST_FILENAME
[cgi_is_subreq] is the value of IS_SUBREQ

```

## Module Mosmlcookie

*Mosmlcookie* -- getting and setting cookies in CGI scripts

```

exception CookieError of string

val allCookies : string list
val getCookieValue : string -> string option
val getCookie : string -> string option

type cookiedata =
 { name : string,
 value : string,
 expiry : Date.date option,
 domain : string option,
 path : string option,
 secure : bool }

val setCookie : cookiedata -> string
val setCookies : cookiedata list -> string
val deleteCookie : { name : string, path : string option } -> string

These functions may be used in CGI scripts to get and set cookies.
(c) Hans Molin, Computing Science Dept., Uppsala University, 1999.

[getCookieValue ck] returns SOME(v) where v is the value associated
with the cookie ck, if any; otherwise returns NONE.

[setCookie ck] returns SOME(nv) where nv is the ck-value string
for the cookie ck, if any; otherwise returns NONE.

[allCookies] is a list [nv1, nv2, ..., nvn] of all the ck-value
pairs of defined cookies.

[setCookie { name, value, expiry, domain, path, secure }] returns a
string which (when transmitted to a browser as part of the HTTP
response header) sets a cookie with the given name, value, expiry
date, domain, path, and security.

[setCookies ckds] returns a string which (when transmitted to a
browser as part of the HTTP response header) sets the specified cookies.

[deleteCookie { name, path }] returns a string which (when
transmitted to a browser as part of the HTTP response header)
deletes the specified cookie by setting its expiry to some time in
the past.

```

## Module Msp

Msp -- utilities for CGI scripts and ML Server Pages

Efficiently concatenable word sequences

```
datatype wseq =
 | Nil
 | $ of string
 | $$ of string list
 | && of wseq * wseq'
Manipulating wseqs
```

```
val pmap : ('a -> wseq) -> 'a list -> wseq
val pseq : wseq -> ('a -> wseq) -> 'a list -> wseq
val flatten : wseq -> string
val printseq : wseq -> unit
val vec2list : 'a vector -> 'a list
```

Shorthands for accessing CGI parameters

```
exception ParamMissing of string
exception NotInt of string * string
val % : string -> string
val %? : string -> bool
val %% : string -> int
val %%# : string * string -> string
val %%## : string * int -> int
```

HTML generic marks

```
val mark0 : string -> wseq
val mark0a : string -> string -> wseq
val mark1 : string -> wseq -> wseq
val mark1a : string -> string -> wseq -> wseq
val comment : wseq -> wseq
```

HTML documents and headers

```
val html : wseq -> wseq
val head : wseq -> wseq
val title : wseq -> wseq
val body : wseq -> wseq
val bodya : string -> wseq -> wseq
val htmldoc : wseq -> wseq -> wseq
```

HTML headings and vertical format

```
val h1 : wseq -> wseq
val h2 : wseq -> wseq
val h3 : wseq -> wseq
val h4 : wseq -> wseq
val h5 : wseq -> wseq
val h6 : wseq -> wseq
val p : wseq -> wseq
val pa : string -> wseq -> wseq
val br : wseq
val bra : string -> wseq
val hr : wseq
val hra : string -> wseq
val divi : wseq -> wseq
val divia : string -> wseq -> wseq
val blockquote : wseq -> wseq
val blockquotea : string -> wseq -> wseq
val center : wseq -> wseq
```

```
val address : wseq -> wseq
val pre : wseq -> wseq
```

HTML anchors and hyperlinks

```
val ahref : string -> wseq -> wseq
val ahrefa : string -> string -> wseq -> wseq
val aname : string -> wseq -> wseq
```

HTML text formats and style

```
val em : wseq -> wseq
val strong : wseq -> wseq
val tt : wseq -> wseq
val sub : wseq -> wseq
val sup : wseq -> wseq
val fonta : string -> wseq -> wseq
```

HTML lists

```
val ul : wseq -> wseq
val ula : string -> wseq -> wseq
val ol : wseq -> wseq
val ola : string -> wseq -> wseq
val li : wseq -> wseq
val lii : wseq -> wseq
val dli : string -> wseq -> wseq
val dt : wseq -> wseq
val dd : wseq -> wseq
```

HTML tables

```
val table : wseq -> wseq
val tablea : string -> wseq -> wseq
val tr : wseq -> wseq
val trr : string -> wseq -> wseq
val td : wseq -> wseq
val tdr : string -> wseq -> wseq
val th : wseq -> wseq
val thr : string -> wseq -> wseq
val caption : wseq -> wseq
val captiona : string -> wseq -> wseq
```

HTML images and image maps

```
val img : string -> wseq
val imga : string -> string -> wseq
val map : string -> wseq -> wseq
val mapa : string -> string -> wseq -> wseq
val area : { alt : string option, coords : string, href : string option, shape : string } -> wseq
```

HTML forms etc

```
val form : string -> wseq -> wseq
val forma : string -> string -> wseq -> wseq
val input : string -> wseq
val inputa : string -> string -> wseq
val intext : string -> string -> wseq
val intexta : string -> string -> wseq
val inpassword : string -> string -> wseq
val incheckbox : { name : string, value : string } -> string -> wseq
val inradio : { name : string, value : string } -> string -> wseq
val inreset : string -> string -> wseq
val insubmit : string -> string -> wseq
val inhidden : { name : string, value : string } -> wseq
val inhiddena : string -> wseq -> wseq
val textarea : string -> string -> wseq -> wseq
val textareaa : string -> string -> wseq -> wseq
val select : string -> string -> wseq
val option : string -> wseq
```

HTML frames and framesets

```
val frameset : string -> wseq -> wseq
val frame : { src : string, name : string } -> wseq
val framea : { src : string, name : string } -> string -> wseq
```

#### HTML encoding

```
val urlencode : string -> string
val htmlentities : string -> string
```

This module provides support functions for writing CGI scripts and ML Server Page scripts.

[wseq] is the type of efficiently concatenable word sequences. Building an HTML page (functionally) as a wseq is more efficient than building it (functionally) as a string, and more convenient and modular than building it (imperatively) by calling print.

[Empty] represents the empty string "".

[NL] represents the string "\n" consisting of a single newline character.

[s] represents the string s.

[\$\$ ss] represents the string String.concat(ss).

[&&(ws1, ws2)] represents the concatenation of the strings represented by ws1 and ws2. The function && should be declared infix &&

[prmap f xs] is f x1 && ... && f xn evaluated from left to right, when xs is [x1, ..., xn].

[prsep sep f xs] is f x1 && sep && ... && sep && f xn, evaluated from left to right, when xs is [x1, ..., xn].

[flatten ws] is the string represented by ws.

[printseq ws] is equivalent to print(flatten ws), but avoids building any new strings.

[vec2list vec] is a list of the elements of vector vec. Use it to convert e.g. the results of a database query into a list, for processing with prmap or prsep.

Shorthands for accessing CGI parameters:

[? fm] returns true if there is a string associated with CGI parameter fm; otherwise returns false.

[% fm] returns a string associated with CGI parameter fm if there is any; raises ParamMissing(fm) if no strings are associated with fm. Equivalent to

```
case Wosm.cgi.cgi_field_string fm of
 NONE => raise ParamMissing "fm"
 | SOME v => v
```

In general, multiple strings may be associated with a CGI parameter; use Wosm.cgi.cgi\_field\_strings if you need to access all of them.

[# fm] returns the integer i if there is a string associated with CGI parameter fm, and that string is parsable as ML integer i. Raises ParamMissing(fm) if no string is associated with fm. Raises NotInt(fm, s) if there is a string but it is not parsable as an ML int.

[%(fm, dflt)] returns a string associated with CGI parameter fm if there is any; otherwise returns the string dflt.

[##(fm, dflt)] returns the integer i if there is a string associated with CGI parameter fm, and that string is parsable as

an ML int; otherwise returns the string dflt.

HTML generic marks:

[mark0 t] generates the HTML tag <t> as a wseq.

[mark0a attr t] generates the attributed HTML tag <t attr> as a wseq.

[mark1 t ws] generates <t>ws</t> as a wseq.

[mark1a attr t ws] generates <t attr>ws</t> as a wseq.

[comment ws] generates <!--ws--> as a wseq.

HTML documents and headers:

[html ws] generates <HTML>ws</HTML>.

[head ws] generates <HEAD>ws</HEAD>.

[title ws] generates <TITLE>ws</TITLE>.

[body ws] generates <BODY>ws</BODY>.

[bodya attr ws] generates <BODY attr>ws</BODY>.

[htmldoc titl ws] generates <HTML><HEAD><TITLE>titl</TITLE></HEAD><BODY>ws</BODY></HTML>.

HTML headings and vertical format:

[h1 ws] generates <H1>ws</H1>.

[p ws] generates <P>ws</P>.

[pa attr ws] generates <P attr>ws</P>.

[br] generates <BR>.

[bra attr] generates <BR attr>.

[hr] generates <HR>.

[hra attr] generates <HR attr>.

[divi ws] generates <DIV>ws</DIV>.

[divia attr ws] generates <DIV attr>ws</DIV>.

[blockquote ws] generates <BLOCKQUOTE>ws</BLOCKQUOTE>.

[blockquotea attr ws] generates <BLOCKQUOTE attr>ws</BLOCKQUOTE>.

[center ws] generates <CENTER>ws</CENTER>.

[address ws] generates <ADDRESS>ws</ADDRESS>.

[pre ws] generates <PRE>ws</PRE>.

HTML anchors and hyperlinks:

[ahref link ws] generates <A HREF="link">ws</A>.

[ahrefa link attr ws] generates <A HREF="link" attr>ws</A>.

[aname nam ws] generates <A NAME="name">ws</A>.

HTML text formats and style:

[em ws] generates <EM>ws</EM>.  
 [strong ws] generates <STRONG>ws</STRONG>.  
 [tt ws] generates <TT>ws</TT>.  
 [sub ws] generates <SUB>ws</SUB>.  
 [sup ws] generates <SUP>ws</SUP>.  
 [fonta attr ws] generates <FONT attr>ws</FONT>.

HTML lists:

[ul ws] generates <UL>ws</UL>.  
 [ul<sub>a</sub> attr ws] generates <UL attr>ws</UL>.  
 [ol ws] generates <OL>ws</OL>.  
 [ol<sub>a</sub> attr ws] generates <OL attr>ws</OL>.  
 [li ws] generates <LI>ws</LI>.  
 [dl ws] generates <DL>ws</DL>.  
 [dl<sub>a</sub> attr ws] generates <DL attr>ws</DL>.  
 [dt ws] generates <DT>ws</DT>.  
 [dd ws] generates <DD>ws</DD>.

HTML tables:

[table ws] generates <TABLE>ws</TABLE>.  
 [table<sub>a</sub> attr ws] generates <TABLE attr>ws</TABLE>.  
 [tr ws] generates <TR>ws</TR>.  
 [tr<sub>a</sub> attr ws] generates <TR attr>ws</TR>.  
 [td ws] generates <TD>ws</TD>.  
 [td<sub>a</sub> attr ws] generates <TD attr>ws</TD>.  
 [th ws] generates <TH>ws</TH>.  
 [th<sub>a</sub> attr ws] generates <TH attr>ws</TH>.  
 [caption ws] generates <CAPTION>ws</CAPTION>.  
 [caption<sub>a</sub> attr ws] generates <CAPTION attr>ws</CAPTION>.

HTML images and image maps:

[img s] generates <IMG SRC="s">.  
 [img<sub>a</sub> s attr] generates <IMG SRC="s" attr>.  
 [map nam ws] generates <MAP NAME="name" attr>ws</MAP>.  
 [map<sub>a</sub> nam attr ws] generates <MAP NAME="name" attr>ws</MAP>.  
 [area { alt, coords, href, shape}] generates  
 <AREA SHAPE="shape" COORDS="coords" HREF="link" ALT="desc">  
 when href is SOME link (where href is replaced by NOHREF otherwise)

and alt is SOME desc (where ALT is omitted otherwise).

HTML forms etc:

[form act ws] generates <FORM ACTION="act">ws</FORM>.  
 [forma act attr ws] generates <FORM ACTION="act" attr>ws</FORM>.  
 [input typ] generates <INPUT TYPE=typ>.  
 [input<sub>a</sub> typ attr] generates <INPUT TYPE=typ attr>.  
 [intext name attr] generates <INPUT TYPE=TEXT NAME="name" attr>.  
 [inpassword name attr] generates <INPUT TYPE=PASSWORD NAME="name" attr>.  
 [incheckbox {name, value} attr] generates  
 <INPUT TYPE=CHECKBOX NAME="name" VALUE="value" attr>.  
 [inradio {name, value} attr] generates  
 <INPUT TYPE=RADIO NAME="name" VALUE="value" attr>.  
 [inreset value attr] generates <INPUT TYPE=RESET VALUE="value" attr>.  
 [insubmit value attr] generates <INPUT TYPE=SUBMIT VALUE="value" attr>.  
 [inhidden {name, value}] generates  
 <INPUT TYPE=HIDDEN NAME="name" VALUE="value">.  
 [textarea name ws] generates <TEXTAREA NAME="name">ws</TEXTAREA>.  
 [textareaa name attr ws] generates  
 <TEXTAREA NAME="name" attr>ws</TEXTAREA>.  
 [select name attr ws] generates <SELECT NAME="name" attr>ws</SELECT>.  
 [option value] generates <OPTION VALUE="value">.

HTML frames and framesets:

[frameset attr ws] generates <FRAMESET attr>ws</FRAMESET>.  
 [frame { src, name }] generates <FRAME SRC="src" NAME="name">.  
 [framea { src, name } attr] generates <FRAME SRC="src" NAME="name" attr>.  
 HTML encoding functions:  
 [urlencode s] returns the url-encoding of s. That is, space (ASCII 32) is replaced by '+', and every non-alphanumeric character c except the characters - \_ . is replaced by %hh, where hh is the hexadecimal representation of the ASCII code of c.  
 [htmlencode s] returns the html-encoding of s. That is, < and > are replaced by &lt; and &gt; respectively, and & is replaced by &amp;



if an error occurred, where msg describes the error.

[execute dbconn query] sends an SQL query to the database server for execution, and returns a resultset dbres.

[resultstatus dbres] returns the status of the result set dbres. After a select query that succeeded, it will be TuplesOk.

[ntuples dbres] returns the number of tuples in the result set after a query.

[cmdtuples dbres] returns the number of tuples affected by an insert, update, or delete SQL command.

[nfields dbres] returns the number of fields in each tuple after a query.

[fname dbres fno] returns the name of field number fno (in the result set after a query). The fields are numbered 0, 1, ...

[fnames dbres] returns a vector of the field names (in the result set after a query).

[fnumber dbres fname] returns SOME i where i is the number (0, 1, ...) of the field called fname (in the result set after a query), if the result set contains such a field name; returns NONE otherwise.

[ftype dbres fno] returns the datatype of field number fno (in the result set after a query).

[ftypes dbres] returns a vector of the datatypes (in the result set after a query).

[fromtag dt] returns the name of the preferred MySQL type used to represent values of the datatype dt. This may be used when building 'create table' statements.

[getint dbres fno tupno] returns the integer value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getreal dbres fno tupno] returns the floating-point value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getstring dbres fno tupno] returns the string value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getdate dbres fno tupno] returns the date (yyyy, mth, day) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[gettime dbres fno tupno] returns the time-of-day (hh, mm, ss) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a time.

[getdatetime dbres fno tupno] returns the Date.date value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[getbool dbres fno tupno] returns the boolean value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[isnull dbres fno tupno] returns true if the value of field number fno in tuple tupno of result set dbres is NULL; false otherwise.

[getdynfield dbres fno tupno] returns the value of field number fno

in tuple tupno of result set dbres as a dynval (a wrapped value). A NULL value is returned as NullVal. Note that the partial application (getdynfield dbres fno) precomputes the type of the field fno. Hence it is far more efficient to compute let val getfno = getdynfield dbres fno in tabulate(ntuples dbres, getfno) end than to compute let fun getfno tupno = getdynfield dbres fno tupno in tabulate(ntuples dbres, getfno) end because the latter repeatedly computes the type of the field.

[getdyn tup dbres tupno] returns the fields of tuple tupno in result set dbres as a vector of dynvals.

[getdyn tuples dbres] returns all tuples of result set dbres as a vector of vectors of dynvals.

[dynval2s dv] returns a string representing the dynval dv.

[applyto x f] computes f(x). This is convenient for applying several functions (given in a list or vector) to the same value: map (applyto 5) (tabulate(3, getdynfield dbres)) equals [getdynfield dbres 0 5, getdynfield dbres 1 5, getdynfield dbres 2 5]

[copytableto(dbconn, tablename, put)] simulates a PostgreSQL "COPY TABLE TO" statement, applies the function put to every tuple of the table, represented as a line of text (not terminated by newline \n), and cleans up at the end. For instance, to copy the contents of a table t to a text stream s (one tuple on each line), define fun put line = (TextIO.output(s, line); TextIO.output(s, "\n")) and execute copytableto(dbconn, "t", put).

[copytablefrom(dbconn, tablename, useput)] simulates a PostgreSQL "COPY TABLE FROM" statement, creates a put function for copying lines to the table, passes the put function to useput, and cleans up at the end. The put function may be called multiple times for each line (tuple); the end of each line is indicated by the newline character "\n" as usual. For instance, to copy the contents of a text stream s to a table t, define fun useput put = while not (TextIO.endOfStream s) do put(TextIO.inputLine s); and execute copytablefrom(dbconn, "t", useput).

Note that TextIO.inputLine preserves the newline at the end of each line.

[formattable dbresult] returns a wseq representing an HTML table. The HTML table has a column for every field in the dbresult. The first row is a table header giving the names of the fields in the dbresult. The remaining rows correspond to the tuples in the dbresult, in the order they are provided by the database server. Null fields are shown as NULL.

[showquery dbconn query] sends the SQL query to the database server, then uses formattable to format the result of the query.



## Module NJ93

*NJ93* -- compatibility *SML/NJ 0.93* top-level environment

```
val print : string -> unit
```

*NJ93 Integer*

```
val max : int * int -> int
val min : int * int -> int
```

*NJ93 List*

exception Hd and Tl and Nth and NthTail

```
val hd : 'a list -> 'a Hd
val tl : 'a list -> 'a list Tl
val nth : 'a list * int -> 'a Nth
val nthtail : 'a list * int -> 'a list NthTail
val app : ('a -> 'b) -> 'a list -> unit
val revapp : ('a -> 'b) -> 'a list -> unit
val fold : ('a * 'b -> 'b) -> 'a list -> 'b -> 'b
val revfold : ('a * 'b -> 'b) -> 'a list -> 'b -> 'b
```

*NJ93 Real*

```
val ceiling : real -> int
val truncate : real -> int
```

*NJ93 Ref*

```
val inc : int ref -> unit
val dec : int ref -> unit
```

*NJ93 String*

exception Substring

```
val ordof : string * int -> int
val ord : string -> int
val chr : int -> string Ord
val substr : string * int * int -> string Chr
val explode : string -> string list Substring
val implode : string list -> string
```

*NJ93 top-level math functions*

```
val sqrt : real -> real
val sin : real -> real
val cos : real -> real
val arctan : real -> real
val exp : real -> real
val ln : real -> real
```

*NJ93 top-level input/output, standard*

type instream and ostream

```
val std_in : instream
val open_in : string -> instream
val input : instream * int -> string
val lookahead : instream -> string
val close_in : instream -> unit
val end_of_stream : instream -> bool
```

```
val std_out : ostream
val open_out : string -> ostream
val output : ostream * string -> unit
val close_out : ostream -> unit
```

*NJ93 top-level input/output, non-standard*

```
val open_in_bin : string -> instream
val open_out_bin : string -> ostream
val inputc : instream -> int -> string
val std_err : ostream
val outputc : ostream -> string -> unit
val flush_out : ostream -> unit
val input_line : instream -> string
val can_input : instream * int -> bool
val open_append : string -> ostream
```

## Module Nonstdio

```

Nonstdio -- non-standard I/O -- use BinIO and TextIO instead

local open BasicIO in
 val open_in_bin : string -> instream
 val buff_input : instream -> CharArray.array -> int -> int -> int
 val input_char : instream -> char Raises Size
 val input_binary_int : instream -> int
 val input_value : instream -> 'a
 val seek_in : instream -> int -> unit
 val pos_in : instream -> int
 val in_stream_length : instream -> int
 val fast_really_input : instream -> string -> int -> int -> unit

 val open_out_bin : string -> ostream
 val open_out_exe : string -> ostream
 val output_char : ostream -> Char.char -> unit
 val output_byte : ostream -> int -> unit
 val buff_output : ostream -> CharArray.array -> int -> int -> unit
 val output_binary_int : ostream -> int -> unit
 val output_value : ostream -> 'a -> unit
 val seek_out : ostream -> int -> unit
 val pos_out : ostream -> int

 val file_exists : string -> bool
end

```

## Module OS

```

OS -- SML Basis Library

signature OS = sig
 type syserror = syserror
 exception SysErr of string * syserror option
 val errorMsg : syserror -> string
 structure FileSys : FileSys
 structure Path : Path
 structure Process : Process
end

[errorMsg err] returns a string explaining the error message system
error code err, as found in a SysErr exception. The precise form
of the string depends on the operating system.

```

## Module Option

*Option* -- SML Basis Library

```

exception Option
datatype option = datatype option

val getOpt : 'a option * 'a -> 'a
val isSome : 'a option -> bool
val valOf : 'a option -> 'a
val filter : ('a -> bool) -> 'a -> 'a option
val map : ('a -> 'b) -> 'a option -> 'b option
val mapOpt : ('a -> unit) -> 'a option -> unit
val join : 'a option option -> 'a option
val compose : ('a -> 'b) * ('c -> 'a option) -> ('c -> 'b option)
val mapPartial : ('a -> 'b option) -> ('a option -> 'b option)
val composePartial : ('a -> 'b option) * ('c -> 'a option) -> ('c -> 'b option)

[getOpt (xopt, d)] returns x if xopt is SOME x; returns d otherwise.
[isSome vopt] returns true if xopt is SOME x; returns false otherwise.
[valOf vopt] returns x if xopt is SOME x; raises Option otherwise.
[filter p x] returns SOME x if p x is true; returns NONE otherwise.
[map f xopt] returns SOME (f x) if xopt is SOME x; returns NONE otherwise.
[app f xopt] applies f to x if xopt is SOME x; does nothing otherwise.
[join xopt] returns x if xopt is SOME x; returns NONE otherwise.
[compose (f, g) x] returns SOME (f y) if g x is SOME y; returns NONE otherwise. It holds that compose (f, g) = map f o g.
[mapPartial f xopt] returns f x if xopt is SOME x; returns NONE otherwise. It holds that mapPartial f = join o map f.
[composePartial (f, g) x] returns f y if g x is SOME y; returns NONE otherwise. It holds that composePartial (f, g) = mapPartial f o g.

The operators (map, join, SOME) form a monad.

```

## Module PP

*PP* -- pretty-printing -- from the SML/NJ Library

```

type ppconsumer = {
 consumer : string -> unit,
 linewidth : int,
 flush : unit -> unit }

datatype break_style =
 CONSISTENT
| INCONSISTENT

val mk_ppstream : ppconsumer -> ppstream
val dest_ppstream : ppstream -> ppconsumer
val add_break : ppstream -> int * int -> unit
val add_newline : ppstream -> unit
val add_string : ppstream -> string -> unit
val begin_block : ppstream -> break_style -> int -> unit
val end_block : ppstream -> unit
val clear_ppstream : ppstream -> unit
val flush_ppstream : ppstream -> unit
val with_pp : ppconsumer -> (ppstream -> unit) -> unit
val pp_to_string : int -> (ppstream -> 'a -> unit) -> 'a -> string

```

This structure provides tools for creating customized Open-Style pretty-printers, based on the type `ppstream`. A `ppstream` is an output stream that contains prettyprinting commands. The commands are placed in the stream by various function calls listed below.

There following primitives add commands to the stream: `begin_block`, `end_block`, `add_string`, `add_break`, and `add_newline`. All calls to `add_string`, `add_break`, and `add_newline` must happen between a pair of calls to `begin_block` and `end_block` must be properly nested dynamically. All calls to `begin_block` and `end_block` must be properly nested (dynamically).

`[ppconsumer]` is the type of sinks for pretty-printing. A value of type `ppconsumer` is a record

```
{ consumer : string -> unit,
 linewidth : int,
 flush : unit -> unit }
```

of a string consumer, a specified linewidth, and a flush function which is called whenever `flush_ppstream` is called.

A prettyprinter can be called outright to print a value. In addition, a prettyprinter for a base type or nullary datatype `ty` can be installed in the top-level system. Then the installed prettyprinter will be invoked automatically whenever a value of type `ty` is to be printed.

`[break_style]` is the type of line break styles for blocks:

`[CONSISTENT]` specifies that if any line break occurs inside the block, then all indicated line breaks occur.

`[INCONSISTENT]` specifies that breaks will be inserted to only to avoid overfull lines.

`[mk_ppstream {consumer, linewidth, flush}]` creates a new `ppstream` which invokes the consumer to output text, putting at most `linewidth` characters on each line.

`[dest_ppstream ppstrm]` extracts the linewidth, flush function, and consumer from a `ppstream`.

`[add_break ppstrm (size, offset)]` notifies the pretty-printer that a line break is possible at this point.

\* When the current block style is `CONSISTENT`:

```
** if the entire block fits on the remainder of the line, then
 output size spaces; else
 ** increase the current indentation by the block offset;
```

further indent every item of the block by offset, and add one newline at every `add_break` in the block.

```
* When the current block style is INCONSISTENT:
** if the next component of the block fits on the remainder of
the line, then output size spaces; else
** issue a newline and indent to the current indentation level
plus the block offset plus the offset.
```

```
[add_newline ppstrm] issues a newline.
[add_string ppstrm str] outputs the string str to the ppstream.
[begin_block ppstrm style blockoffset] begins a new block and
level of indentation, with the given style and block offset.
[end_block ppstrm] closes the current block.
```

```
[clear_ppstream ppstrm] restarts the stream, without affecting the
underlying consumer.
```

```
[flush_ppstream ppstrm] executes any remaining commands in the
ppstream (that is, flushes currently accumulated output to the
consumer associated with ppstrm); executes the flush function
associated with the consumer; and calls clear_ppstream.
```

```
[with_pp_consumer f] makes a new ppstream from the consumer and
applies f (which can be thought of as a producer) to that
ppstream, then flushed the ppstream and returns the value of f.
```

```
[pp_to_string linewidth printit x] constructs a new ppstream
ppstrm whose consumer accumulates the output in a string s. Then
evaluates (printit ppstrm x) and finally returns the string s.
```

Example 1: A simple prettyprinter for Booleans:

```
load "pp";
fun ppbool pps d =
 let open PP
 in
 begin_block pps INCONSISTENT 6;
 add_string pps (if d then "right" else "wrong");
 end_block pps
 end;
```

Now one may define a ppstream to print to, and exercise it:

```
val ppstrm = PP.mk_ppstream {consumer =
 fn s => TextIO.output(TextIO.stdOut, s),
 linewidth = 72,
 flush =
 fn () => TextIO.flushOut TextIO.stdOut};

fun ppb b = (ppbool ppstrm b; PP.flush_ppstream ppstrm);

- ppb false;
wrong> val it = () : unit
```

The prettyprinter may also be installed in the toplevel system; then it will be used to print all expressions of type `bool` subsequently computed:

```
- installPP ppbool;
> val it = () : unit
- !=0;
> val it = wrong : bool
- !=1;
> val it = right : bool
```

See library `Meta` for a description of `installPP`.

Example 2: Prettyprinting simple expressions (examples/pretty/ppexpr.sml):

```
datatype expr =
 Cst of int
 | Neg of expr
 | Plus of expr * expr

fun ppexpr pps e0 =
 let open PP
 in
 fun ppe (Cst i) = add_string pps (Int.toString i)
 | ppe (Neg e) = (add_string pps "~"; ppe e)
 | ppe (Plus(e1, e2)) = (begin_block pps CONSISTENT 0;
 add_string pps "(";
 ppe e1;
 add_string pps " + ";
 add_break pps (0, 1);
 ppe e2;
 add_string pps ")";
 end_block pps)
 in
 begin_block pps INCONSISTENT 0;
 ppe e0;
 end_block pps
 end
 end

val _ = installPP ppexpr;

Some example values:

val e1 = Cst 1;
val e2 = Cst 2;
val e3 = Plus(e1, Neg e2);
val e4 = Plus(Neg e3, e3);
val e5 = Plus(Neg e4, e4);
val e6 = Plus(e5, e5);
val e7 = Plus(e6, e6);
val e8 =
 Plus(e3, Plus(e3, Plus(e3, Plus(e3, Plus(e3, e7)))));
```

## Module Parsing

*Parsing* -- runtime library for parsers generated by *mosmlyac*  
 Based on the runtime library for *camlyacc*; copyright 1993 INRIA, France

local open Vector Obj Lexing in

```
val symbolStart : unit -> int
val symbolEnd : unit -> int
val itemStart : int -> int
val itemEnd : int -> int
val clearParser : unit -> unit
```

For internal use in generated parsers:

```
type parseTables = (unit -> obj) vector *
actions int vector *
transl string *
lits string *
len string *
defred string *
dgoto string *
sindex string *
rindex string *
gindex string *
tablesize int *
table string *
check string
```

```
exception yyexit of obj
exception ParseError of (obj -> bool)
```

```
val yyparse : parseTables -> int -> (lexbuf -> 'a) -> lexbuf -> 'b
val peekVal : int -> 'a
end
```

---

These functions are for use in *mosmlyac*-generated parsers. For further information, see the Moscow ML Owner's Manual. For examples, see *mosml/examples/lexyacc* and *mosml/examples/calc*.

A grammar definition (input to *mosmlyac*) consists of fragments of this form

```
nonterm :
 grsyms1 { action1 }
 | grsyms2 { action2 }
 | grsyms3 { action3 }
 | ...
```

where the *grsyms* are sequences of grammar symbols, matching some string of characters, and the actions are corresponding semantic actions, written in ML. The following functions can be used in the semantic actions:

`[symbolStart ()]` returns the start position of the string that matches the sequence of grammar symbols. The first character in the input stream has position 0. May be called in a semantic action only.

`[symbolEnd ()]` returns the end position, plus one, of the string that matches the sequence of grammar symbols. The first character in the input stream has position 0. May be called in a semantic action only.

`[itemStart i]` returns the start position of the string that matches the *i*'th grammar symbol in the sequence. The first grammar symbol has number 1. The first character in the input stream has position 0. May be called in a semantic action only.

`[itemEnd i]` returns the end position, plus one, of the string that matches the *i*'th grammar symbol in the sequence. The first grammar symbols has number 1. The first character in the input stream has position 0. May be called in a semantic action only.

`[clearParser ()]` clears the parser stack. It may be called after a parsing function has returned, to remove all pointers from the parser stack to structures that were built by semantic actions during parsing. This is not strict necessary, but reduces the memory requirements of the program.

## Module Path

OS.Path -- SML Basis Library

exception Path

```

val parentArc : string
val currentArc : string
val fromString : string -> {isAbs: bool, vol : string, arcs : string list} -> string
val toString : {isAbs: bool, vol : string, arcs : string list} -> string
val getVolume : string -> string
val validVolume : {isAbs: bool, vol : string} -> bool
val getParent : string -> string
val isAbsolute : string -> bool
val isRelative : string -> bool
val mkAbsolute : string * string -> string
val mkRelative : string * string -> string
val concat : string * string -> string
val mkCanonical : string -> string
val isCanonical : string -> bool
val splitDirFile : string -> {dir : string, file : string}
val joinDirFile : {dir : string, file : string} -> string
val dir : string -> string
val file : string -> string
val splitBaseExt : string -> {base : string, ext : string option}
val joinBaseExt : {base : string, ext : string option} -> string
val base : string -> string
val ext : string -> string option

```

This module provides OS-independent functions for manipulating strings that represent file names and paths in a directory structure. None of these functions accesses the actual filesystem.

Definitions:

- \* An arc denotes a directory or file. Under Unix or DOS, an arc may have form "...", ".", "", or "abc", or similar.
- \* An absolute path has a root: Unix examples include "/", "/a/b"; DOS examples include "\", "\a\b", "A:\a\b".
- \* A relative path is one without a root: Unix examples include "...", "a/b"; DOS examples include ".", "a\b", "A:a\b".
- \* A path has an associated volume. Under Unix, there is only one volume, whose name is "...". Under DOS, the volume names are "...", "A:", "C:", and similar.
- \* A canonical path contains no occurrences of the empty arc "" or the current arc ".", and contains or the parent arc ".." only at the beginning and only if the path is relative.
- \* All functions (except concat) preserve canonical paths. That is, if all arguments are canonical, then so will the result be.
- \* All functions are defined so that they work sensibly on canonical paths.
- \* There are three groups of functions, corresponding to three ways to look at paths, exemplified by the following paths:
 

|       |                |     |                |
|-------|----------------|-----|----------------|
| Unix: | d/e/f/a.b.c    | and | /d/e/f/a.b.c   |
| DOS:  | A:\d\e\f\a.b.c | and | A:\d\e\f\a.b.c |

(1) A path consists of a sequence of arcs, possibly preceded by a volume and a root:

```

vol [--- arcs ---] vol root [--- arcs ---]
Unix examples: d e f a.b.c
DOS examples: A: d e f a.b A: < d e f a.b.c

```

(2) A path consists of a directory part and a (last) file name part:

```

directory file directory file
Unix examples: d/e/f a.b.c /d/e/f a.b.c
DOS examples: A:\d\e\f a.b A:\d\e\f a.b

```

(3) A path consists of a base and an extension:

```

base extension base extension
Unix examples: d/e/f/a.b c /d/e/f/a.b c
DOS examples: A:\d\e\f\ a b A:\d\e\f\ a b

```

GROUP 0: General functions on paths:

[parentArc] is the arc denoting a parent directory: "." under DOS and Unix.

[currentArc] is the arc denoting the current directory: "." under DOS and Unix.

[isRelative p] returns true if p is a relative path.

[isAbsolute p] returns true if p is an absolute path. Equals not (isRelative p).

[validVolume {isAbs, vol}] returns true if vol is a valid volume name for an absolute path (if isAbs=true) resp. for a relative path (if isAbs=false). Under Unix, the only valid volume name is "" under MS DOS and MS Windows the valid volume names are "...", "a:", "b:", ..., and "A:", "B:", ...

[getParent p] returns a string denoting the parent directory of p. It holds that getParent p = p if and only if p is a root.

[concat (p1, p2)] returns the path consisting of p1 followed by p2. Does not preserve canonical paths: concat("a/b", "../c") equals "a/b/./c". This is because "a/b/./c" and "a/c" may not be equivalent in the presence of symbolic links. Raises Path if p2 is not a relative path.

[mkAbsolute(p1, p2)] returns the absolute path made by taking path p2, then p1. That is, returns p1 if p1 is absolute; otherwise returns the canonicalized concatenation of p2 and p1. Raises Path if p2 is not absolute (even if p1 is absolute).

[mkRelative(p1, p2)] returns p1 relative to p2. That is, returns p1 if p1 is already relative; otherwise returns the relative path leading from p2 to p1. Raises Path if p2 is not absolute (and even if p1 is relative), or if p1 and p2 are both absolute but have different roots.

[mkCanonical p] returns a canonical path which is equivalent to p. Redundant occurrences of the parent arc, the current arc, and the empty arc are removed. The canonical path will never be the empty string; the empty path is converted to the current directory path ("." under Unix and DOS).

[isCanonical p] is equal to (p = mkCanonical p).

GROUP 1: Manipulating volumes and arcs:

```
[fromString p] returns {isAbs=false, vol, arcs} if the path p is relative, and {isAbs=true, vol, arcs} if the path p is absolute. In both cases vol is the volume name and arcs is the list of (possibly empty) arcs of the path. Under Unix, the volume name is always the empty string ""; under DOS it will have form "A:", "C:", or similar.
```

```
[toString path] reconstitutes a path from its root (if any) and arcs. Raises Path if applied to a relative path whose first arc is empty. It holds that toString(fromString p) = p, except that in MS DOS, slashes "/" in p will be replaced by backslashes "\". It holds that fromString(toString p) = p when no exception is raised. It holds that isRelative(toString {isAbs=false, vol, arcs}) = true when no exception is raised.
```

```
[getVolume p] returns the volume name of the path p, if given. Under Unix and MacOS, this is always the empty string "", and under MS DOS and MS Windows, it may have form "A:", "B:", ...
```

GROUP 2: Manipulating directory paths and file names:

```
[splitDirFile p] returns {dir, file} where file is the last arc in p, and dir is the path preceding that arc. A typical use is to split a path into the directory part (dir) and the filename (file).
```

```
[joinDirFile {dir, file}] returns the path p obtained by extending the path dir with the arc file.
```

```
[dir p] equals #dir (splitDirFile p).
```

```
[file p] equals #file (splitDirFile p).
```

GROUP 3: Manipulating file names and extensions:

```
[splitBaseExt s] returns {base, ext} where ext = NONE if s has no extension, and ext = SOME e if s has extension e; base is the part of s preceding the extension. A path s is considered having no extension if its last arc contains no extension separator (typically ".") or contains an extension separator only as its leftmost character, or contains an extension separator as its right-most character. Hence none of "a.b/cd", "a/.login", "a.", ". .", ". ." and ". ." has an extension.
```

```
[joinBaseExt {base, ext}] returns an arc composed of the base name and the extension (if different from NONE). It is a left inverse of splitBaseExt, so joinBaseExt (splitBaseExt s) = s, but the opposite does not hold (since the extension may be empty, or may contain extension separators).
```

```
[ext s] equals #ext (splitBaseExt s).
```

```
[base s] equals #base (splitBaseExt s).
```

## Module Polygdbm

*Polygdbm* -- GNU gdbm persistent polymorphic hashtables -- requires Dynlib

```
type ('key, 'data) table
exception NotFound
exception AlreadyThere
exception NotWriter
exception Closed
exception GdbmError of string
val withtable : string * Gdbm.openmode -> (('key, 'data) table -> 'a) -> 'a
val add : ('key, 'data) table -> 'key * 'data -> unit
val insert : ('key, 'data) table -> 'key * 'data -> unit
val find : ('key, 'data) table -> 'key -> 'data
val peek : ('key, 'data) table -> 'key -> 'data option
val haskey : ('key, 'data) table -> 'key -> bool
val remove : ('key, 'data) table -> 'key -> unit
val listKeys : ('key, 'data) table -> 'key list
val numItems : ('key, 'data) table -> int
val listItems : ('key, 'data) table -> ('key * 'data) list
val app : ('key * 'data -> unit) -> ('key, 'data) table -> unit
val map : ('key * 'data -> 'a) -> ('key, 'data) table -> 'a list
val fold : ('key * 'data * 'a -> 'a) -> 'a -> ('key, 'data) table -> 'a
val fastwrite : bool ref
val reorganize : ('key, 'data) table -> unit
```

[('key, 'data) table] is the type of an opened table with keys of type 'key and associated values of type 'data. The actual values of type 'key and 'data cannot contain function closures or abstract values. Values involving references (even circular values) can be stored, but the identity of references is preserved only with every single key or value stored, not across several different values.

The Polygdbm table files of are not portable across platforms, because word size and endianness affects the lay-out of values.

A value of type table can be used only in the argument f to the withtable function. This makes sure that the table is closed after use.

[withtable {nam, mod} f] first opens the table db in file nam with mode mod, then applies f to db, then closes db. Makes sure to close db even if an exception is raised during the evaluation of f(db). Raises GdbmError with an informative message in case the table cannot be opened. E.g. the table cannot be opened for reading if already opened for writing, and cannot be opened for writing if already opened for reading.

[add db {k,v}] adds the pair (k, v) to db. Raises AlreadyThere if there is a pair (k, \_) in db already. Raises NotWriter if db is not opened in write mode.

[insert db {k, v}] adds the pair (k, v) to db, replacing any pair (k, \_) at k if present. Raises NotWriter if db is not opened in write mode.

[find{db, k}] returns v if the pair (k, v) is in db; otherwise raises NotFound.

[peek db k] returns SOME v if the pair (k, v) is in db; otherwise returns NONE.

[haskey{db, k}] returns true if there is a pair (k, \_) in db; otherwise returns false.

[remove db k] deletes the pair (k, \_) from the table if present; otherwise raises NotFound. Raises NotWriter if db is not opened in write mode.

```
[listKeys db] returns a list of all keys in db in an unspecified order.
[numItems db] is the number of (key, value) pairs in db. Equivalent to length(listKeys db).
[listItems db] returns a list of all (key, value) pairs in db in some order. List.map (fn key => (key, find(db,key))) (listKeys db)
[app f db] is equivalent to List.app f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the effect is unpredictable.
[map f db] is equivalent to List.map f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.
[fold f a db] is equivalent to
 List.foldr (fn ((k, v), r) => f(k, v, r)) a (listItems db)
provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.
[fastwrite] can be set to speed up writes to a table. By default, !fastwrite is false and every write to a table will be followed by file system synchronization. This is safe, but slow if you perform thousands of writes. However, if !fastwrite is true when calling withtable, then writes may not be followed by synchronization, which may speed up writes considerably. In any case, the file system is synchronized before withtable returns.
[reorganize db] has no visible effect, but may be called after a lot of deletions to shrink the size of the table file.
```

## Module Polyhash

*Polyhash* -- polymorphic hashables as in the *SML/NJ Library*

```
type ('key, 'data) hashtable
val mkTable : ('key -> int) * ('key * 'key -> bool) -> int * exn
 -> ('key, 'data) hashtable
val numItems : ('key, 'data) hashtable -> int
val insert : ('key, 'data) hashtable -> 'key * 'data -> unit
val peekInsert : ('key, 'data) hashtable -> 'key * 'data
 -> 'data option
val find : ('key, 'data) hashtable -> 'key -> 'data
val peek : ('key, 'data) hashtable -> 'key -> 'data option
val remove : ('key, 'data) hashtable -> 'key -> 'data
val listItems : ('key, 'data) hashtable -> ('key * 'data) list
val apply : ('key * 'data -> unit) -> ('key, 'data) hashtable -> unit
val map : ('key * 'data -> 'res) -> ('key, 'data) hashtable
 -> ('key, 'res) hashtable
val filter : ('key * 'data -> bool) -> ('key, 'data) hashtable -> unit
val transform : ('data -> 'res) -> ('key, 'data) hashtable
 -> ('key, 'res) hashtable
val copy : ('key, 'data) hashtable -> ('key, 'data) hashtable
val bucketSizes : ('key, 'data) hashtable -> int list
Polymorphic hash primitives from Caml Light
val hash : 'key -> int
val hash_param : int -> int -> 'key -> int
val mkPolyTable : int * exn -> ('key, 'data) hashtable
```

`[('key, 'data) hashtable]` is the type of hashables with keys of type 'key and data values of type 'data.

`[mkTable (hashVal, sameKey) (sz, exc)]` returns a new hashtable, using hash function hashVal and equality predicate sameKey. The sz is a size hint, and exc is the exception raised by function find. It must be the case that sameKey(k1, k2) implies hashVal(k1) = hashVal(k2) for all k1, k2.

`[numItems htbl]` is the number of items in the hash table.

`[insert htbl (k, d)]` inserts data d for key k. If k already had an item associated with it, then the old item is overwritten.

`[find htbl k]` returns d, where d is the data item associated with key k, or raises the exception (given at creation of htbl) if there is no such d.

`[peek htbl k]` returns SOME d, where d is the data item associated with key k, or NONE if there is no such d.

`[peekInsert htbl (k, d)]` inserts data d for key k, if k is not already in the table, returning NONE. If k is already in the table, and the associated data value is d', then returns SOME d' and leaves the table unmodified.

`[remove htbl k]` returns d, where d is the data item associated with key k, removing d from the table; or raises the exception if there is no such d.

`[listItems htbl]` returns a list of the (key, data) pairs in the hashtable. `[apply f htbl]` applies function f to all (key, data) pairs in the hashtable, in some order.

`[map f htbl]` returns a new hashtable, whose data items have been obtained by applying f to the (key, data) pairs in htbl. The new tables have the same keys, hash function, equality predicate, and exception, as htbl.

`[filter p htbl]` deletes from htbl all data items which do not satisfy predicate p.





```

Date of int * int * int psql date yyyy-mm-dd
Time of int * int * int psql time hh:mm:ss
DateTime of Date.date psql datetime
Oid of oid psql oid
Bytea of Word8Array.array psql bytea
NullVal psql NULL

val getdynfield : dbresult -> int -> int -> dynval
val getdynfncp : dbresult -> int -> dynval vector
val getdynfncps : dbresult -> dynval vector
val dynval2s : dynval -> string

Bulk copying to or from a table

val copytableto : dbconn * string * (string -> unit) -> unit
val copytablefrom : dbconn * string * ((string -> unit) -> unit) -> unit

Some standard ML and Postgres types:

datatype dynotype =
 BoolTy ML bool psql bool
 IntTy ML int psql int4
 RealTy ML real psql float8, float4
 StringTy ML string psql text, varchar
 DateTy ML (yyyy, mth, day) psql date
 TimeTy ML (hh, mm, ss) psql time
 DateTimeTy ML Date.date psql datetime, abstime
 OidTy ML oid psql oid
 ByteArrTy ML Word8Array.array psql bytea
 UnknownTy of oid

val frontag : dynotype -> string
val ftype : dbresult -> int -> dynotype
val ftypes : dbresult -> dynotype Vector.vector
val applyto : 'a -> ('a -> 'b) -> 'b

Formatting the result of a database query as an HTML table

val formattable : dbresult -> Msp.wseq
val showquery : dbconn -> string -> Msp.wseq

```

[dbconn] is the type of connections to a PostgreSQL database.

[dbresult] is the type of result sets from SQL queries.

[oid] is the type of PostgreSQL internal object identifiers.

[openbase { dbhost, dbport, dboptions, dbtty, dbname, dbuser, dbpwd }]  
opens a connection to a PostgreSQL database server on the given  
host (default the local one) on the given port (default 5432), with  
the given options (default the empty string), with error logging on  
the given tty (default?), to the given database (defaults to the  
user's login name), for the given user name (defaults to the  
current user's login name), and the given password (default none).  
The result is a connection which may be used in subsequent queries.

[closebase dbconn] closes the database connection. No further  
queries can be executed.

[db dbconn] returns the name of the database.

[host dbconn] returns SOME h, where h is the database server host  
name, if the connection uses the Internet; returns NONE if the  
connection is to a socket on the local server.

[options dbconn] returns the options given when opening the database.

[port dbconn] returns the port number of the connection.

[tty dbconn] returns the name of the tty used for logging.

[status dbconn] returns true if the connection is usable, false otherwise.

[reset dbconn] attempts to close and then reopen the connection to the database server.

[errmsg dbconn] returns NONE if no error occurred, and SOME msg if an error occurred, where msg describes the error.

[execute dbconn query] sends an SQL query to the database server for execution, and returns a resultset dbres.

[resultstatus dbres] returns the status of the result set dbres. After a select query that succeeded, it will be Tuples\_ok.

[ntuples dbres] returns the number of tuples in the result set after a query.

[cmdtuples dbres] returns the number of tuples affected by an insert, update, or delete SQL command.

[nfields dbres] returns the number of fields in each tuple after a query.

[fname dbres fno] returns the name of field number fno (in the result set after a query). The fields are numbered 0, 1, ...

[fnames dbres] returns a vector of the field names (in the result set after a query).

[fnumber dbres fname] returns SOME i where i is the number (0, 1, ...) of the field called fname (in the result set after a query), if the result set contains such a field name; returns NONE otherwise.

[ftype dbres fno] returns the dyntype of field number fno (in the result set after a query).

[ftypes dbres] returns a vector of the dyntypes (in the result set after a query).

[frontag dt] returns the name of the preferred PostgreSQL type used to represent values of the dyntype dt. This may be used when building 'create table' statements.

[getint dbres fno tupno] returns the integer value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getreal dbres fno tupno] returns the floating-point value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getstring dbres fno tupno] returns the string value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getdate dbres fno tupno] returns the date (yyyy, mth, day) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[gettime dbres fno tupno] returns the time-of-day (hh, mm, ss) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a time.

[getdatetime dbres fno tupno] returns the Date.date value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a

date.

[getbool dbres fno tupno] returns the boolean value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[isnull dbres fno tupno] returns true if the value of field number fno in tuple tupno of result set dbres is NULL; false otherwise.

[getdynfield dbres fno tupno] returns the value of field number fno in tuple tupno of result set dbres as a dynval (a wrapped value). A NULL value is returned as NullVal. Note that the partial application (getdynfield dbres fno) precomputes the type of the field fno. Hence it is far more efficient to compute

```
let val getfno = getdynfield dbres fno
 in tabulate(ntuples dbres, getfno) end
than to compute
```

```
let fun getfno tupno = getdynfield dbres fno tupno
 in tabulate(ntuples dbres, getfno) end
because the latter repeatedly computes the type of the field.
```

[getdyn tup dbres tupno] returns the fields of tuple tupno in result set dbres as a vector of dynvals.

[getdyn tups dbres] returns all tuples of result set dbres as a vector of vectors of dynvals.

[dynval2s dv] returns a string representing the dynval dv.

[applyto x f] computes f(x). This is convenient for applying several functions (given in a list or vector) to the same value:

```
map (applyto 5) (tabulate(3, getdynfield dbres))
equals
[getdynfield dbres 0 5, getdynfield dbres 1 5, getdynfield dbres 2 5]
```

[copytableto(dbconn, tablename, put)] executes a "COPY TABLE" statement, applies the function put to every tuple of the table, represented as a line of text (not terminated by newline \n), and cleans up at the end. For instance, to copy the contents of a table t to a text stream s (one tuple on each line), define

```
fun put line =
 (TextIO.output(s, line); TextIO.output(s, "\n"))
and execute
 copytableto(dbconn, "t", put).
```

[copytablefrom(dbconn, tablename, useput)] executes a "COPY TABLE FROM" statement, creates a put function for copying lines to the table, passes the put function to useput, and cleans up at the end.

The put function may be called multiple times for each line (tuple); the end of each line is indicated with the newline character "\n" as usual. For instance, to copy the contents of a text stream s to a table t, define

```
fun useput put =
 while not (TextIO.endofstream s) do put(TextIO.inputline s);
and execute
 copytablefrom(dbconn, "t", useput).
Note that TextIO.inputline preserves the newline at the end of each line.
```

[formattable dbresult] returns a wseq representing an HTML table. The HTML table has a column for every field in the dbresult. The first row is a table header giving the names of the fields in the dbresult. The remaining rows correspond to the tuples in the dbresult, in the order they are provided by the database server. Null fields are shown as NULL.

[showquery dbconn query] sends the SQL query to the database server, then uses formattable to format the result of the query.

## Module Process

OS.Process -- SML Basis Library

eqtype status

```
val success : status
val failure : status
```

```
val system : string -> status
```

```
val atExit : (unit -> unit) -> unit
```

```
val exit : status -> 'a
```

```
val terminate : status -> 'a
```

```
val getEnv : string -> string option
```

Portable functions for manipulating processes.

[success] is the unique status value that signifies successful termination of a process. Note: MS DOS (sometimes) believes that all processes are successful.

[failure] is a status value that signifies an error during execution of a process. Note that in contrast to the success value, there may be several distinct failure values.

[system cmd] asks the operating system to execute command cmd, and returns a status value.

[atExit act] registers the action act to be executed when the current SML program calls Process.exit. Actions will be executed in reverse order of registration.

[exit i] executes all registered actions, then terminates the SML process with completion code i.

[terminate i] terminates the SML process with completion code i (but without executing the registered actions).

[getEnv env] returns SOME s if the environment variable env is defined and is associated with the string s; otherwise NONE.

## Module Random

*Random* -- random number generator

type generator

```
val newgenseed : real -> generator
val newgen : unit -> generator
val random : generator -> real
val randomlist : int * generator -> real list
val range : int * int -> generator -> int
val rangelist : int * int -> int * generator -> int list
```

[generator] is the type of random number generators, here the linear congruential generators from Paulson 1991, 1996.

[newgenseed seed] returns a random number generator with the given seed.

[newgen ()] returns a random number generator, taking the seed from the system clock.

[random gen] returns a random number in the interval [0..1).

[randomlist (n, gen)] returns a list of n random numbers in the interval [0,1).

[range (min, max) gen] returns an integral random number in the range [min, max]. Raises Fail if min > max.

[rangelist (min, max) (n, gen)] returns a list of n integral random numbers in the range [min, max]. Raises Fail if min > max.

## Module Real

*Real* -- SML Basis Library

type real = real

exception Div  
and Overflow

```
val ~ : real -> real
val + : real * real -> real
val * : real * real -> real
val - : real * real -> real
val / : real * real -> real
val abs : real -> real
val min : real * real -> real
val max : real * real -> real
val sign : real -> int
val compare : real * real -> order

val sameSign : real * real -> bool
val codeDefault : real -> real
val fromDefault : real -> real
val fromInt : int -> real

val floor : real -> int
val ceil : real -> int
val trunc : real -> int
val round : real -> int

val > : real * real -> bool
val >= : real * real -> bool
val < : real * real -> bool
val <= : real * real -> bool
val == : real * real -> bool
val != : real * real -> bool
val ?= : real * real -> bool

val toString : real -> string
val fromString : string -> real option
val scan : (char, 'a) StringCvt.reader -> (real, 'a) StringCvt.reader
val fmt : StringCvt.realfmt -> real -> string
```

```
[~]
[*]
[/]
[+]
[-]
[.]
[>]
[>=]
[<]
[<=]
```

[<=] are the usual operations on defined reals (excluding NaN and Inf).

[abs x] is x if x >= 0, and -x if x < 0, that is, the absolute value of x.

[min(x, y)] is the smaller of x and y.

[max(x, y)] is the larger of x and y.

[sign x] is -1, 0, or 1, according as x is negative, zero, or positive.

[compare(x, y)] returns LESS, EQUAL, or GREATER, according as x is less than, equal to, or greater than y.

[sameSign(x, y)] is true iff sign x = sign y.

[toDefault x] is x.

[fromDefault x] is x.

[fromInt i] is the floating-point number representing integer i.

[floor r] is the largest integer  $\leq r$  (rounds towards minus infinity).  
May raise Overflow.

[ceil r] is the smallest integer  $\geq r$  (rounds towards plus infinity).  
May raise Overflow.

[trunc r] is the numerically largest integer between  $r$  and zero  
(rounds towards zero). May raise Overflow.

[round r] is the integer nearest to  $r$ , using the default rounding  
mode. May raise Overflow.

[=(x, y)] is equivalent to  $x=y$  in Moscow ML (because of the  
absence of NaNs and Infs).

[!=(x, y)] is equivalent to  $x \neq y$  in Moscow ML (because of the  
absence of NaNs and Infs).

[?(x, y)] is false in Moscow ML (because of the absence of NaNs  
and Infs).

[fmt spec r] returns a string representing  $r$ , in the format  
specified by spec (see below). The requested number of digits must  
be  $>= 0$  in the SCI and FIX formats and  $> 0$  in the GEN format;  
otherwise size is raised, even in a partial application  $\text{fmt}(\text{spec})$ .

| spec         | description                        | C printf |
|--------------|------------------------------------|----------|
| SCI NONE     | scientific, 6 digits after point   | %e       |
| SCI (SOME n) | scientific, n digits after point   | %.ne     |
| FIX NONE     | fixed-point, 6 digits after point  | %f       |
| FIX (SOME n) | fixed-point, n digits after point  | %.nf     |
| GEN NONE     | auto choice, 12 significant digits | %.12g    |
| GEN (SOME n) | auto choice, n significant digits  | %.ng     |

[toString r] returns a string representing  $r$ , with automatic choice  
of format according to the magnitude of  $r$ .  
Equivalent to  $(\text{fmt } (\text{GEN NONE}) r)$ .

[fromString s] returns  $\text{SOME}(r)$  if a floating-point numeral can be  
scanned from a prefix of string  $s$ , ignoring any initial whitespace;  
returns  $\text{NONE}$  otherwise. The valid forms of floating-point numerals  
are described by:

```
[+-]?(((0-9)+(\.[0-9]+)?|(\.[0-9]+)))([eE][+-]?[0-9]+)?
```

[scan getc charsrc] attempts to scan a floating-point number from  
the character source  $\text{charsrc}$ , using the accessor  $\text{getc}$ , and ignoring  
any initial whitespace. If successful, it returns  $\text{SOME}(r, \text{rest})$   
where  $r$  is the number scanned and  $\text{rest}$  is the unused part of the  
character source. The valid forms of floating-point numerals  
are described by:

```
[+-]?(((0-9)+(\.[0-9]+)?|(\.[0-9]+)))([eE][+-]?[0-9]+)?
```

## Module Regex

Regex -- regular expressions a la POSIX 1003.2 -- requires Dynlib

exception Regex of string

type regex

A compiled regular expression

datatype cflag =

  | Extended  
  | Icase  
  | Newline

Compile POSIX extended REs  
Compile case-insensitive match  
Treat \n in target string as new line

datatype eflag =

  | Notbol  
  | Noteol

Do not match ^ at beginning of string  
Do not match \$ at end of string

val regcomp : string -> cflag list -> regex

val regexec : regex -> eflag list -> string -> substring vector option  
val regexecBool : regex -> eflag list -> string -> bool

val regnexec : regex -> eflag list -> substring  
-> substring vector option

val regnexecBool : regex -> eflag list -> substring -> bool

val regmatch : { pat : string, tgt : string } -> cflag list  
-> eflag list -> substring vector option

val regmatchBool : { pat : string, tgt : string } -> cflag list  
-> eflag list -> bool

datatype replacer =

  | Str of string  
  | Sus of int  
  | Tr of (string -> string) \* int  
  | Trs of substring vector -> string

A literal string  
The i'th parenthesized group  
Transformation of i'th group  
Transformation of all groups

val replacer : regex -> replacer list -> string -> string

val replace : regex -> replacer list -> string -> string

val substitute : regex -> (string -> string) -> string -> string

val substitute : regex -> (string -> string) -> string -> string

val tokens : regex -> string -> substring list

val fields : regex -> string -> substring list

val map : regex -> (substring vector -> 'a) -> string -> 'a list

val app : regex -> (substring vector -> unit) -> string -> unit

val fold : regex  
-> (substring \* 'a -> 'a) \* (substring vector \* 'a -> 'a)

-> 'a -> string -> 'a

This structure provides pattern matching with POSIX 1003.2 regular  
expressions.

The form and meaning of Extended and Basic regular expressions are  
described below. Here R and S denote regular expressions; m and n  
denote natural numbers; L denotes a character list; and d denotes a  
decimal digit:

| Extended | Basic | Meaning                     |
|----------|-------|-----------------------------|
| c        | c     | Match the character c       |
| .        | .     | Match any character         |
| R*       | R*    | Match R zero or more times  |
| R+       | R+    | Match R one or more times   |
| R S      | R S   | Match R or S                |
| R?       | R?    | Match R or the empty string |
| R{m}     | R{m}  | Match R exactly m times     |
| R{m,}    | R{m,} | Match R at least m times    |

```

R{m,n} R\{m,n} Match R at least m and at most n times
[L] [L] Match any character in L
[^L] [^L] Match any character not in L
^ ^ Match at string's beginning
$ $ Match at string's end
(R) \ (R) Match R as a group; save the match
\d \d Match the same as previous group d
\\ \\ Match \ --- similarly for *.{,}$
+ + Match + --- similarly for |?{}()

```

Some example character lists L:

```

[aeiou] Match vowel: a or e or i or o or u
[0-9] Match digit: 0 or 1 or 2 or ... or 9
[^-0-9] Match non-digit
[-+*/^] Match - or + or * or / or ^
[0-9a-zA-F] Match lowercase letter or hyphen (-)
[0-9a-z] Match hexadecimal digit
[:alnum:] Match letter or digit
[:alpha:] Match letter
[:cntrl:] Match ASCII control character
[:digit:] Match decimal digit; same as [0-9]
[:graph:] Same as [:print:] but not [:space:]
[:lower:] Match lowercase letter
[:print:] Match printable character
[:punct:] Match punctuation character
[:space:] Match SML # " '\r\n', #'\t', #'\v', #'\f'
[:upper:] Match uppercase letter
[:xdigit:] Match hexadecimal digit; same as [0-9a-zA-F]
[:lower:laeø] Match lowercase Danish letters (ISO Latin 1)

```

Remember that backslash (\) must be escaped as "\\ " in SML strings.

[regcomp pat cflags] returns a compiled representation of the regular expression pat. Raises Regex in case of failure.

[cflag] is the type of compilation flags with the following meanings:

```

[Extended] : compile as POSIX extended regular expression.
[IgnoreCase] : compile case-insensitive match.
[Newline] : make the newline character \n significant, so ^ matches
 just after newline (\n), and $ matches just before \n.

```

Example: Match SML integer constant:

```
regcomp "^-[0-9]+$" [Extended]
```

Example: Match SML alphanumeric identifier:

```
regcomp "[a-zA-Z0-9_]*$" [Extended]
```

Example: Match SML floating-point constant:

```
regcomp "[+-]?[0-9]+(\.[0-9]+)?[eE][+-]?[0-9]+$" [Extended]
```

Example: Match any HTML start tag; make the tag's name into a group:

```
regcomp "<([[:alnum:]]+)>*" [Extended]
```

[regexec regex eflags s] returns SOME(vec) if some substring of s matches regex, NONE otherwise. In case of success, vec is the match vector, a vector of substrings such that vec[0] is the (longest leftmost) substring of s matching regex, and vec[1], vec[2], ... are substrings matching the parenthesized groups in pat (numbered 1, 2, ... from left to right in the order of their opening parentheses). For a group that does not take part in the match, such as (ab) in "(ab)|(cd)" when matched against the string "xcdy", the corresponding substring is the empty substring at the beginning of the underlying string. For a group that takes part in the match repeatedly, such as the group (b+) in "(a(b+))\*" when matched against "babbbab", the corresponding substring is the last (rightmost) one matched.

[eflag] is the type of end flags with the following meaning:

[Notbol] : do not match ^ at beginning of string.

[Noteol] : do not match \$ at end of string.

[regexecBool regex eflags s] returns true if some substring of s matches regex, false otherwise. Equivalent to, but faster than, Option.isSome(regexec regex eflags s).

[regnec regex eflags sus] returns SOME(vec) if some substring of sus matches regex, NONE otherwise. The substrings returned in the vector vec will have the same base string as sus. Useful e.g. for splitting a string into fragments separated by substrings matching some regular expression.

[regnecxBool regex eflags sus] returns true if some substring of sus matches regex, false otherwise. Equivalent to, but faster than, Option.isSome(regnecx regex eflags sus).

[regmatch { pat, tgt } cflags eflags] is equivalent to regexec (regcomp pat cflags) eflags tgt but more efficient when the compiled regex is used only once.

[regmatchBool { pat, tgt } cflags eflags] is equivalent to regexecxBool (regcomp pat cflags) eflags tgt but more efficient when the compiled regex is used only once.

[replace regex repl s] finds the (disjoint) substrings of s matching regex from left to right, and returns the string obtained from s by applying the replacer list repl to every such substring (see below). Raises Regex if it fails to make progress in decomposing s, that is, if regex matches an empty string at the head of s or immediately after a previous regex match. Example use: delete all HTML tags from s:  
replace (regcomp "<[^>]+>") [Extended] [] s

[replacer regex repl s] finds the leftmost substring bi of s matching regex, and returns the string resulting from s by applying the replacer list repl to the match vector vec1 (see below).

Let x0 be a substring matching the entire regex and xi be the substring matching the i'th parenthesized group in regex; thus xi = vec[i] where vec is the match vector (see regexec above). Then a single replacer evaluates to a string as follows:

```

[Str s] gives the string s
[Sub i] gives the string xi
[Tr (f, i)] gives the string f(xi)
[Trs fs] gives the string f(vec)

```

A replacer list repl evaluates to the concatenation of the results of the replacers. The replacers are applied from left to right.

[substitute regex f s] finds the (disjoint) substrings bi, ..., bn of s matching regex from left to right, and returns the string obtained from s by replacing every bi by f(bi). Function f is applied to the matching substrings from left to right. Raises Regex if it fails to make progress in decomposing s. Equivalent to replace regex [Tr (f, 0)] s

[subtutel regex f s] finds the leftmost substring b of s matching regex, and returns the string obtained from s by replacing that substring by f(b). Equivalent to replace regex [Tr (f, 0)] s

[map regex f s] finds the (disjoint) substrings of s matching regex from left to right, applies f to the match vectors vec1, ..., vecn, and returns the list [f(vec1), ..., f(vecn)]. Raises Regex if it fails to make progress in decomposing s.

[app regex f s] finds the (disjoint) substrings of s matching regex from left to right, and applies f to the match vectors vec1, ..., vecn. Raises Regex if the regex fails to make progress in decomposing s.

[fields regex s] returns the list of fields in s, from left to right. A field is a (possibly empty) maximal substring of s not containing any delimiter. A delimiter is a maximal substring that matches regex. The eflags Notbol and Noteol are set. Raises Regex if it fails to make progress in decomposing s.

Example use:

```
fields (regcomp " *; * [] "56; 23 ; 22;; 89; 99"
```

[tokens regex s] returns the list of tokens in s, from left to right. A token is a non-empty maximal substring of s not containing any delimiter. A delimiter is a maximal substring that matches regex. The eflags Notbol and Noteol are set. Raises Regex if it fails to make progress in decomposing s. Equivalent to List.filter (not o Substring.isEmpty) (fields regex s)

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character "#", then

```
"abc||def" contains three fields: "abc" and "" and "def"
"abc||def" contains two tokens: "abc" and "def"
```

[fold regex (fa, fb) e s] finds the (disjoint) substrings b<sub>1</sub>, ..., b<sub>n</sub> of s matching regex from left to right, and splits s into the substrings

```
a0, b1, a1, b2, a2, ..., bn, an
```

where n >= 0 and where a<sub>0</sub> is the (possibly empty) substring of s preceding the first match, and a<sub>i</sub> is the (possibly empty) substring between the matches b<sub>i</sub> and b<sub>(i+1)</sub>. Then it computes and returns fa(an, fb(vecn, ..., fa(a1, fb(vec1, fa(a0, e))) ...)

where veci is the match vector corresponding to b<sub>i</sub>. Raises Regex if it fails to make progress in decomposing s.

If we define the auxiliary functions

```
fun fapp f (x, r) = f x :: r
fun get i vec = Substring.string(Vector.sub(vec, i))
```

then

```
map regex f s = List.rev (fold regex (#2, fapp f) [] s)
app regex f s = fold regex (ignore, f o #1) () s
fields regex s = List.rev (fold regex (op ::, #2) [] s)
substitute regex f s =
 Substring.concat(List.rev
 (fold regex (op ::, fapp (Substring.all o f o get 0)) [] s))
```

## Module SML90

SML90 -- part of the initial basis of the 1990 Definition

Math

```
val sqrt : real -> real
val sin : real -> real
val cos : real -> real
val arctan : real -> real
val exp : real -> real
val ln : real -> real
```

Strings

```
val chr : int -> string
val ord : string -> int
val explode : string -> string list
val implode : string list -> string
```

```
exception Abs
and Diff
and Exp
and Floor
and Neg
and Prod
and Sum
and Mod
and Quot
```

Input/output

```
type instream and outstream
val std_in : instream
val open_in : string -> instream
val input : instream * int -> string
val lookahead : instream -> string
val close_in : instream -> unit
val end_of_stream : instream -> bool
val std_out : outstream
val open_out : string -> outstream
val output : outstream * string -> unit
val close_out : outstream -> unit
```

## Module Signal

Signal -- SML Basis Library

eqtype signal

```
val abort : signal
val alarm : signal
val bus : signal
val fpe : signal
val hup : signal
val ill : signal
val int : signal
val kill : signal
val pipe : signal
val quit : signal
val segv : signal
val term : signal
val usr1 : signal
val usr2 : signal
val chld : signal
val cont : signal
val stop : signal
val tstp : signal
val ttin : signal
val ttou : signal
```

```
val toWord : signal -> Word.word
val fromWord : Word.word -> signal
```

---

[signal] is the type of Unix/Posix-style signals, which can be sent to another process.

[toWord sig] returns the signal number as an unsigned word.

[fromWord w] returns the signal whose number is w.

[abort] is SIGABRT, the abort signal from abort(3).

[alarm] is SIGALRM, a timer signal from alarm(1).

[bus] is SIGBUS, a bus error.

[fpe] is SIGFPE, a floating point exception.

[hup] is SIGHUP, a hangup.

[ill] is SIGILL, an illegal instruction.

[int] is SIGINT, an interrupt.

[kill] is SIGKILL, the kill signal.

[pipe] is SIGPIPE, a broken pipe.

[quit] is SIGQUIT, a quit from keyboard.

[segv] is SIGSEGV, a segmentation violation.

[term] is SIGTERM, the termination signal.

[usr1] is SIGUSR1, the first user signal.

[usr2] is SIGUSR2, the second user signal.

[chld] is SIGCHLD, child process stopped or terminated.

[cont] is SIGCONT, continue if stopped.

[stop] is SIGSTOP, signal to stop process.

[tstp] is SIGTSTP, a stop signal typed at the tty.

[ttin] is SIGTTIN, tty input for background process.

[ttou] is SIGTTOU, tty output for background process.



## Module Socket

Socket -- SML Basis Library -- requires Dynlib

```
type ('addressfam, 'socketype) sock
type 'addressfam sock_addr
```

```
Socket types
type dgram : ('a, active stream) sock * Word8Vector.vector buf -> int
type 'a stream : ('a, active stream) sock * Word8Array.array buf -> int
type passive : ('a, active stream) sock * Word8Vector.vector
type active : ('a, active stream) sock * Word8Array.array buf
```

```
Socket protocol families
type pf_file : The Unix file protocol family
type pf_inet : The Internet protocol family
```

```
Address constructors
val fileAddr : string -> pf_file sock_addr
val inetAddr : string -> int -> pf_inet sock_addr
```

```
Socket constructors
val fileStream : unit -> (pf_file, 'a stream) sock
val fileDgram : unit -> (pf_file, dgram) sock
val inetStream : unit -> (pf_inet, 'a stream) sock
val inetDgram : unit -> (pf_inet, dgram) sock

val accept : ('a, passive stream) sock
-> ('a, active stream) sock * 'a sock_addr
val bind : ('a, 'b) sock * 'a sock_addr -> unit
val connect : ('a, 'b) sock * 'a sock_addr -> unit
val listen : ('a, passive stream) sock * int -> unit
val close : ('a, 'b) sock -> unit
```

```
Socket management
datatype shutdown_mode =
| NO_RECVS
| NO_SENDS
| NO_RECVS_OR_SENDS
val shutdown : ('a, 'b stream) sock * shutdown_mode -> unit
```

```
type sock_desc
val sockDesc : ('a, 'b) sock -> sock_desc
val sameDesc : sock_desc * sock_desc -> bool
val compare : sock_desc * sock_desc -> order
val select :
{ rds : sock_desc list, wrs : sock_desc list, exs : sock_desc list,
 timeout : Time.time option }
-> { rds : sock_desc list, wrs : sock_desc list, exs : sock_desc list }
```

```
val getinetaddr : pf_inet sock_addr -> string
```

```
Socket I/O option types
type out_flags = { don't_route : bool, oob : bool }
type in_flags = { peek : bool, oob : bool }
```

```
type 'a buf = { buf : 'a, ofs : int, size : int option }
```

```
Socket output operations
val recvVec : ('a, active stream) sock * Word8Vector.vector buf -> int
val sendArr : ('a, active stream) sock * Word8Array.array buf -> int
val sendVec' : ('a, active stream) sock * Word8Vector.vector buf
* out_flags -> int
val sendArr' : ('a, active stream) sock * Word8Array.array buf
* out_flags -> int
val sendVecTo : ('a, dgram) sock * 'a sock_addr * Word8Vector.vector buf
-> int
val sendArrTo : ('a, dgram) sock * 'a sock_addr * Word8Array.array buf
```

```
-> int
val sendVecTo : ('a, dgram) sock * 'a sock_addr * Word8Vector.vector buf
* out_flags -> int
val sendArrTo : ('a, dgram) sock * 'a sock_addr * Word8Array.array buf
* out_flags -> int
```

Socket input operations

```
val recvVec : ('a, active stream) sock * int -> Word8Vector.vector
val recvArr : ('a, active stream) sock * Word8Array.array buf -> int
val recvVec' : ('a, active stream) sock * int * in_flags
-> Word8Vector.vector
val recvArr' : ('a, active stream) sock * Word8Array.array buf * in_flags
-> int
val recvVecFrom : ('a, dgram) sock * int
-> Word8Vector.vector * 'a sock_addr
val recvArrFrom : ('a, dgram) sock * Word8Array.array buf
-> int * 'a sock_addr
val recvVecFrom' : ('a, dgram) sock * int * in_flags
-> Word8Vector.vector * 'a sock_addr
val recvArrFrom' : ('a, dgram) sock * Word8Array.array buf * in_flags
-> int * 'a sock_addr
```

Structure Socket defines functions for creating and using sockets, a means for communication between SML processes on the same machine or via a network.

[('addressfam, 'socketype) sock] is the type of sockets with address family 'addressfam and having type 'socketype.

[ 'addressfam sock\_addr] is the type of sockets addresses.

The possible address (protocol) families are

```
type pf_file The Unix address family (file)
type pf_inet The Internet address family
```

The possible socket types are

```
type dgram datagram sockets
type 'a stream stream sockets
type passive passive stream sockets
type active active, or connected, stream sockets
```

[fileAddr fname] returns a socket address for the Unix protocol family, created from the given file name fname.

[inetAddr inetaddr portno] returns a socket address for the Internet protocol family, created from the given Internet number (e.g. "130.225.40.253") and port number (e.g. 8080).

[fileStream ()] returns a new stream socket for the Unix protocol family.

[fileDgram ()] returns a new datagram socket for the Unix protocol family.

[inetStream ()] returns a new stream socket for the Internet protocol family.

[inetDgram ()] returns a new datagram socket for the Internet protocol family.

[accept sock] extracts the first connection on the queue of pending connections to sock. Returns (sock', addr) where sock' is a copy of the socket sock, bound to that connection, and addr is the address of the communications counterpart (the other end of the connection). Blocks if no connections are pending. The stream socket sock must have been assigned a name (with bind) and must be listening for connections (following a call to listen).

[bind sock addr] binds the socket sock to the address addr, that is, assigns the name addr to the socket. Binding a name in the

Unix protocol family creates a socket in the file system that must be deleted when it is no longer needed

[connect (sock, addr)] attempts to connect socket to the communications peer at address addr. If sock is a datagram socket, then addr is the address to which datagrams is to be sent, and the only address from which datagrams will be accepted. If sock is a stream socket, then addr specifies another socket to which to connect.

[listen (sock, queuelen)] enables the passive stream socket to accept incoming connections. The parameter queuelen specifies the maximal number of pending connections. Further connections from clients may be refused when this limit is reached.

[close sock] closes the socket.

[shutdown sock shutdown mode] shuts down socket sock for further communication, as specified by the shutdown\_mode parameter:

[NO\_RECVS] no further receives are allowed;

[NO\_SENDS] no further sends are allowed;

[NO\_RECVS\_OR\_SENDS] no further receives or sends are allowed.

[getinetaddr addr] returns the Internet number (e.g. "130.225.40.253") of the Internet socket address addr.

[ 'a buf] is the type of records { buf, ofs, size } which represent subvectors or subarrays:

if size = SOME s it represents buf[ofs..ofs+s-1];

if size = NONE it represents buf[ofs..len-1] where len is buf's length. When the subbuffer is used in a call, exception Subscript will be raised if ofs < 0 or size < 0 or ofs-size > len.

[sendVec (sock, vecbuf)] transmits the bytes from buffer vecbuf on the active stream socket sock. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[sendArr (sock, arrbuf)] is analogous til sendVec.

[sendVec' (sock, vecbuf, out\_flags)] transmits the bytes from buffer vecbuf on the active stream socket sock, observing the out\_flags. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[out\_flags] is the type of records { don't\_route, oob } in which the field don't\_route specifies whether routing should be bypassed, and the field oob specifies whether data should be sent out-of-band.

[sendArr' (sock, arrbuf, out\_flags)] is analogous til sendVec'.

[sendVecTo (sock, addr, vecbuf)] transmits the bytes from buffer vecbuf on the datagram socket sock to the target address addr. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[sendArrTo (sock, addr, arrbuf)] is analogous til sendVecTo.

[sendVecTo' (sock, addr, vecbuf, out\_flags)] transmits the bytes from buffer vecbuf on the datagram socket sock to the target address addr, observing the out\_flags. Returns the number of bytes sent. Blocks until sufficient space is available at the socket. See above for a description of vecbuf and out\_flags.

[sendArrTo' (sock, addr, arrbuf, out\_flags)] is analogous til sendVecTo'.

[recvVec (sock, n)] receives up to n bytes from the active stream socket sock. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to n bytes. Excess data are

not lost; they are available for subsequent receive calls.

[recvArr (sock, arrbuf)] receives bytes from the active stream socket sock into the subarray arrbuf, up to the available space. If #size(arrbuf) = SOME(s) the available space is s bytes; if #size(arrbuf) = NONE the available space is len - #ofs(arrbuf) bytes. Returns the number of bytes actually received. Blocks until some data become available at the socket. Excess data are not lost; they are available for subsequent receive calls.

[recvVec' (sock, n, in\_flags)] receives up to n bytes from the active stream socket sock, observing the in\_flags. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to n bytes. Data in excess of n bytes are not lost; they are available for subsequent receive calls.

[in\_flags] is the type of records { peek, oob } in which the field peek specifies that the data read should not be removed from the receive queue, and the field oob specifies that data may be received out-of-band.

[recvArr' (sock, arrbuf, in\_flags)] receives bytes from the active stream socket sock into the subarray arrbuf, observing the in\_flags, up to the available space. Returns the number of bytes actually received. Blocks until some data become available at the socket. Excess data are not lost; they are available for subsequent receive calls.

[recvVecFrom (sock, n)] receives up to n bytes from the datagram socket sock. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to n bytes.

[recvArrFrom (sock, arrbuf)] receives bytes from the datagram socket sock into the subarray arrbuf. Returns the number of bytes actually received. Blocks until some data become available at the socket.

[recvVecFrom' (sock, n, in\_flags)] receives up to n bytes from the datagram socket sock, observing the in\_flags (see above). Returns (vec, addr) where vec is a byte vector containing the bytes actually received, and addr is the source address of the message. Blocks until some data become available at the socket, then returns any available data, up to n bytes.

[recvArrFrom' (sock, arrbuf, in\_flags)] receives bytes from the datagram socket sock into the array buffer arrbuf, observing the in\_flags (see above). Returns (n, addr) where n is the number of bytes actually received, and addr is the source address of the message. Blocks until some data become available at the socket.

[sockDesc sock] returns a descriptor for the socket sock, to be used in a call to select.

[compare (sdl, sd2)] compares sdl and sd2 according to an unspecified total ordering, and returns LESS if sdl precedes sd2, returns GREATER if sdl precedes sd2, and returns EQUAL otherwise.

[sameDesc (sdl, sd2)] returns true if sdl and sd2 describe the same socket. Equivalent to compare(sdl, sd2) = EQUAL.

[select { rds, wrs, eks, timeout }] blocks the calling process until some input/output operations become possible on some sockets. The call will check the sockets described in rds for reading, those in wrs for writing, and those in eks for exceptional conditions. Returns { rds, wrs, eks } where rds now is a list of descriptors of sockets ready for reading, wrs are ready for writing, and eks have exceptional conditions. The order of the socket descriptors in the results is the same as their order in the corresponding arguments. If timeout is NONE then the call blocks until some input/output operations become possible; if timeout is SOME(t) then the call

blocks for at most time t.

A server socket is considered ready for reading if there is a pending connection which can be accepted with `'accept'`. A client socket is ready for writing when its connection is fully established.

## Module Splaymap

*Splaymap* -- applicative maps implemented by *splay-trees*  
 From *SML/NJ Lib 0.2*, copyright 1993 by AT&T Bell Laboratories

```
type ('key, 'a) dict
exception NotFound
val mkDict : ('key * 'key -> order) -> ('_key, '_a) dict
val insert : ('key, '_a) dict * 'key * 'a -> ('_key, '_a) dict
val find : ('key, '_a) dict * 'key -> 'a option
val peek : ('key, '_a) dict * 'key -> 'a option
val remove : ('_key, '_a) dict * '_key -> ('_key, '_a) dict * 'a
val numItems : ('key, '_a) dict -> int
val listItems : ('key, '_a) dict -> ('key, 'a) list
val app : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val revapp : ('key * 'a -> 'b) -> ('key, 'a) dict -> unit
val foldr : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val foldl : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val map : ('key * 'a -> '_b) -> ('_key, 'a) dict -> ('_key, '_b) dict
val transform : ('a -> '_b) -> ('_key, 'a) dict -> ('_key, '_b) dict
```

---

`[('key, 'a) dict]` is the type of applicative maps from domain type 'key to range type 'a, or equivalently, applicative dictionaries with keys of type 'key and values of type 'a. They are implemented as ordered *splay-trees* (Sleator and Tarjan).

`[mkDict ord]` returns a new, empty map whose keys have ordering `ord`.

`[insert(m, i, v)]` extends (or modifies) map `m` to map `i` to `v`.

`[find (m, k)]` returns `v` if `m` maps `k` to `v`; otherwise raises `NotFound`.

`[peek(m, k)]` returns `SOME v` if `m` maps `k` to `v`; otherwise returns `NONE`.

`[remove(m, k)]` removes `k` from the domain of `m` and returns the modified map and the element `v` corresponding to `k`. Raises `NotFound` if `k` is not in the domain of `m`.

`[numItems m]` returns the number of entries in `m` (that is, the size of the domain of `m`).

`[listItems m]` returns a list of the entries `(k, v)` of keys `k` and the corresponding values `v` in `m`, in increasing order of `k`.

`[app f m]` applies function `f` to the entries `(k, v)` in `m`, in increasing order of `k` (according to the ordering `ord` used to create the map or dictionary).

`[revapp f m]` applies function `f` to the entries `(k, v)` in `m`, in decreasing order of `k`.

`[foldl f e m]` applies the folding function `f` to the entries `(k, v)` in `m`, in increasing order of `k`.

`[foldr f e m]` applies the folding function `f` to the entries `(k, v)` in `m`, in decreasing order of `k`.

`[map f m]` returns a new map whose entries have form `(k, f(k,v))`, where `(k, v)` is an entry in `m`.

`[transform f m]` returns a new map whose entries have form `(k, f v)`, where `(k, v)` is an entry in `m`.

## Module Splayset

*Splayset* -- applicative sets implemented by splay-trees  
 From *SM/Lib 0.2*, copyright 1993 by AT&T Bell Laboratories

```

type 'item set
exception NotFound

val empty : ('item * 'item -> order) -> 'item set
val singleton : ('item * 'item -> order) -> 'item -> 'item set
val add : 'item set * 'item -> 'item set
val addlist : 'item set * 'item list -> 'item set
val retrieve : 'item set * 'item -> 'item
val peek : 'item set * 'item -> 'item option
val isEmpty : 'item set -> bool
val equal : 'item set * 'item set -> bool
val isSubset : 'item set * 'item set -> bool
val member : 'item set * 'item -> bool
val delete : 'item set * 'item -> 'item set
val numItems : 'item set -> int
val union : 'item set * 'item set -> 'item set
val intersection : 'item set * 'item set -> 'item set
val difference : 'item set * 'item set -> 'item set
val listItems : 'item set -> 'item list
val app : ('item -> unit) -> 'item set -> unit
val revapp : ('item -> unit) -> 'item set -> unit
val foldr : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val foldl : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val find : ('item -> bool) -> 'item set -> 'item option

```

`{'item set}` is the type of sets of ordered elements of type `'item`. The ordering relation on the elements is used in the representation of the set. The result of combining two sets with different underlying ordering relations is undefined. The implementation uses splay-trees (Sleator and Tarjan).

`{empty order}` creates a new empty set with the given ordering relation.

`{singleton order i}` creates the singleton set containing `i`, with the given ordering relation.

`{add(s, i)}` adds item `i` to set `s`.

`{addlist(s, xs)}` adds all items from the list `xs` to the set `s`.

`{retrieve(s, i)}` returns `i` if it is in `s`; raises `NotFound` otherwise.

`{peek(s, i)}` returns `SOME i` if `i` is in `s`; returns `NONE` otherwise.

`{isEmpty s}` returns true if and only if the set is empty.

`{equal(s1, s2)}` returns true if and only if the two sets have the same elements.

`{isSubset(s1, s2)}` returns true if and only if `s1` is a subset of `s2`.

`{member(s, i)}` returns true if and only if `i` is in `s`.

`{delete(s, i)}` removes item `i` from `s`. Raises `NotFound` if `i` is not in `s`.

`{numItems s}` returns the number of items in set `s`.

`{union(s1, s2)}` returns the union of `s1` and `s2`.

`{intersection(s1, s2)}` returns the intersection of `s1` and `s2`.

`{difference(s1, s2)}` returns the difference between `s1` and `s2` (that is, the set of elements in `s1` but not in `s2`).

`{listItems s}` returns a list of the items in set `s`, in increasing order.

`{app f s}` applies function `f` to the elements of `s`, in increasing order.

`{revapp f s}` applies function `f` to the elements of `s`, in decreasing order.

`{foldl f e s}` applies the folding function `f` to the entries of the set in increasing order.

`{foldr f e s}` applies the folding function `f` to the entries of the set in decreasing order.

`{find p s}` returns `SOME i`, where `i` is an item in `s` which satisfies `p`, if one exists; otherwise returns `NONE`.

## Module String

String -- SML Basis Library

```

local
 type char = Char.char
in
 type string = string
 val maxSize : int
 val size : string -> int
 val sub : string * int -> char
 val substring : string * int * int -> string
 val extract : string * int * int option -> string
 val concat : string list -> string
 val ^ : string * string -> string
 val str : char -> string
 val implode : char list -> string
 val explode : string -> char list
 val map : (char -> char) -> string -> string
 val translate : (char -> string) -> string -> string
 val tokens : (char -> bool) -> string -> string list
 val fields : (char -> bool) -> string -> string list
 val isPrefix : string -> string -> bool
 val compare : string * string -> order
 val collate : (char * char -> order) -> string * string -> order
 val fromString : string -> string option
 val toString : string -> string
 val fromCString : string -> string option
 val toCString : string -> string
 val < : string * string -> bool
 val <= : string * string -> bool
 val > : string * string -> bool
 val >= : string * string -> bool
end

```

[string] is the type of immutable strings of characters, with constant-time indexing.

[maxSize] is the maximal number of characters in a string.

[size s] is the number of characters in string s.

[sub(s, i)] is the i'th character of s, counting from zero. Raises Subscript if i < 0 or i > size s.

[substring(s, i, n)] is the string s[i..i+n-1]. Raises Subscript if i < 0 or i+n > size s. Equivalent to extract(s, i, SOME n).

[extract (s, i, NONE)] is the string s[i..size s-1]. Raises Subscript if i < 0 or i > size s.

[extract (s, i, SOME n)] is the string s[i..i+n-1]. Raises Subscript if i < 0 or i+n > size s.

[concat ss] is the concatenation of all the strings in ss. Raises Size if the sum of their sizes is greater than maxSize.

[s1 ^ s2] is the concatenation of strings s1 and s2.

[str c] is the string of size one which contains the character c.

[implode cs] is the string containing the characters in the list cs. Equivalent to concat (List.map str cs).

[explode s] is the list of characters in the string s.

[map f s] applies f to every character of s, from left to right,

and returns the string consisting of the resulting characters. Equivalent to CharVector.map f s and to implode (List.map f (explode s)).

[translate f s] applies f to every character of s, from left to right, and returns the concatenation of the resulting strings. Raises Size if the sum of their sizes is greater than maxSize. Equivalent to concat (List.map f (explode s)).

[tokens p s] returns the list of tokens in s, from left to right, where a token is a non-empty maximal substring of s not containing any delimiter, and a delimiter is a character satisfying p.

[fields p s] returns the list of fields in s, from left to right, where a field is a (possibly empty) maximal substring of s not containing any delimiter, and a delimiter is a character satisfying p.

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character "#", then

```
"abc|def" contains two tokens: "abc" and "def"
"abc|def" contains three fields: "abc" and "" and "def"
```

[isPrefix s1 s2] is true if s1 is a prefix of s2.

That is, if there exists a string t such that s1 ^ t = s2.

[fromString s] scans the string s as an ML source program string, converting escape sequences into the appropriate characters. Does not skip leading whitespace.

[toString s] returns a string corresponding to s, with non-printable characters replaced by ML escape sequences. Equivalent to String.translate Char.toString.

[fromCString s] scans the string s as a C source program string, converting escape sequences into the appropriate characters. Does not skip leading whitespace.

[toCString s] returns a string corresponding to s, with non-printable characters replaced by C escape sequences. Equivalent to String.translate Char.toCString.

[compare (s1, s2)] does lexicographic comparison, using the standard ordering Char.compare on the characters. Returns LESS, EQUAL, or GREATER, according as s1 is less than, equal to, or greater than s2.

[collate cmp (s1, s2)] performs lexicographic comparison, using the given ordering cmp on characters.

```
[<]
```

```
[<=]
```

```
[>]
```

[>=] compare strings lexicographically, using the representation ordering on characters.

## Module StringCvt

StringCvt -- *SML Basis Library*

datatype radix = BIN | OCT | DEC | HEX

datatype realfmt =  
 SCI of int option     *scientific, arg = # dec. digits, dflt=6*  
 | FIX of int option   *fixed-point, arg = # dec. digits, dflt=6*  
 | GEN of int option   *auto choice of the above,*  
                           *arg = # significant digits, dflt=12*

```
type cs
type ('a, 'b) reader = 'b -> ('a * 'b) option
val scanString : ((char, cs) reader -> ('a, cs) reader) -> string -> 'a option
val split1
val take1
val drop1
val skipWS
val padLeft
val padRight
```

This structure presents tools for scanning strings and values from functional character streams, and for simple formatting.

[('elm, 'src) reader] is the type of source readers for reading a sequence of 'elm values from a source of type 'src. For instance, a character source reader  
 getc : (char, cs) reader  
 is used for obtaining characters from a functional character source src of type cs, one at a time. It should hold that

```
getc src = SOME(c, src')
 = NONE
 if the next character in src
 is c, and src' is the rest of src;
 if src contains no characters
```

A character source scanner takes a character source reader getc as argument and uses it to scan a data value from the character source.

[scanString scan s] turns the string s into a character source and applies the scanner 'scan' to that source.

[split1 p getc src] returns (pref, suff) where pref is the longest prefix (left substring) of src all of whose characters satisfy p, and suff is the remainder of src. That is, the first character retrievable from suff, if any, is the leftmost character not satisfying p. Does not skip leading whitespace.

[take1 p getc src] returns the longest prefix (left substring) of src all of whose characters satisfy predicate p. That is, if the leftmost character does not satisfy p, the result is the empty string. Does not skip leading whitespace. It holds that  
 take1 p getc src = #1 (split1 p getc src)

[drop1 p getc src] drops the longest prefix (left substring) of src all of whose characters satisfy predicate p. If all characters do, it returns the empty source. It holds that  
 drop1 p getc src = #2 (split1 p getc src)

[skipWS getc src] drops any leading whitespace from src. Equivalent to drop1 Char.isSpace.

[padLeft c n s] returns the string s if size s >= n, otherwise pads s with (n - size s) copies of the character c on the left. In other words, right-justifies s in a field n characters wide.

[padRight c n s] returns the string s if size s >= n, otherwise pads s with (n - size s) copies of the character c on the right. In other words, left-justifies s in a field n characters wide.

## Module Substring

*Substring* -- *SML Basis Library*

type substring

```

val substring : string * int * int -> substring
val extract : string * int * int option -> substring
val all : string -> substring
val string : substring -> string
val base : substring -> (string * int * int)

val isEmpty : substring -> bool
val getc : substring -> (char * substring) option
val first : substring -> char option
val trim : int -> substring -> substring
val triml : int -> substring -> substring
val trimr : int -> substring -> substring
val sub : substring * int -> char
val size : substring -> int
val slice : substring * int * int option -> substring
val concat : substring list -> string
val explode : substring -> char list
val isPrefix : string -> substring -> bool
val compare : substring * substring -> order
val collate : (char * char -> order) -> substring * substring -> order

val drop1 : (char -> bool) -> substring -> substring
val drop : (char -> bool) -> substring -> substring
val takel : (char -> bool) -> substring -> substring
val take : (char -> bool) -> substring -> substring
val taker : (char -> bool) -> substring -> substring
val split1 : (char -> bool) -> substring -> substring * substring
val splitr : (char -> bool) -> substring -> substring * substring
val splitAt : substring * int -> substring * substring

val position : string -> substring -> substring * substring

exception Span
val span : substring * substring -> substring

val translate : (char -> string) -> substring -> string

val tokens : (char -> bool) -> substring -> substring list
val fields : (char -> bool) -> substring -> substring list

val foldl : (char * 'a -> 'a) -> 'a -> substring -> 'a
val foldr : (char * 'a -> 'a) -> 'a -> substring -> 'a
val app : (char -> unit) -> substring -> unit

[substring] is the type of substrings of a basestring, an efficient
representation of a piece of a string.
A substring (s,i,n) is valid if 0 <= i <= i+n <= size s,
or equivalently, 0 <= i and 0 <= n and i+n <= size s.
A valid substring (s, i, n) represents the string s[i..i+n-1].
Invariant in the implementation: Any value of type substring is valid.

[substring(s, i, n)] creates the substring (s, i, n), consisting of
the substring of s with length n starting at i. Raises Subscript
if i<0 or n<0 or i+n > size s. Equivalent to extract(s, i, SOME n).

[extract(s, i, NONE)] creates the substring (s, i, size s-i)
consisting of the tail of s starting at i.
Raises Subscript if i<0 or i > size s.

[extract(s, i, SOME n)] creates the substring (s, i, n),
consisting of the substring of s with length n starting at i.
Raises Subscript if i<0 or n<0 or i+n > size s.

[all s] is the substring (s, 0, size s).

[string sus] is the string s[i..i+n-1] represented by sus = (s, i, n).

```

```

[base sus] is the concrete triple (s, i, n), where sus = (s, i, n).
[isEmpty (s, i, n)] true if the substring is empty (that is, n = 0).
[getc sus] returns SOME(c, rst) where c is the first character and
rst the remainder of sus, if sus is non-empty; otherwise returns
NONE. Note that
#1 0 valOf o scanFn Substring.getc
is equivalent to, but more efficient than,
valOf o StringCvt.scanString scanFn o Substring.string
[first sus] returns SOME c where c is the first character in sus,
if sus is non-empty; otherwise returns NONE.
[triml k sus] returns sus less its leftmost k characters; or the
empty string at the end of sus if it has less than k characters.
Raises Subscript if k < 0, even in the partial application triml(k).
[trimr k sus] returns sus less its rightmost k characters; or the
empty string at the beginning of sus if it has less than k characters.
Raises Subscript if k < 0, even in the partial application trimr(k).
[sub (sus, k)] returns the k'th character of the substring; that is,
s(i+k) where sus = (s, i, n). Raises Subscript if k<0 or k>=n.
[size (s, i, n)] returns the size of the substring, that is, n.
[slice (sus, i', NONE)] returns the substring (s, i+i', n-i'), where
sus = (s, i, n). Raises Subscript if i' < 0 or i' > n.
[slice (sus, i', SOME n')] returns the substring (s, i+i', n'), where
sus = (s, i, n). Raises Subscript if i' < 0 or n' < 0 or i'+n' >= n.
[concat sus] returns a string consisting of the concatenation of
the substrings. Equivalent to String.concat (List.map string sus).
[explode sus] returns the list of characters of sus, that is,
[s(i), s(i+1), ..., s(i+n-1)]
where sus = (s, i, n). Equivalent to String.explode(string sus).
[isPrefix s1 s2] is true if s1 is a prefix of s2. That is, if there
exists a string t such that string s1 ^ t = string s2.
[compare (sus1, sus2)] performs lexicographic comparison, using the
standard ordering Char.compare on the characters. Returns LESS,
EQUAL, or GREATER, according as sus1 is less than, equal to, or
greater than sus2. Equivalent to, but more efficient than,
String.compare(string sus1, string sus2).
[collate cmp (sus1, sus2)] performs lexicographic comparison, using the
given ordering cmp on characters. Equivalent to, but more efficient
than, String.collate cmp (string sus1, string sus2).
[drop1 p sus] drops the longest prefix (left substring) of sus all
of whose characters satisfy predicate p. If all characters do, it
returns the empty substring (s, i+n, 0) where sus = (s, i, n).
[drop p sus] drops the longest suffix (right substring) of sus all
of whose characters satisfy predicate p. If all characters do, it
returns the empty substring (s, i, 0) where sus = (s, i, n).
[take1 p sus] returns the longest prefix (left substring) of sus
all of whose characters satisfy predicate p. That is, if the
left-most character does not satisfy p, returns the empty (s, i, 0)
where sus = (s, i, n).
[take p sus] returns the longest suffix (right substring) of sus
all of whose characters satisfy predicate p. That is, if the
right-most character satisfies p, returns the empty (s, i+n, 0)
where sus = (s, i, n).
Let p be a predicate and xxxxyyyyzzzz a string where all

```

characters in xxxx and zzzz satisfy p, and f a is character not satisfying p. Then

```

sus = xxxxfyyyyfzzzz sus = xxxzzzzz
drop1 p sus = fyyyyfzzzz
take1 p sus = xxxxfyyyyf
take1 p sus = xxxxx xxxzzzzz
 xxxzzzzz

```

It also holds that

```

concat[take1 p sus, drop1 p sus] = string sus
concat[drop1 p sus, take1 p sus] = string sus

```

[split1 p sus] splits sus into a pair (sus1, sus2) of substrings where sus1 is the longest prefix (left substring) all of whose characters satisfy p, and sus2 is the rest. That is, sus2 begins with the leftmost character not satisfying p. Disregarding sideeffects, we have:

```
split1 p sus = (take1 p sus, drop1 p sus).
```

[splitr p sus] splits sus into a pair (sus1, sus2) of substrings where sus2 is the longest suffix (right substring) all of whose characters satisfy p, and sus1 is the rest. That is, sus1 ends with the rightmost character not satisfying p. Disregarding sideeffects, we have:

```
splitr p sus = (drop1 p sus, take1 p sus)
```

[splitAt (sus, k)] returns the pair (sus1, sus2) of substrings, where sus1 contains the first k characters of sus, and sus2 contains the rest. Raises Subscript if  $k < 0$  or  $k > \text{size sus}$ .

[position s (s', i, n)] splits the substring into a pair (pref, suff) of substrings, where suff is the longest suffix of (s', i, n) which has s as a prefix. More precisely, let  $m = \text{size s}$ . If there is a least index  $k$  in  $i..i+n-m$  for which  $s = s'[k..k+m-1]$ , then the result is  $(\text{pref} = (s', i, k-i)$  and  $\text{suff} = (s', k, n-(k-i))$ ; otherwise the result is  $(\text{pref} = (s', i, n)$  and  $\text{suff} = (s', i+n, 0)$ .

[span (sus1, sus2)] returns a substring spanning from the start of sus1 to the end of sus2, provided this is well-defined: sus1 and sus2 must have the same underlying string, and the start of sus1 must not be to the right of the end of sus2; otherwise raises Span.

More precisely, if  $\text{base}(\text{sus1}) = (s, i, n)$  and  $\text{base}(\text{sus2}) = (s', i', n')$  and  $s = s'$  and  $i' < i+n'$ , then  $\text{base}(\text{join}(\text{sus1}, \text{sus2})) = (s, i, i+n'-i)$ . This may be used to compute 'span', 'union', and 'intersection'.

[translate f sus] applies f to every character of sus, from left to right, and returns the concatenation of the results. Raises Size if the sum of their sizes is greater than String.maxSize. Equivalent to String.concat(List.map f (explode sus)).

[tokens p sus] returns the list of tokens in sus, from left to right, where a token is a non-empty maximal substring of sus not containing any delimiter, and a delimiter is a character satisfying p.

[fields p sus] returns the list of fields in sus, from left to right, where a field is a (possibly empty) maximal substring of sus not containing any delimiter, and a delimiter is a character satisfying p.

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character "#", then

```

"abc||def" contains two tokens: "abc" and "def"
"abc||def" contains three fields: "abc" and "" and "def"

```

[foldl f e sus] folds f over sus from left to right. That is, evaluates  $f(s[i+n-1], f(\dots, f(s[i+1], f(s[i] \& e) \dots)))$  tail-recursively, where  $\text{sus} = (s, i, n)$ . Equivalent to List.foldl f e (explode sus).

[foldr f e sus] folds f over sus from right to left. That is, evaluates  $f(s[i], f(s[i+1], f(\dots, f(s[i+n-1] \& e) \dots)))$  tail-recursively, where  $\text{sus} = (s, i, n)$ . Equivalent to List.foldr f e (explode sus).

[app f sus] applies f to all characters of sus, from left to right. Equivalent to List.app f (explode sus).



## Module Susp

*Susp* -- support for lazy evaluation

```
type 'a susp
val delay : (unit -> 'a) -> 'a susp
val force : 'a susp -> 'a
```

---

[*'a susp*] is the type of lazily evaluated expressions with result type *'a*.

[*delay* (fn () => e)] creates a suspension for the expression *e*. The first time the suspension is forced, the expression *e* will be evaluated, and the result stored in the suspension. All subsequent forcing of the suspension will just return this result, so *e* is evaluated at most once. If the suspension is never forced, then *e* is never evaluated.

[*force su*] forces the suspension *su* and returns the result of the expression *e* stored in the suspension.

## Module TextIO

*TextIO* -- SML Basis Library

```
type elem = Char.char
type vector = string

Text input
type instream
 val openIn : string -> instream
 val closeIn : instream -> unit
 val input : instream -> vector
 val inputAll : instream -> vector
 val inputNoBlock : instream -> vector option
 val input1 : instream -> elem option
 val inputN : instream * int -> vector
 val inputLine : instream -> string
 val endOfStream : instream -> bool
 val lookahead : instream -> elem option

type cs character source state
val scanStream : ((char, cs) StringCvt.reader -> ('a, cs) StringCvt.reader)
 -> instream -> 'a option

val stdin : instream

Text output
type ostream
 val openOut : string -> ostream
 val openAppend : string -> ostream
 val closeOut : ostream -> unit
 val output : ostream * vector -> unit
 val output1 : ostream * elem -> unit
 val outputSubstr : ostream * substring -> unit
 val flushOut : ostream -> unit

 val stdout : ostream
 val stderr : ostream

 val print : string -> unit
```

---

This structure provides input/output functions on text streams. The functions are state-based: reading from or writing to a stream changes the state of the stream. The streams are buffered: output to a stream may not immediately affect the underlying file or device.

Note that under DOS, Windows, OS/2, and MacOS, text streams will be 'translated' by converting (e.g.) the double newline CRLF to a single newline character \n.

[*instream*] is the type of state-based characters input streams.

[*ostream*] is the type of state-based character output streams.

[*elem*] is the type char of characters.

[*vector*] is the type of character vectors, that is, strings.

TEXT INPUT:

[*openIn s*] creates a new instream associated with the file named *s*. Raises *Io.Io* if file *s* does not exist or is not accessible.

[*closeIn istr*] closes stream *istr*. Has no effect if *istr* is closed

already. Further operations on istr will behave as if istr is at end of stream (that is, will return "" or NONE or true).

[input istr] reads some elements from istr, returning a vector v of those elements. The vector will be empty (size v = 0) if and only if istr is at end of stream or is closed. May block (not return until data are available in the external world).

[inputAll istr] reads and returns the string v of all characters remaining in istr up to end of stream.

[inputNoBlock istr] returns SOME(v) if some elements v can be read without blocking; returns NONE("") if it can be determined without blocking that istr is at end of stream; returns NONE otherwise. If istr does not support non-blocking input, raises Io.NonblockingNotSupported.

[input1 istr] returns SOME(e) if at least one element e of istr is available; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds.

[inputN(istr, n)] returns the next n characters from istr as a string, if that many are available; returns all remaining characters if end of stream is reached before n characters are available; blocks if necessary until one of these conditions holds. (This is the behaviour of the 'input' function prescribed in the 1990 Definition of Standard ML).

[inputLine istr] returns one line of text, including the terminating newline character. If end of stream is reached before a newline character, then the remaining part of the stream is returned, with a newline character added. If istr is at end of stream or is closed, then the empty string "" is returned.

[eofStream istr] returns false if any elements are available in istr; returns true if istr is at end of stream or closed; blocks if necessary until one of these conditions holds.

[lookahead istr] returns SOME(e) where e is the next element in the stream; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds. Does not advance the stream.

[stdIn] is the buffered state-based standard input stream.

[scanStream scan istr] turns the instream istr into a character source and applies the scanner 'scan' to that source. See StringCvt for more on character sources and scanners. The Moscow ML implementation currently can backtrack only 512 characters, and raises Fail if the scanner backtracks further than that.

TEXT OUTPUT:

[openOut s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, it is truncated (any existing contents are lost).

[openAppend s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, any existing contents are retained, and output goes at the end of the file.

[closeOut ostr] closes stream ostr; further operations on ostr (except for additional close operations) will raise exception Io.Io.

[output(ostr, v)] writes the string v on outstream ostr.

[output1(ostr, e)] writes the character e on outstream ostr.

[flushOut ostr] flushes the outstream ostr, so that all data written to ostr becomes available to the underlying file or device.

[stdOut] is the buffered state-based standard output stream.

[stdErr] is the unbuffered state-based standard error stream. That is, it is always kept flushed, so flushOut(stdErr) is redundant.

[print s] outputs s to stdOut and flushes immediately.

The functions below are not yet implemented:

[setPosIn(istr, i)] sets istr to the (untranslated) position i. Raises Io.Io if not supported on istr.

[getPosIn istr] returns the (untranslated) current position of istr. Raises Io.Io if not supported on istr.

[endPosIn istr] returns the (untranslated) last position of istr. Because of translation, one cannot expect to read endPosIn istr - getPosIn istr from the current position.

[getPosOut ostr] returns the current position in stream ostr. Raises Io.Io if not supported on ostr.

[endPosOut ostr] returns the ending position in stream ostr. Raises Io.Io if not supported on ostr.

[setPosOut(ostr, i)] sets the current position in stream to ostr to i. Raises Io.Io if not supported on ostr.

[mkInstream sistr] creates a state-based instream from the functional instream sistr.

[getInstream istr] returns the functional instream underlying the state-based instream istr.

[setInstream(istr, sistr)] redirects istr, so that subsequent input is taken from the functional instream sistr.

[mkOutstream sostr] creates a state-based outstream from the outstream sostr.

[getOutstream ostr] returns the outstream underlying the state-based outstream ostr.

[setOutstream(ostr, sostr)] redirects the outstream ostr so that subsequent output goes to sostr.

## Module Time

Time -- SML Basis Library

```

datatype time
exception Time
val zeroTime : time
val now : unit -> time
val toSeconds : time -> int
val toMilliseconds : time -> int
val toMicroseconds : time -> int
val fromSeconds : int -> time
val fromMilliseconds : int -> time
val fromMicroseconds : int -> time
val fromReal : real -> time
val toReal : time -> real
val toString : int -> string rounded to millisecond precision
val fmt : string -> time -> string
val fromString : string -> time option
val scan : (char, 'a) StringCvt.reader -> (time, 'a) StringCvt.reader
val + : time * time -> time
val - : time * time -> time
val < : time * time -> bool
val <= : time * time -> bool
val > : time * time -> bool
val >= : time * time -> bool
val compare : time * time -> order

```

[time] is a type for representing durations as well as absolute points in time (which can be thought of as durations since some fixed time zero).

[zeroTime] represents the 0-second duration, and the origin of time, so zeroTime + t = t + zeroTime = t for all t.

[now ()] returns the point in time at which the application occurs.

[fromSeconds s] returns the time value corresponding to s seconds. Raises Time if s < 0.

[fromMilliseconds ms] returns the time value corresponding to ms milliseconds. Raises Time if ms < 0.

[fromMicroseconds us] returns the time value corresponding to us microseconds. Raises Time if us < 0.

[toSeconds t] returns the number of seconds represented by t, truncated. Raises Overflow if that number is not representable as an int.

[toMilliseconds t] returns the number of milliseconds represented by t, truncated. Raises Overflow if that number is not representable as an int.

[toMicroseconds t] returns the number of microseconds represented by t, truncated. Raises Overflow if t that number is not representable as an int.

[fromReal r] converts a real to a time value representing that many seconds. Raises Time if r < 0 or if r is not representable as a time value. It holds that realToTime 0.0 = zeroTime.

[toReal t] converts a time the number of seconds it represents;

hence realToTime and timeToReal are inverses of each other when defined. Raises Overflow if t is not representable as a real.

[fmt n t] returns as a string the number of seconds represented by t, rounded to n decimal digits. If n <= 0, then no decimal digits are reported.

[toString t] returns as a string the number of seconds represented by t, rounded to 3 decimal digits. Equivalent to (fmt 3 t).

[fromString s] returns SOME t where t is the time value represented by the string s of form [\\n\\t ]\*( [0-9]+(\\. [0-9]+)? )|(\\. [0-9]+); or returns NONE if s cannot be parsed as a time value.

[scan getc src], where getc is a character accessor, returns SOME (t, rest) where t is a time and rest is rest of the input, or NONE if s cannot be parsed as a time value.

[+] adds two time values. For reals r1, r2 >= 0.0, it holds that realToTime r1 + realToTime r2 = realToTime (Real.(+r1,r2)). Raises Overflow if the result is not representable as a time value.

[-] subtracts a time value from another. That is, t1 - t2 is the duration from t2 to t1. Raises Time if t1 < t2 or if the result is not representable as a time value. It holds that t - zeroTime = t.

[<]

[<=]

[>]

[>=] compares time values. For instance, for reals r1, r2 >= 0.0 it holds that realToTime r1 < realToTime r2 iff Real.<(r1, r2)

[compare(t1, t2)] returns LESS, EQUAL, or GREATER, according as t1 precedes, equals, or follows t2 in time.

## Module Timer

*Timer -- SML Basis Library*

```
type cpu_timer
type real_timer

val startCPUtimer : unit -> cpu_timer
val totalCPUtimer : unit -> cpu_timer
val checkCPUtimer : cpu_timer ->
 { usr : Time.time, sys : Time.time, gc : Time.time }

val startRealTimer : unit -> real_timer
val totalRealTimer : unit -> real_timer
val checkRealTimer : real_timer -> Time.time
```

[cpu\_timer] is the type of timers for measuring CPU time consumption (user time, garbage collection time, and system time).

[real\_timer] is the type of timers for measuring the passing of real time (wall-clock time).

[startCPUtimer ()] returns a cpu\_timer started at the moment of the call.

[totalCPUtimer ()] returns a cpu\_timer started at the moment the library was loaded.

[checkCPUtimer tmr] returns {usr, sys, gc} where usr is the amount of user CPU time consumed since tmr was started, gc is the amount of user CPU time spent on garbage collection, and sys is the amount of system CPU time consumed since tmr was started. Note that gc time is included in the usr time. Under MS DOS, usr time and gc time are measured in real time.

[startRealTimer ()] returns a real\_timer started at the moment of the call.

[totalRealTimer ()] returns a real\_timer started at the moment the library was loaded.

[checkRealTimer tmr] returns the amount of real time that has passed since tmr was started.

## Module Unix

*Unix -- SML Basis Library*

```
type proc
type signal = Signal.signal

val executeInEnv : string * string list * string list -> proc
val execute : string * string list -> proc
val streamsOf : proc -> TextIO.instream * TextIO.outstream
val kill : proc * signal -> unit
val reap : Proc -> Process.status
```

This structure allows Moscow ML programs to start other processes and to communicate with them.

Child processes are not automatically terminated when the parent (ML) process terminates. To forcibly terminate a child process pr, use Unix.kill(pr, Signal.term). Then, to remove the terminated process from the operating system tables, call Unix.reap(pr).

The protocol for communication between the ML program and its child process must be designed with some care, typically using non-blocking input for reading from the child process.

[proc] is the type of processes started by the ML program.

[signal] is the type of Unix-style signals, which can be sent to another process. Signal values must be obtained from the Signal structure.

[execute (cmd, args)] asks the operating system to execute the command cmd with the argument list args, as a separate process. Two pipes connected to the standard input and standard output of the new process are created; these may be obtained using streamsOf. A proc value representing the new process is returned. The new process executes using the same environment as the calling process. Raises Fail in case of failure, e.g. if the process or the pipes cannot be created.

Typically, the cmd argument will be the full pathname of an executable. On Unix systems, simple command searching as done by the shell, allowing cmd to be a relative pathname, can be achieved by using

```
execute("/bin/sh", "-c" :: concat (cmd :: " " :: args))
```

[executeInEnv (cmd, args, env)] asks the operating system to execute the command cmd with the argument list args in the environment env, as a separate process. Returns a proc value representing the new process. Typically, a string in the env list has the form "NAME=VALUE". See also Process.getEnv.

[streamsOf pr] returns a pair (ins, outs) of input and output streams associated with process pr. The standard output of pr is the source for the input stream ins, and the standard input of pr is the sink for the output stream outs.

[reap pr] closes the input and output streams associated with pr, and then suspends the current (ML) process until the process corresponding to pr terminates. Returns the exit status given by pr when it terminated. Raises Fail in case of failure, e.g. if pr has already been reaped.

Under Unix, information about a terminated process remains in the system tables until the process is reaped. Thus, an ML program using execute or executeInEnv must make sure to reap any process it has created, or else the system tables will fill up.

[kill (pr, s)] sends the signal s to the process pr. Raises Fail in case of failure, e.g. if pr has already been killed.

## Module Vector

```
Vector -- SML Basis Library
```

```
type 'a vector = 'a vector
val maxLen : int

val fromList : 'a list -> 'a vector
val tabulate : int * (int -> 'a) -> 'a vector

val length : 'a vector -> int
val sub : 'a vector * int -> 'a
val extract : 'a vector * int * int option -> 'a vector
val concat : 'a vector list -> 'a vector

val app : ('a -> unit) -> 'a vector -> unit
val map : ('a -> 'b) -> 'a vector -> 'b vector
val foldl : ('a * 'b -> 'b) -> 'b -> 'a vector -> 'b
val foldr : ('a * 'b -> 'b) -> 'b -> 'a vector -> 'b

val appi : (int * 'a -> unit) -> 'a vector * int * int option -> unit
val mapi : (int * 'a -> 'b) -> 'a vector * int * int option -> 'b vector
val foldli : (int * 'a * 'b -> 'b) -> 'b -> 'a vector * int * int option -> 'b
val foldri : (int * 'a * 'b -> 'b) -> 'b -> 'a vector * int * int option -> 'b
```

`'ty vector` is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type `'ty`.  
Type `'ty vector` admits equality if `'ty` does. Vectors `v1` and `v2` are equal if they have the same length and their elements are equal.

`[maxLen]` is the maximal number of elements in a vector.

`[fromList xs]` returns a vector whose elements are those of `xs`.  
Raises `Size` if `length xs > maxLen`.

`[tabulate(n, f)]` returns a vector of length `n` whose elements are `f 0, f 1, ..., f (n-1)`, created from left to right. Raises `Size` if `n < 0` or `n > maxLen`.

`[length v]` returns the number of elements in `v`.

`[sub(v, i)]` returns the `i`'th element of `v`, counting from 0.  
Raises `Subscript` if `i < 0` or `i > length v`.

`[extract(v, i, NONE)]` returns a vector of the elements `v[i..length v-1]` of `v`. Raises `Subscript` if `i < 0` or `i > length v`.

`[extract(v, i, SOME n)]` returns a vector of the elements `v[i..i+n-1]` of `v`. Raises `Subscript` if `i < 0` or `i+n > length v`.

`[concat vs]` returns a vector which is the concatenation from left to right of the vectors in `vs`. Raises `Size` if the sum of the sizes of the vectors in `vs` is larger than `maxLen`.

`[foldl f e v]` folds function `f` over `v` from left to right. That is, computes `f(v[0], f(v[1], ..., f(v[len-2], f(v[0], e) ...))`, where `len` is the length of `v`.

`[foldr f e v]` folds function `f` over `v` from right to left. That is, computes `f(v[0], f(v[1], ..., f(v[len-2], f(v[len-1], e) ...))`, where `len` is the length of `v`.

`[app f v]` applies `f` to `v[j]` for `j=0,1,...,length v-1`.

`[map f v]` applies `f` to `v[j]` for `j=0,1,...,length v-1` and returns a new vector containing the results.

The following iterators generalize the above ones in two ways:

\* the index `j` is also being passed to the function being iterated;

\* the iterators work on a slice (subvector) of a vector.

The slice `(v, i, SOME n)` denotes the subvector `v[i..i+n-1]`. That is, `v[i]` is the first element of the slice, and `n` is the length of the slice. Valid only if `0 <= i <= i+n <= length v`.

The slice `(v, i, NONE)` denotes the subvector `v[i..length v-1]`. That is, the slice denotes the suffix of the vector starting at `i`. Valid only if `0 <= i <= length v`. Equivalent to `(v, i, SOME(length v - i))`.

| slice                       | meaning                                                  |
|-----------------------------|----------------------------------------------------------|
| <code>(v, 0, NONE)</code>   | the whole vector                                         |
| <code>(v, 0, SOME n)</code> | a left subvector (prefix) <code>v[0..n-1]</code>         |
| <code>(v, i, NONE)</code>   | a right subvector (suffix) <code>v[i..length v-1]</code> |
| <code>(v, i, SOME n)</code> | a general slice <code>v[i..i+n-1]</code>                 |

`[foldli f e (v, i, SOME n)]` folds function `f` over the subvector `v[i..i+n-1]` from left to right. That is, computes `f(i+n-1, v[i+n-1], f(..., f(i+1, v[i+1]), f(i, v[i]), e) ...))`. Raises `Subscript` if `i < 0` or `i+n > length v`.

`[foldri f e (v, i, NONE)]` folds function `f` over the subvector `v[i..length v-1]` from left to right, where `len = length v`. That is, computes `f(len-1, v[len-1], f(..., f(i+1, v[i+1]), f(i, v[i], e) ...))`. Raises `Subscript` if `i < 0` or `i > length v`.

`[foldri f e (v, i, SOME n)]` folds function `f` over the subvector `v[i..i+n-1]` from right to left. That is, computes `f(i, v[i], f(i+1, v[i+1], ...), f(i+n-1, v[i+n-1], e) ...))`. Raises `Subscript` if `i < 0` or `i+n > length v`.

`[foldri f e (v, i, NONE)]` folds function `f` over the subvector `v[i..length v-1]` from right to left, where `len = length v`. That is, computes `f(i, v[i], f(i+1, v[i+1], ...), f(len-1, v[len-1], e) ...))`. Raises `Subscript` if `i < 0` or `i > length v`.

`[appi f (v, i, SOME n)]` applies `f` to successive pairs `(j, v[j])` for `j=i, i+1, ..., i+n-1`. Raises `Subscript` if `i < 0` or `i+n > length v`.

`[appi f (v, i, NONE)]` applies `f` to successive pairs `(j, v[j])` for `j=i, i+1, ..., length v-1`, where `len = length v`. Raises `Subscript` if `i < 0` or `i > length v`.

`[mapi f (v, i, SOME n)]` applies `f` to successive pairs `(j, v[j])` for `j=i, i+1, ..., i+n-1` and returns a new vector (of length `n`) containing the results. Raises `Subscript` if `i < 0` or `i+n > length v`.

`[mapi f (v, i, NONE)]` applies `f` to successive pairs `(j, v[j])` for `j=i, i+1, ..., length v-1`, where `len = length v`, and returns a new vector (of length `length v - i`) containing the results. Raises `Subscript` if `i < 0` or `i > length v`.

## Module Weak

Weak --- weak pointers and arrays of weak pointers

Single weak pointers

```
type 'a weak
val weak : 'a -> 'a weak
val set : 'a weak * 'a -> unit
val get : 'a weak -> 'a
val isweak : 'a weak -> bool
```

Arrays of weak pointers

```
prim_EQtype 'a array
val maxlen : int
val array : int -> 'a array
val sub : 'a array * int -> 'a
val update : 'a array * int * 'a -> unit
val isdead : 'a array * int -> bool
val length : 'a array -> int
val app : ('a -> unit) -> 'a array -> unit
val foldl : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldr : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val modify : ('a -> 'a) -> 'a array -> unit
val appi : (int * 'a -> unit) -> 'a array * int * int option -> unit
val foldli : (int * 'a * 'b -> 'b) -> 'b -> 'a array * int * int option
-> 'b
val foldri : (int * 'a * 'b -> 'b) -> 'b -> 'a array * int * int option
-> 'b
val modifyi : (int * 'a -> 'a) -> 'a array * int * int option -> unit
```

[*'a weak*] is the type of weak pointers to objects of type *'a*. A weak pointer is a pointer that cannot itself keep an object alive. Hence the object pointed to by a weak pointer may be deallocated by the garbage collector if the object is reachable only by weak pointers. In this case, subsequent accesses via the *get* function will raise Fail "dangling weak pointer". (We raise an exception instead of returning an option value, because access via a weak pointer to a deallocated object is likely to be a programming error).

Integers, characters, words and booleans will not be deallocated by the garbage collector and will remain reachable forever by a weak pointer. Reals, strings, tuples and other non-nullary constructors may be deallocated by the garbage collector. Constants, even composite ones, will not be deallocated either.

[*weak v*] creates and returns a weak pointer to value *v*.

[*get w*] returns the value pointed to by weak pointer *w*, if the value is still alive. Otherwise raises Fail "dangling weak pointer".

[*set(w, v)*] makes the weak pointer *w* point to the value *v*.

[*isweak w*] returns true if the value pointed to by *w* is dead; returns false otherwise. If an object is reported to be dead, it remains dead. However, an object is reported to be live just if it has not yet been deallocated by the garbage collector. The allocation of any new value may activate the garbage collector and cause the object to die. Thus if not (*isweak w*) then get *w* else "blah" will not raise exception Fail, whereas the following might: if not (*isweak w*) then ([1,2] @ [3,4]); get *w* else "blah" because evaluation of the list append may cause *w* to die.

The value of *isweak w* is the same as that of

(get *w* false) handle Fail \_ => true but evaluating the latter expression may have the side effect of keeping *w* alive for slightly longer, because a pointer to *w* is returned by get *w*.

---

[*'a array*] is the type of arrays of weak pointers to objects of type *'a*.

A value of type *'a Weak.weak* (above) is equivalent to, but more efficient than, a one-element *'a Weak.array*. On the other hand, an *'a Weak.array* is more efficient than an (*'a Weak.weak*) *Array.array*.

[*array n*] creates an array of *n* weak pointers. Initially, any access to the array will raise Fail.

[*sub(a, i)*] returns the object pointed to by cell *i* (counting from 0) of the array *a*, if it is live. Raises Fail "dangling weak pointer" if cell *i* has never been updated or if the object pointed to has been deallocated by the garbage collector. Raises Subscript if *i* < 0 or *i* > length *a*. To make 'sub' infix, use the declaration `infix 9 sub`

[*update(a, i, v)*] updates cell *i* of array *a* to point (weakly) to the value *v*. Raises Subscript if *i* < 0 or *i* > length *a*.

[*isdead(a, i)*] returns true if the object in cell *i* of array *a* is dead, and false otherwise. Analogous to *isweak*; see above.

[*length a*] returns the number of elements in *a*.

[*maxLen*] is the maximal number of elements in an array.

The iterators described below operate on the live elements only. Note that an element *a[k]* may die in the course of folding *f* over earlier elements (e.g. *a[1] ... a[k-1]*). Thus the functions should be used with great care.

[*foldl f e a*] folds function *f* over the live elements of *a*, from left to right.

[*foldr f e a*] folds function *f* over the live elements of *a*, from right to left.

[*app f a*] applies *f* to the live elements of *a* from left to right.

[*modify f a*] applies *f* to *a[j]* and updates *a[j]* with the result *f(a[j])*, for each live element *a[j]*, from left to right.

The following iterators generalize the above ones in two ways:

- . the index *j* is also being passed to the function being iterated;
- . the iterators work on a slice (subarray) of an array.

The slice (*a, i, SOME n*) denotes the subarray *a[i..i+n-1]*. That is, *a[i]* is the first element of the slice, and *n* is the length of the slice. Valid only if  $0 \leq i \leq i+n \leq \text{length } a$ .

The slice (*a, i, NONE*) denotes the subarray *a[i..length a-1]*. That is, the slice denotes the suffix of the array starting at *i*. Valid only if  $0 \leq i \leq \text{length } a$ . Equivalent to (*a, i, SOME(length a - i)*).

| slice                   | meaning                                      |
|-------------------------|----------------------------------------------|
| ( <i>a, 0, NONE</i> )   | the whole array <i>a[0..len-1]</i>           |
| ( <i>a, 0, SOME n</i> ) | a left subarray (prefix) <i>a[0..n-1]</i>    |
| ( <i>a, i, NONE</i> )   | a right subarray (suffix) <i>a[i..len-1]</i> |
| ( <i>a, i, SOME n</i> ) | a general slice <i>a[i..i+n-1]</i>           |

[*foldl f e (a, i, SOME n)*] folds function *f* over the live elements of the subarray *a[i..i+n-1]* from left to right. Raises Subscript

```

if i<0 or n<0 or i+n > length a.
[foldl f e (a, i, NONE)] folds function f over the live elements
of the subarray a[i..i+n-1] from left to right, where len = length
a. Raises Subscript if i<0 or i > length a.
[foldr f e (a, i, SOME n)] folds function f over the live elements
of the subarray a[i..i+n-1] from right to left. Raises Subscript
if i<0 or n<0 or i+n > length a.
[foldri f e (a, i, NONE)] folds function f over the live elements
of the subarray a[i..i+n-1] from right to left, where len = length
a. Raises Subscript if i<0 or i > length a.
[appi f (a, i, SOME n)] applies f to successive pairs (j, a[j]) for
j=i,i+1,...,i+n-1, provided a[j] is live. Raises Subscript if i<0
or n<0 or i+n > length a.
[appi f (a, i, NONE)] applies f to successive pairs (j, a[j]) for
j=i,i+1,...,i+n-1, where len = length a, provided a[j] is live.
Raises Subscript if i<0 or i > length a.
[modifi f (a, i, SOME n)] applies f to (j, a[j]) and updates a[j]
with the result f(j, a[j]) for j=i,i+1,...,i+n-1, provided a[j] is
live. Raises Subscript if i<0 or n<0 or i+n > length a.
[modifi f (a, i, NONE)] applies f to (j, a[j]) and updates a[j]
with the result f(j, a[j]) for j=i,i+1,...,i+n-1, provided a[j] is
live. Raises Subscript if i<0 or i > length a.

```

## Module Word

```

Word -- SML Basis Library
type word = word
val wordSize : int
val orb : word * word -> word
val andb : word * word -> word
val xorb : word * word -> word
val notb : word -> word
val << : word * word -> word
val >> : word * word -> word
val ~>> : word * word -> word
val + : word * word -> word
val - : word * word -> word
val * : word * word -> word
val div : word * word -> word
val mod : word * word -> word
val > : word * word -> bool
val < : word * word -> bool
val >= : word * word -> bool
val <= : word * word -> bool
val compare : word * word -> order
val min : word * word -> word
val max : word * word -> word
val toString : word -> string
val fromString : string -> word option
val scan : StringCvt.radix
-> (char, 'a) StringCvt.reader -> (word, 'a) StringCvt.reader
val fmt : StringCvt.radix -> word -> string
val toInt : word -> int
val toIntX : word -> int
val fromInt : int -> word
val toLargeWord : word -> word
val toLargeWordX : word -> word
val fromLargeWord : word -> word
val toLargeInt : word -> int
val toLargeIntX : word -> int
val fromLargeInt : int -> word

```

---

```

[word] is the type of n-bit words, or n-bit unsigned integers.
[wordSize] is the value of n above. In Moscow ML, n=31 on 32-bit
machines and n=63 on 64-bit machines.
[orb(w1, w2)] returns the bitwise 'or' of w1 and w2.
[andb(w1, w2)] returns the bitwise 'and' of w1 and w2.
[xorb(w1, w2)] returns the bitwise 'exclusive or' or w1 and w2.
[notb w] returns the bitwise negation of w.
[<<(w, k)] returns the word resulting from shifting w left by k
bits. The bits shifted in are zero, so this is a logical shift.
Consequently, the result is 0-bits when k >= wordSize.
[>>(w, k)] returns the word resulting from shifting w right by k
bits. The bits shifted in are zero, so this is a logical shift.
Consequently, the result is 0-bits when k >= wordSize.

```

[>>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are replications of the left-most bit: the 'sign bit', so this is an arithmetical shift. Consequently, for k >= wordSize and wordToInt w >= 0 the result is all 0-bits, and for k >= wordSize and wordToInt w < 0 the result is all 1-bits.

To make <<, >>, and ~>> infix, use the declaration  
infix 5 << >> ~>>

```
[+]
[-]
[*]
[div]
```

[mod] represent unsigned integer addition, subtraction, multiplication, division, and remainder, modulus 2 raised to the n'th power, where n=wordSize. The operations (i div j) and (i mod j) raise Div when j=0. Otherwise no exceptions are raised.

```
[<]
[<=]
[>]
[>=]
```

[>=] compare words as unsigned integers.

[compare(w1, w2)] returns LESS, EQUAL, or GREATER, according as w1 is less than, equal to, or greater than w2 (as unsigned integers).

[min(w1, w2)] returns the smaller of w1 and w2 (as unsigned integers).

[max(w1, w2)] returns the larger of w1 and w2 (as unsigned integers).

[fmt radix w] returns a string representing w, in the radix (base) specified by radix.

| radix | description          | output format       |
|-------|----------------------|---------------------|
| BIN   | unsigned binary      | (base 2) [01]+      |
| OCT   | unsigned octal       | (base 8) [0-7]+     |
| DEC   | unsigned decimal     | (base 10) [0-9]+    |
| HEX   | unsigned hexadecimal | (base 16) [0-9A-F]+ |

[toString w] returns a string representing w in unsigned hexadecimal format. Equivalent to (fmt HEX w).

[fromString s] returns SOME(w) if a hexadecimal unsigned numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. Raises Overflow if the scanned number cannot be represented as a word. An unsigned hexadecimal numeral must have form, after possible initial whitespace:  
[0-9a-fA-F]+

[scan radix getch charsrc] attempts to scan an unsigned numeral from the character source charsrc, using the accessor getch, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns SOME(w, rest) where w is the value of the numeral scanned, and rest is the unused part of the character source. Raises Overflow if the scanned number cannot be represented as a word. A numeral must have form, after possible initial whitespace:

| radix | input format                    |
|-------|---------------------------------|
| BIN   | (0w)?[0-1]+                     |
| OCT   | (0w)?[0-7]+                     |
| DEC   | (0w)?[0-9]+                     |
| HEX   | (0w [0wX] 0x [0X])?[0-9a-fA-F]+ |

[toInt w] returns the (signed) integer represented by bit-pattern w.  
[toIntX w] returns the (signed) integer represented by bit-pattern w.  
[fromInt i] returns the word representing integer i.

[toLargeInt w] returns the (signed) integer represented by bit-pattern w.  
[toLargeIntX w] returns the (signed) integer represented by bit-pattern w.

[fromLargeInt i] returns the word representing integer i.

```
[toLargeWord w] returns w.
[toLargeWordX w] returns w.
[fromLargeWord w] returns w.
```



## Module Word8

Word8 -- *SML Basis Library*

```

type word = word8

val wordSize : int
val orb : word * word -> word
val andb : word * word -> word
val xorb : word * word -> word
val notb : word -> word
val << : word * Word.word -> word
val >> : word * Word.word -> word
val ~>> : word * Word.word -> word
val + : word * word -> word
val - : word * word -> word
val * : word * word -> word
val div : word * word -> word
val mod : word * word -> word
val < : word * word -> bool
val > : word * word -> bool
val >= : word * word -> bool
val <= : word * word -> bool
val compare : word * word -> order
val min : word * word -> word
val max : word * word -> word
val toString : word -> string
val fromString : string -> word option
val scan : StringCvt.radix
-> (char, 'a) StringCvt.reader -> (word, 'a) StringCvt.reader
val fmt : StringCvt.radix -> word -> string
val toInt : word -> int
val toIntX : word -> int
val fromInt : int -> word
val toLargeInt : word -> int
val toLargeIntX : word -> int
val fromLargeInt : int -> word
val toLargeWord : word -> Word.word
val fromLargeWord : Word.word -> word

```

[word] is the type of 8-bit words, or 8-bit unsigned integers in the range 0..255.

[wordSize] equals 8.

[orb(w1, w2)] returns the bitwise 'or' of w1 and w2.

[andb(w1, w2)] returns the bitwise 'and' of w1 and w2.

[xorb(w1, w2)] returns the bitwise 'exclusive or' of w1 and w2.

[notb w] returns the bitwise negation of w.

[<<(w, k)] returns the word resulting from shifting w left by k bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.

[>>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.

[->>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are replications of the left-most bit: the 'sign bit', so this is an arithmetical shift. Consequently, for k >= wordSize and wordToInt w >= 0 the result is all 0-bits, and for k >= wordSize and wordToInt w < 0 the result is all 1-bits.

To make <<, >>, and ~>> infix, use the declaration:  
infix 5 << >> ~>>

```

[+]
[-]
[*]
[div]
[mod] represent unsigned integer addition, subtraction,
multiplication, division, and remainder, modulus 256. The
operations (i div j) and (i mod j) raise Div when j = 0. Otherwise
no exceptions are raised.
[<]
[<=]
[>]
[>=] compare words as unsigned integers.
[compare(w1, w2)] returns LESS, EQUAL, or GREATER, according
as w1 is less than, equal to, or greater than w2 (as unsigned integers).
[min(w1, w2)] returns the smaller of w1 and w2 (as unsigned integers).
[max(w1, w2)] returns the larger of w1 and w2 (as unsigned integers).
[fmt radix w] returns a string representing w, in the radix (base)
specified by radix.

```

| radix | description          | output format       |
|-------|----------------------|---------------------|
| BIN   | unsigned binary      | (base 2) [01]+      |
| OCT   | unsigned octal       | (base 8) [0-7]+     |
| DEC   | unsigned decimal     | (base 10) [0-9]+    |
| HEX   | unsigned hexadecimal | (base 16) [0-9A-F]+ |

[toString w] returns a string representing w in unsigned hexadecimal format. Equivalent to (fmt HEX w).

[fromString s] returns SOME(w) if a hexadecimal unsigned numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. Raises Overflow if the scanned number cannot be represented as a word. An unsigned hexadecimal numeral must have form, after possible initial whitespace:  
[0-9a-fA-F]+

[scan radix {getc} charsrc] attempts to scan an unsigned numeral from the character source charsrc, using the accessor getc, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns SOME(w, rest) where w is the value of the numeral scanned, and rest is the unused part of the character source. Raises Overflow if the scanned number cannot be represented as a word. A numeral must have form, after possible initial whitespace:

| radix | input format             |
|-------|--------------------------|
| BIN   | (0w)?[0-1]+              |
| OCT   | (0w)?[0-7]+              |
| DEC   | (0w)?[0-9]+              |
| HEX   | (0w [0x 0X])[0-9a-fA-F]+ |

[toInt w] returns the integer in the range 0..255 represented by w.  
[toIntX w] returns the signed integer (in the range ~128..127) represented by bit-pattern w.

[fromInt i] returns the word holding the 8 least significant bits of i.

[toLargeInt w] returns the integer in the range 0..255 represented by w.  
 [toLargeIntX w] returns the signed integer (in the range ~128..127) represented by bit-pattern w.  
 [fromLargeInt i] returns the word holding the 8 least significant bits of i.  
 [toLargeWord w] returns the Word.word value corresponding to w.  
 [toLargeWordX w] returns the Word.word value corresponding to w, with sign extension. That is, the 8 least significant bits of the result are those of w, and the remaining bits are all equal to the most significant bit of w: its 'sign bit'.  
 [fromLargeWord w] returns w modulo 256.

## Module Word8Array

Word8Array -- SML Basis Library

```

eqtype array = Word8.word
type vector = Word8Vector.vector

val maxLen : int
val array : int * elem -> array
val tabulate : int * (int -> elem) -> array
val fromList : elem list -> array
val length : array -> int
val sub : array * int -> elem
val update : array * int * elem -> unit
val extract : array * int * int option -> vector
val copy : {src: array, si: int, len: int option,
 dst: array, di: int} -> unit
val copyVec : {src: vector, si: int, len: int option,
 dst: array, di: int} -> unit
val app : (elem -> unit) -> array -> unit
val foldl : (elem * 'b -> 'b) -> 'b -> array -> 'b
val foldr : (elem * 'b -> 'b) -> 'b -> array -> 'b
val modify : (elem -> elem) -> array -> unit
val appi : (int * elem -> unit) -> array * int * int option -> unit
val foldli : (int * elem * 'b -> 'b) -> 'b -> array * int * int option -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> array * int * int option -> 'b
val modifyi : (int * elem -> elem) -> array * int * int option -> unit

```

---

[array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type Word8.word, that is, 8-bit words. Arrays a1 and a2 are equal if both were created by the same call to a primitive (array0, array, tabulate, fromList).

All operations are as for Array.array.

## Module Word8Vector

*Word8Vector* -- SML Basis Library

```

datatype vector
type elem = Word8.word

val maxLen : int
val fromList : elem list -> vector
val tabulate : int * (int -> elem) -> vector

val length : vector -> int
val sub : vector * int -> elem
val extract : vector * int * int option -> vector
val concat : vector list -> vector

val app : (elem -> unit) -> vector -> unit
val map : (elem -> elem) -> vector -> vector
val foldl : (elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldr : (elem * 'b -> 'b) -> 'b -> vector -> 'b

val appi : (int * elem -> unit) -> vector * int * int option -> unit
val mapi : (int * elem -> elem) -> vector * int * int option -> vector
val foldli : (int * elem * 'b -> 'b) -> 'b -> vector*int*int option -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> vector*int*int option -> 'b

```

[vector] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type `Word8.word`, that is, 8-bit words. Type vector admits equality, and vectors `v1` and `v2` are equal if they have the same length and their elements are equal.

All operations are as for `Vector.vector`.

## Index

```

! value (General), 41, 43
!= value (Real), 103, 104
$ constructor (Msp), 72
$$ constructor (Msp), 72
% value (Msp), 70, 72
value (Msp), 70, 72
%% value (Msp), 70, 72
value (Msp), 70, 72
%? value (Msp), 70, 72
&& constructor (Msp), 72
* value (General), 42, 44
 value (Int), 46
 value (Real), 103
 value (Time), 132, 133
 value (Word), 141, 142
 value (Word8), 144, 145
+ value (General), 42, 44
 value (Int), 46
 value (Real), 103
 value (Time), 132, 133
 value (Word), 141, 142
 value (Word8), 144, 145
- value (General), 42, 44
 value (Int), 46
 value (Real), 103
 value (Time), 132, 133
 value (Word), 141, 142
 value (Word8), 144, 145
/ value (General), 42, 44
 value (Real), 103
:= value (General), 41, 43
< value (Char), 21, 23
 value (General), 42, 44
 value (Int), 46, 47
 value (Real), 103
 value (String), 120, 121
 value (Time), 132, 133
 value (Word), 141, 142
 value (Word8), 144, 145
 value (General), 41, 44
 value (String), 120
~ value (General), 42, 44
 value (Int), 46
 value (Real), 103
~>> value (Word), 141, 142
 value (Word8), 144, 145
A_EXECC

```

constructor (FileSys), 34  
 A\_READ  
 constructor (FileSys), 34  
 A\_WRITE  
 constructor (FileSys), 34  
 abrt  
 value (Signal), 110  
 Abs  
 exception (SML90), 109  
 abs  
 value (General), 42, 44  
 value (Int), 46  
 value (Real), 103  
 accept  
 value (Socket), 112, 113  
 access  
 type (FileSys), 33, 34  
 value (FileSys), 33, 34  
 acos  
 value (Math), 59  
 active  
 type (Socket), 112, 113  
 add  
 value (Binaryset), 14  
 value (Gdbm), 36, 37  
 value (Intset), 49  
 value (Polygdbm), 93  
 value (Splayset), 118  
 add\_break  
 value (PP), 85  
 add\_newline  
 value (PP), 85, 86  
 add\_string  
 value (PP), 85, 86  
 addlist  
 value (Binaryset), 14  
 value (Intset), 49  
 value (Splayset), 118  
 address  
 value (Msp), 71, 73  
 ahref  
 value (Msp), 71, 73  
 ahrefa  
 value (Msp), 71, 73  
 all  
 value (List), 53, 54  
 value (ListPair), 55  
 value (Substring), 124  
 allCookies  
 value (MosmlCookie), 69  
 AlreadyThere  
 exception (Gdbm), 36  
 exception (Polygdbm), 93  
 alrm  
 value (Signal), 110  
 aname  
 value (Msp), 71, 73  
 andb  
 value (Word), 141  
 value (Word8), 144  
 app  
 value (Array), 3, 4  
 value (Array2), 6, 7  
 value (Binarymap), 13  
 value (Binaryset), 14, 15  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Gdbm), 36, 37  
 value (Intmap), 48  
 value (Intset), 49  
 value (List), 53, 54  
 value (ListPair), 55  
 value (NU93), 80  
 value (Option), 84  
 value (Polygdbm), 93, 94  
 value (Regex), 105, 107  
 value (Splaymap), 117  
 value (Splayset), 118, 119  
 value (Substring), 124, 127  
 value (Vector), 136  
 value (Weak), 138, 139  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 app1  
 value (Callback), 18, 19  
 value (Dynlib), 31, 32  
 app2  
 value (Callback), 18, 19  
 value (Dynlib), 31, 32  
 app3  
 value (Callback), 18, 19  
 value (Dynlib), 31, 32  
 app4  
 value (Callback), 18, 20  
 value (Dynlib), 31, 32  
 app5  
 value (Callback), 18, 20  
 value (Dynlib), 31, 32  
 appi  
 value (Array), 3–5  
 value (Array2), 6, 8  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Vector), 136, 137  
 value (Weak), 138, 140  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 AppleScript  
 AppleScriptErr  
 exception (AppleScript), 2  
 apply  
 value (Polyhash), 95  
 applyto  
 value (MySQL), 77, 79

value (Postgres), 98, 100  
 arctan  
 value (NU93), 80  
 value (SML90), 109  
 area  
 value (Msp), 71, 74  
 arguments  
 value (CommandLine), 26  
 argv  
 value (Mosml), 65  
 Array (structure), 3–5  
 array  
 type (Array), 3  
 type (Array2), 6  
 type (CharArray), 24  
 type (Dynarray), 30  
 type (Weak), 138, 139  
 type (Word8Array), 147  
 value (Array), 3  
 value (Array2), 6  
 value (CharArray), 24  
 value (Dynarray), 30  
 value (Weak), 138, 139  
 value (Word8Array), 147  
 Array2 (structure), 6–8  
 Arraysort (structure), 9  
 as\_compile  
 value (AppleScript), 2  
 as\_dispose  
 value (AppleScript), 2  
 as\_run\_script  
 value (AppleScript), 2  
 as\_run\_text  
 value (AppleScript), 2  
 asin  
 value (Math), 59  
 atan  
 value (Math), 59  
 atan2  
 value (Math), 59  
 atExit  
 value (Process), 101  
 backtrack  
 value (Lexing), 51  
 base  
 value (Path), 90, 92  
 value (Substring), 124, 125  
 before  
 value (General), 41, 43  
 begin\_block  
 value (PP), 85, 86  
 Binarymap (structure), 13  
 Binaryset (structure), 14–15  
 Bind  
 exception (General), 41, 43  
 bind  
 value (Socket), 112, 113  
 BinIO (structure), 10–12  
 blockquote  
 value (Msp), 70, 73  
 blockquotea  
 value (Msp), 70, 73  
 body  
 value (Msp), 70, 73  
 bodya  
 value (Msp), 70, 73  
 Bool (structure), 16  
 bool  
 type (Bool), 16  
 type (General), 41, 42  
 bound  
 value (Dynarray), 30  
 br  
 value (Msp), 70, 73  
 bra  
 value (Msp), 70, 73  
 break\_style  
 type (PP), 85  
 browser  
 value (Help), 45  
 bucketSizes  
 value (Polyhash), 95, 96  
 buf  
 type (Socket), 112, 114  
 buff\_input  
 value (Nonstdio), 82  
 buff\_output  
 value (Nonstdio), 82  
 bus  
 value (Signal), 110  
 Byte (structure), 17  
 bytesToString  
 value (Byte), 17  
 byteToChar  
 value (Byte), 17  
 Callback (structure), 18–20  
 can\_input  
 value (NU93), 81  
 caption  
 value (Msp), 71, 74  
 captiona  
 value (Msp), 71, 74  
 ceil  
 value (General), 41, 44  
 value (Real), 103, 104  
 ceiling  
 value (NU93), 80  
 center  
 value (Msp), 70, 73  
 cfLag  
 type (Regex), 105, 106  
 cgi\_annotation\_server  
 value (Mosmlcgi), 66, 68  
 cgi\_api\_version

value (MosmLcgi), 66, 68  
 cgi\_auth\_type  
 value (MosmLcgi), 66  
 cgi\_content\_length  
 value (MosmLcgi), 66, 68  
 cgi\_content\_type  
 value (MosmLcgi), 66  
 cgi\_document\_root  
 value (MosmLcgi), 66, 68  
 cgi\_field\_integer  
 value (MosmLcgi), 66, 67  
 cgi\_field\_string  
 value (MosmLcgi), 66, 67  
 cgi\_field\_strings  
 value (MosmLcgi), 66, 67  
 cgi\_fieldnames  
 value (MosmLcgi), 66, 67  
 cgi\_gateway\_interface  
 value (MosmLcgi), 66, 68  
 cgi\_http\_accept  
 value (MosmLcgi), 66, 68  
 cgi\_http\_cookie  
 value (MosmLcgi), 66, 68  
 cgi\_http\_forwarded  
 value (MosmLcgi), 66, 68  
 cgi\_http\_host  
 value (MosmLcgi), 66, 68  
 cgi\_http\_proxy\_connection  
 value (MosmLcgi), 66, 68  
 cgi\_http\_referer  
 value (MosmLcgi), 66, 68  
 cgi\_http\_user\_agent  
 value (MosmLcgi), 66, 68  
 cgi\_is\_subreq  
 value (MosmLcgi), 66, 68  
 cgi\_part  
 value (MosmLcgi), 66, 67  
 cgi\_partnames  
 value (MosmLcgi), 66, 67  
 cgi\_parts  
 value (MosmLcgi), 66, 67  
 cgi\_path\_info  
 value (MosmLcgi), 66, 68  
 cgi\_path\_translated  
 value (MosmLcgi), 66, 68  
 cgi\_query\_string  
 value (MosmLcgi), 66, 68  
 cgi\_remote\_addr  
 value (MosmLcgi), 66, 68  
 cgi\_remote\_host  
 value (MosmLcgi), 66, 68  
 cgi\_remote\_ident  
 value (MosmLcgi), 66, 68  
 cgi\_remote\_user  
 value (MosmLcgi), 66, 68  
 cgi\_request\_filename  
 value (MosmLcgi), 66, 68

cgi\_request\_method  
 value (MosmLcgi), 66, 68  
 cgi\_request\_uri  
 value (MosmLcgi), 66, 68  
 cgi\_script\_filename  
 value (MosmLcgi), 66, 68  
 cgi\_script\_name  
 value (MosmLcgi), 66, 68  
 cgi\_server\_admin  
 value (MosmLcgi), 66, 68  
 cgi\_server\_name  
 value (MosmLcgi), 66, 67  
 cgi\_server\_port  
 value (MosmLcgi), 66, 68  
 cgi\_server\_protocol  
 value (MosmLcgi), 66, 68  
 cgi\_server\_software  
 value (MosmLcgi), 66, 67  
 cgi\_the\_request  
 value (MosmLcgi), 66, 68  
 Char (structure), 21–23  
 char  
 type (Char), 21  
 type (General), 41, 42  
 value (GdImage), 38, 40  
 CharArray (structure), 24  
 charsize  
 value (GdImage), 38, 40  
 charToByte  
 value (Byte), 17  
 charUp  
 value (GdImage), 38, 40  
 CharVector (structure), 25  
 chdir  
 value (FileSys), 33  
 checkPUTimer  
 value (Timer), 134  
 checkReaTimer  
 value (Timer), 134  
 child  
 value (Signal), 110  
 Chr  
 exception (General), 41  
 chr  
 value (Char), 21  
 value (NJ93), 80  
 value (SML90), 109  
 clear\_ppstream  
 value (PP), 85, 86  
 clearParser  
 value (Parsing), 88, 89  
 close  
 value (Socket), 112, 114  
 close\_in  
 value (NJ93), 80  
 value (SML90), 109  
 close\_out

value (NJ93), 80  
 value (SML90), 109  
 closebase  
 value (Mysql), 76, 77  
 value (Postgres), 97, 98  
 Closed  
 exception (Dymlib), 31  
 exception (Gdbm), 36  
 exception (Mysql), 76  
 exception (Polygdbm), 93  
 exception (Postgres), 97  
 closeDir  
 value (FileSys), 33  
 closeIn  
 value (BinIO), 10  
 value (TextIO), 129  
 closeOut  
 value (BinIO), 10, 11  
 value (TextIO), 129, 130  
 cmdtuples  
 value (Mysql), 76, 78  
 value (Postgres), 97, 99  
 collate  
 value (String), 120, 121  
 value (Substring), 124, 125  
 CollMajor  
 constructor (Array2), 6  
 color  
 constructor (GdImage), 39  
 type (GdImage), 38, 39  
 value (GdImage), 38, 39  
 column  
 value (Array2), 6, 7  
 CommandLine (structure), 26  
 comment  
 value (Msp), 70, 73  
 compare  
 value (Char), 21, 23  
 value (Date), 27, 28  
 value (FileSys), 33, 35  
 value (Int), 46, 47  
 value (Real), 103  
 value (Socket), 112, 115  
 value (String), 120, 121  
 value (Substring), 124, 125  
 value (Time), 132, 133  
 value (Word), 141, 142  
 value (Word8), 144, 145  
 compile  
 value (Meta), 61, 62  
 compileStructure  
 value (Meta), 61, 62  
 compileTopLevel  
 value (Meta), 61, 62  
 compose  
 value (Option), 84  
 composePartial  
 cs  
 value (Option), 84  
 concat  
 value (CharVector), 25  
 value (List), 53  
 value (Path), 90, 91  
 value (String), 120  
 value (Substring), 124, 125  
 value (Vector), 136  
 value (Word8Vector), 148  
 connect  
 value (Socket), 112, 114  
 conservative  
 value (Meta), 61, 62  
 CONSISTENT  
 constructor (PP), 85  
 cont  
 value (Signal), 110  
 contains  
 value (Char), 21, 22  
 cookiedata  
 type (MosmLcookie), 69  
 CookieError  
 exception (MosmLcookie), 69  
 copy  
 value (Array), 3, 4  
 value (Array2), 6, 8  
 value (CharArray), 24  
 value (GdImage), 38, 40  
 value (Polyhash), 95, 96  
 value (Word8Array), 147  
 copyResize  
 value (GdImage), 38, 40  
 copytableFrom  
 value (Mysql), 77, 79  
 value (Postgres), 98, 100  
 copytableto  
 value (Mysql), 77, 79  
 value (Postgres), 98, 100  
 copyVec  
 value (Array), 3, 4  
 value (CharArray), 24  
 value (Word8Array), 147  
 cos  
 value (Math), 59  
 value (NJ93), 80  
 value (SML90), 109  
 cosh  
 value (Math), 59  
 cptr  
 type (Callback), 18, 19  
 cpu\_timer  
 type (Timer), 134  
 createLexer  
 value (Lexing), 51  
 createLexerString  
 value (Lexing), 51  
 cs

type (StringCvt), 122  
 type (TextIO), 129  
 currentArc  
   value (Path), 90, 91  
 Date  
   exception (Date), 27  
 Date (structure), 27–29  
 date  
   type (Date), 27  
   value (Date), 27  
 datum  
   type (Date), 27  
 day  
   value (Date), 27, 28  
 db  
   value (MySQL), 76, 77  
   value (Postgres), 97, 98  
 dbconn  
   type (MySQL), 76, 77  
   type (Postgres), 97, 98  
 dbresult  
   type (MySQL), 76, 77  
   type (Postgres), 97, 98  
 dbresultstatus  
   type (MySQL), 76  
   type (Postgres), 97  
 dd  
   value (Msp), 71, 74  
 dec  
   value (Num93), 80  
 default  
   value (Dynarray), 30  
 defaultBrowser  
   value (Help), 45  
 delay  
   value (Susp), 128  
 delete  
   value (Binaryset), 14  
   value (Intset), 49  
   value (Splayset), 118  
 deleteCookie  
   value (MosmCookie), 69  
 dest\_ppstream  
   value (PP), 85  
 dgram  
   type (Socket), 112, 113  
 dict  
   type (Binarymap), 13  
   type (Splaymap), 117  
 difference  
   value (Binaryset), 14  
   value (Intset), 49  
   value (Splayset), 118  
 dimensions  
   value (Array2), 6, 7  
 dir  
   value (Path), 90, 92  
   value (Unix), 135  
   exists  
   value (List), 53, 54  
   value (ListPair), 55  
 exit  
   value (Process), 101  
 exn  
   type (General), 41, 42  
   exnMessage  
   value (General), 41, 43  
   exnName  
   value (General), 41, 43  
 exp  
   value (Math), 59  
   value (Num93), 80  
   value (SML90), 109  
 explode  
   value (Num93), 80  
   value (SML90), 109  
   value (String), 120  
   value (Substring), 124, 125  
 ext  
   value (Path), 90, 92  
 Extended  
   constructor (Regex), 106  
   extract  
   value (Array), 3, 4  
   value (CharArray), 24  
   value (CharVector), 25  
   value (String), 120  
   value (Substring), 124  
   value (Vector), 136  
   value (Word8Array), 147  
   value (Word8Vector), 148  
 Fail  
   exception (General), 41  
 failure  
   value (Process), 101  
   fast\_really\_input  
   value (NonStdio), 82  
 fastwrite  
   value (Gdbm), 36, 37  
   value (Polygdbm), 93, 94  
 fields  
   value (Regex), 105, 108  
   value (String), 120, 121  
   value (Substring), 124, 126  
 file  
   value (Path), 90, 92  
   file\_exists  
   value (NonStdio), 82  
   file\_id  
   type (FileSys), 33, 34  
   fileAddr  
   value (Socket), 112, 113  
   fileDgram  
   value (Socket), 112, 113

  type (MySQL), 77  
   type (Postgres), 98  
 dynval  
   type (MySQL), 76  
   type (Postgres), 97  
 dynval2s  
   value (MySQL), 77, 79  
   value (Postgres), 98, 100  
 e  
   value (Math), 59  
 eflag  
   type (Regex), 105, 106  
 elem  
   type (BinIO), 10  
   type (CharArray), 24  
   type (CharVector), 25  
   type (TextIO), 129  
   type (Word8Array), 147  
   type (Word8Vector), 148  
 em  
   value (Msp), 71, 74  
 Empty  
   constructor (Msp), 72  
   exception (List), 53  
 empty  
   value (Binaryset), 14  
   value (Intmap), 48  
   value (Intset), 49  
   value (Splayset), 118  
 end\_block  
   value (PP), 85, 86  
 end\_of\_stream  
   value (Num93), 80  
   value (SML90), 109  
 endOfStream  
   value (BinIO), 10, 11  
   value (TextIO), 129, 130  
 equal  
   value (Binaryset), 14  
   value (Intset), 49  
   value (Splayset), 118  
 errLocation  
   value (Location), 57  
 errMsg  
   value (Location), 57  
 errorMessage  
   value (MySQL), 76, 77  
   value (Postgres), 97, 99  
 errorMsg  
   value (OS), 83  
 errPrompt  
   value (Location), 57  
 execute  
   value (MySQL), 76, 78  
   value (Postgres), 97, 99  
   value (Unix), 135  
 executeInEnv

fileId  
 value (FileSys), 33, 35  
 fileSize  
 value (FileSys), 33, 34  
 fileStream  
 value (Socket), 112, 113  
 FileSys (structure), 33–35  
 fill  
 value (Gdimage), 38, 40  
 fillBorder  
 value (Gdimage), 38, 40  
 fillPolygon  
 value (Gdimage), 38, 40  
 fillRect  
 value (Gdimage), 38, 40  
 filter  
 value (List), 53, 54  
 value (Option), 84  
 value (Polyhash), 95  
 find  
 value (Binarymap), 13  
 value (Binaryset), 14, 15  
 value (Gdbm), 36, 37  
 value (List), 49, 50  
 value (List), 53, 54  
 value (Polygdbm), 93  
 value (Polyhash), 95  
 value (Splaymap), 117  
 value (Splayset), 118, 119  
 value (Substring), 124, 125  
 flag  
 type (Dynlib), 31, 32  
 flatten  
 value (Msp), 70, 72  
 floatVec  
 value (Mosml), 65  
 floor  
 value (General), 41, 44  
 value (Real), 103, 104  
 flush\_out  
 value (NJ93), 81  
 flush\_ppstream  
 value (PP), 85, 86  
 flushout  
 value (BinIO), 10, 11  
 value (TextIO), 129, 131  
 fnt  
 value (Date), 27, 28  
 value (Int), 46, 47  
 value (Real), 103, 104  
 value (Time), 132, 133  
 value (Word), 141, 142  
 value (Word8), 144, 145  
 fname  
 value (Mysql), 76, 78  
 value (Postgres), 97, 99  
 foldr  
 value (Word8Vector), 148

fnames  
 value (Mysql), 76, 78  
 value (Postgres), 97, 99  
 fnumber  
 value (Mysql), 76, 78  
 value (Postgres), 97, 99  
 fold  
 value (Array2), 6, 7  
 value (Gdbm), 36, 37  
 value (NJ93), 80  
 value (Polygdbm), 93, 94  
 value (Regex), 105, 108  
 foldi  
 value (Array2), 6, 8  
 foldl  
 value (Array), 3, 4  
 value (Binarymap), 13  
 value (Binaryset), 14, 15  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Intmap), 48  
 value (Intset), 49  
 value (List), 53, 54  
 value (ListPair), 55  
 value (Splaymap), 117  
 value (Splayset), 118, 119  
 value (Substring), 124, 126  
 value (Vector), 136  
 value (Weak), 138, 139  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 foldli  
 value (Array), 3, 4  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Vector), 136, 137  
 value (Weak), 138–140  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 foIdr  
 value (Array), 3, 4  
 value (Binarymap), 13  
 value (Binaryset), 14, 15  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Intmap), 48  
 value (Intset), 49, 50  
 value (List), 53, 54  
 value (ListPair), 55  
 value (Splaymap), 117  
 value (Splayset), 118, 119  
 value (Substring), 124, 127  
 value (Vector), 136  
 value (Weak), 138, 139  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 foIdri

value (Array), 3, 4  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Vector), 136, 137  
 value (Weak), 138, 140  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 font  
 type (Gdimage), 38, 39  
 fonta  
 value (Msp), 71, 74  
 force  
 value (Susp), 128  
 form  
 value (Msp), 71, 75  
 forma  
 value (Msp), 71, 75  
 formatTable  
 value (Mysql), 77, 79  
 value (Postgres), 98, 100  
 fpe  
 value (Signal), 110  
 frag  
 type (General), 41, 42  
 frame  
 value (Msp), 72, 75  
 framea  
 value (Msp), 72, 75  
 frameset  
 value (Msp), 72, 75  
 fromCString  
 value (Char), 21, 23  
 value (String), 120, 121  
 fromDefault  
 value (Real), 103  
 fromInt  
 value (Int), 46  
 value (Real), 103  
 value (Word), 141, 142  
 value (Word8), 144, 145  
 fromLarge  
 value (Int), 46  
 fromLargeInt  
 value (Word), 141, 143  
 value (Word8), 144, 146  
 fromLargeWord  
 value (Word), 141, 143  
 value (Word8), 144, 146  
 fromList  
 value (Array), 3  
 value (Array2), 6  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Dynarray), 30  
 value (Vector), 136  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 fromMicroseconds  
 value (Time), 132  
 fromMilliseconds  
 value (Time), 132  
 fromPng  
 value (Gdimage), 38, 39  
 fromReal  
 value (Time), 132  
 fromSeconds  
 value (Time), 132  
 fromString  
 value (Bool), 16  
 value (Char), 21, 22  
 value (Date), 27, 28  
 value (Int), 46, 47  
 value (Path), 90, 92  
 value (Real), 103, 104  
 value (String), 120, 121  
 value (Time), 132, 133  
 value (Word), 141, 142  
 value (Word8), 144, 145  
 frontag  
 value (Mysql), 77  
 value (Postgres), 98  
 fromTimeLocal  
 value (Date), 27, 29  
 fromTimeUnix  
 value (Date), 27, 29  
 fromWord  
 value (Signal), 110  
 ftype  
 value (Mysql), 77  
 value (Postgres), 98  
 ftypes  
 value (Mysql), 77  
 value (Postgres), 98  
 fullPath  
 value (FileSys), 33, 34  
 Gdbm (structure), 36–37  
 GdbmError  
 exception (Gdbm), 36  
 exception (Polygdbm), 93  
 Gdimage (structure), 38–40  
 General (structure), 41–44  
 generator  
 type (Random), 102  
 get  
 value (Weak), 138  
 getbool  
 value (Mysql), 76, 78  
 value (Postgres), 97, 100  
 getc  
 value (Substring), 124, 125  
 getCookie  
 value (Mosml.cookie), 69  
 getCookieValue  
 value (Mosml.cookie), 69

getcptr  
   value (Callback), 18, 19  
 getCurrentLocation  
   value (Location), 57  
 getDate  
   value (MySQL), 76, 78  
   value (Postgres), 97, 99  
 getdatetime  
   value (MySQL), 76, 78  
   value (Postgres), 97, 99  
 getDir  
   value (FileSys), 33  
 getdyntfield  
   value (MySQL), 77, 78  
   value (Postgres), 98, 100  
 getdyntup  
   value (MySQL), 77, 79  
   value (Postgres), 98, 100  
 getdyntups  
   value (MySQL), 77, 79  
   value (Postgres), 98, 100  
 getEnv  
   value (Process), 101  
 getinetaddr  
   value (Socket), 112, 114  
 getint  
   value (MySQL), 76, 78  
   value (Postgres), 97, 99  
 getItem  
   value (List), 53, 54  
 getLexeme  
   value (Lexing), 51, 52  
 getLexemeChar  
   value (Lexing), 51, 52  
 getLexemeEnd  
   value (Lexing), 51, 52  
 getLexemeStart  
   value (Lexing), 51, 52  
 getOpt  
   value (Option), 84  
 getParent  
   value (Path), 90, 91  
 getreal  
   value (MySQL), 76, 78  
   value (Postgres), 97, 99  
 getstring  
   value (MySQL), 76, 78  
   value (Postgres), 97, 99  
 gettime  
   value (MySQL), 76, 78  
   value (Postgres), 97, 99  
 getTransparent  
   value (GImage), 38, 39  
 getVolume  
   value (Path), 90, 92  
 Graphic  
   exception (General), 41

h1  
   value (Msp), 70, 73  
 h2  
   value (Msp), 70  
 h3  
   value (Msp), 70  
 h4  
   value (Msp), 70  
 h5  
   value (Msp), 70  
 h6  
   value (Msp), 70  
 hash  
   value (FileSys), 33, 35  
   value (Polyhash), 95, 96  
 hash\_param  
   value (Polyhash), 95, 96  
 hash\_table  
   type (Polyhash), 95  
 hasKey  
   value (Gdbm), 36, 37  
   value (Polygdbm), 93  
 Hd  
   exception (NU93), 80  
 hd  
   value (List), 53  
   value (NU93), 80  
 head  
   value (Msp), 70, 73  
 Help (structure), 45  
 help  
   value (Help), 45  
 helpdirs  
   value (Help), 45  
 host  
   value (MySQL), 76, 77  
   value (Postgres), 97, 98  
 hour  
   value (Date), 27, 28  
 hr  
   value (Msp), 70, 73  
 hra  
   value (Msp), 70, 73  
 html  
   value (Msp), 70, 73  
 htmlColors  
   value (GImage), 38, 39  
 htmlDoc  
   value (Msp), 70, 73  
 htmlEncode  
   value (Msp), 72, 75  
 hup  
   value (Signal), 110  
 ICase  
   constructor (Regex), 106  
 ignore  
   value (General), 41, 43

ill  
   value (Signal), 110  
 image  
   type (GImage), 38, 39  
   value (GImage), 38, 39  
 img  
   value (Msp), 71, 74  
 imga  
   value (Msp), 71, 74  
 impLode  
   value (NU93), 80  
   value (SML90), 109  
   value (String), 120  
 in\_flags  
   type (Socket), 112, 115  
 in\_stream\_length  
   value (NonstdIo), 82  
 inc  
   value (NU93), 80  
 incheckBox  
   value (Msp), 71, 75  
 INCONSISTENT  
   constructor (FP), 85  
 indexfiles  
   value (Help), 45  
 inetAddr  
   value (Socket), 112, 113  
 inetDgram  
   value (Socket), 112, 113  
 inetStream  
   value (Socket), 112, 113  
 inhidden  
   value (Msp), 71, 75  
 inpassword  
   value (Msp), 71, 75  
 input  
   value (BinIO), 10  
   value (Msp), 71, 75  
   value (NU93), 80  
   value (SML90), 109  
   value (TextIO), 129, 130  
 input1  
   value (BinIO), 10  
   value (TextIO), 129, 130  
 input\_binary\_int  
   value (NonstdIo), 82  
 input\_char  
   value (NonstdIo), 82  
 input\_line  
   value (NU93), 81  
 input\_value  
   value (NonstdIo), 82  
 inputa  
   value (Msp), 71, 75  
 inputAll  
   value (BinIO), 10  
   value (TextIO), 129, 130

inputc  
   value (NU93), 81  
 inputLine  
   value (TextIO), 129, 130  
 inputN  
   value (BinIO), 10, 11  
   value (TextIO), 129, 130  
 inputNOBlock  
   value (BinIO), 10  
   value (TextIO), 129, 130  
 inradio  
   value (Msp), 71, 75  
 inreset  
   value (Msp), 71, 75  
 insert  
   value (BinaryMap), 13  
   value (Gdbm), 36, 37  
   value (Intmap), 48  
   value (Polygdbm), 93  
   value (Polyhash), 95  
   value (SplayMap), 117  
 installPP  
   value (Meta), 61  
 instream  
   type (BinIO), 10  
   type (NU93), 80  
   type (SML90), 109  
   type (TextIO), 129  
 insubmit  
   value (Msp), 71, 75  
 Int (structure), 46-47  
 int  
   type (General), 41, 42  
   type (Int), 46  
   value (Signal), 110  
 Interrupt  
   exception (General), 41  
 intersection  
   value (BinarySet), 14  
   value (Intset), 49  
   value (SplaySet), 118  
 intext  
   value (Msp), 71, 75  
 Intmap (structure), 48  
 intmap  
   type (Intmap), 48  
 Intset (structure), 49-50  
 intset  
   type (Intset), 49  
 Invalid\_argument  
   exception (General), 41  
 Io  
   exception (General), 41  
 isAbsolute  
   value (Path), 90, 91  
 isAlpha  
   value (Char), 21, 22



isAlphaNum  
 value (Char), 21, 22  
 isAscii  
 value (Char), 21, 22  
 isCanonical  
 value (Path), 90, 91  
 isCtrl  
 value (Char), 21, 22  
 isDead  
 value (Weak), 138, 139  
 isDigit  
 value (Char), 21  
 isDir  
 value (FileSys), 33, 34  
 isDst  
 value (Date), 27, 28  
 isEmpty  
 value (Binaryset), 14  
 value (Intset), 49  
 value (Splayset), 118  
 value (Substring), 124, 125  
 isGraph  
 value (Char), 21, 22  
 isHexDigit  
 value (Char), 21, 22  
 isLink  
 value (FileSys), 33, 34  
 isLower  
 value (Char), 21  
 isNull  
 value (MySQL), 76, 78  
 value (Postgres), 97, 100  
 isPrefix  
 value (String), 120, 121  
 value (Substring), 124, 125  
 isPrint  
 value (Char), 21, 22  
 isPunct  
 value (Char), 21, 22  
 isRegistered  
 value (Callback), 18, 19  
 isRelative  
 value (Path), 90, 91  
 isSome  
 value (Option), 84  
 isSpace  
 value (Char), 21, 22  
 isSubset  
 value (Binaryset), 14  
 value (Intset), 49  
 value (Splayset), 118  
 isUpper  
 value (Char), 21  
 isWeak  
 value (Weak), 138  
 it emEnd  
 value (Parsing), 88, 89

itemStart  
 value (Parsing), 88  
 join  
 value (Option), 84  
 joinBaseExt  
 value (Path), 90, 92  
 joinDirFile  
 value (Path), 90, 92  
 kill  
 value (Signal), 110  
 value (Unix), 135  
 last  
 value (List), 53  
 length  
 value (Array), 3  
 value (CharArray), 24  
 value (CharVector), 25  
 value (List), 53  
 value (Vector), 136  
 value (Weak), 138, 139  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 lexbuf  
 type (Lexing), 51  
 Lexing (structure), 51–52  
 li  
 value (Msp), 71, 74  
 liberal  
 value (Meta), 61, 62  
 List (structure), 53–54  
 list  
 type (General), 41, 42  
 type (List), 53  
 listDir  
 value (Mosml), 65  
 listen  
 value (Socket), 112, 114  
 listItems  
 value (Binarymap), 13  
 value (Binaryset), 14, 15  
 value (Gdbm), 36, 37  
 value (Intmap), 48  
 value (Intset), 49  
 value (Polygdbm), 93, 94  
 value (Polyhash), 95  
 value (Splaymap), 117  
 value (Splayset), 118, 119  
 listKeys  
 value (Gdbm), 36, 37  
 value (Polygdbm), 93, 94  
 ListPair (structure), 55  
 Listsort (structure), 56  
 ln  
 value (Match), 59  
 value (NJ93), 80

value (SML90), 109  
 load  
 value (Meta), 61, 63  
 loaded  
 value (Meta), 61, 63  
 loadOne  
 value (Meta), 61, 63  
 loadPath  
 value (Meta), 61, 63  
 localOffset  
 value (Date), 27, 29  
 Location  
 type (Location), 57  
 Location (structure), 57–58  
 log10  
 value (Math), 59  
 lookahead  
 value (BinIO), 10, 11  
 value (NJ93), 80  
 value (CharVector), 109  
 value (TextIO), 129, 130  
 makestring  
 value (General), 42, 44  
 map  
 value (Binarymap), 13  
 value (CharVector), 25  
 value (Gdbm), 36, 37  
 value (Intmap), 48  
 value (List), 53, 54  
 value (ListPair), 55  
 value (Msp), 71, 74  
 value (Option), 84  
 value (Polygdbm), 93, 94  
 value (Polyhash), 95  
 value (Regex), 105, 107  
 value (Splaymap), 117  
 value (String), 120  
 value (Vector), 136  
 value (Word8Vector), 148  
 mapa  
 value (Msp), 71, 74  
 mapi  
 value (CharVector), 25  
 value (Vector), 136, 137  
 value (Word8Vector), 148  
 mapPartial  
 value (List), 53, 54  
 value (Option), 84  
 mark0  
 value (Msp), 70, 73  
 mark0a  
 value (Msp), 70, 73  
 mark1  
 value (Msp), 70, 73  
 mark1a  
 value (Msp), 70, 73  
 Match  
 value (General), 41  
 Math (structure), 59–60  
 max  
 value (Int), 46, 47  
 value (NJ93), 80  
 value (Real), 103  
 value (Word), 141, 142  
 value (Word8), 144, 145  
 maxChar  
 value (Char), 21  
 maxInt  
 value (Int), 46  
 maxLen  
 value (Array), 3  
 value (CharArray), 24  
 value (CharVector), 25  
 value (Vector), 136  
 value (Weak), 138, 139  
 value (Word8Array), 147  
 value (Word8Vector), 148  
 maxOrd  
 value (Char), 21  
 maxSize  
 value (String), 120  
 md5sum  
 value (Mosml), 65  
 member  
 value (Binaryset), 14  
 value (Intset), 49  
 value (Splayset), 118  
 Meta (structure), 61–64  
 min  
 value (Int), 46, 47  
 value (NJ93), 80  
 value (Real), 103  
 value (Word), 141, 142  
 value (Word8), 144, 145  
 minChar  
 value (Char), 21  
 minInt  
 value (Int), 46  
 minute  
 value (Date), 27, 28  
 mk\_ppstream  
 value (PP), 85  
 mkAbsolute  
 value (Path), 90, 91  
 mkCanonical  
 value (Path), 90, 91  
 mkDict  
 value (Binarymap), 13  
 value (Splaymap), 117  
 mkDir  
 value (FileSys), 33  
 mkLoc  
 value (Location), 57  
 mkPolyTable

value (Polyhash), 95, 96  
 mktime  
 value (Path), 90, 91  
 mktime  
 value (Polyhash), 95  
 mod  
 value (General), 42, 44  
 value (Int), 46  
 value (Word), 141, 142  
 value (Word8), 144, 145  
 mode  
 type (Gdimage), 38, 39  
 modify  
 value (Array), 3, 4  
 value (Array2), 6, 7  
 value (CharArray), 24  
 value (Weak), 138, 139  
 value (Word8Array), 147  
 modify  
 value (Array), 3, 5  
 value (Array2), 6, 8  
 value (CharArray), 24  
 value (Weak), 138, 140  
 value (Word8Array), 147  
 modtime  
 value (FileSys), 33, 34  
 month  
 type (Date), 27  
 value (Date), 27, 28  
 Mysql (structure), 65  
 Mysqlcgi (structure), 66–68  
 Mysqlcookie (structure), 69  
 Msp (structure), 70–75  
 Mysql (structure), 76–79  
 name  
 value (CommandLine), 26  
 nCols  
 value (Array2), 6, 7  
 newgen  
 value (Random), 102  
 newgensend  
 value (Random), 102  
 NewLine  
 constructor (Regex), 106  
 nFields  
 value (Mysql), 76, 78  
 value (Postgres), 97, 99  
 niLocation  
 value (Location), 57  
 NJ93 (structure), 80–81  
 NI  
 constructor (Msp), 72  
 NO\_RECVS  
 constructor (Socket), 114  
 NO\_RECVS\_OR\_SENDS  
 constructor (Socket), 114  
 NO\_SENDS  
 constructor (Socket), 114  
 value (Polyhash), 95, 96  
 NonStdio (structure), 82  
 not  
 value (Bool), 16  
 value (General), 41, 44  
 notb  
 value (Word), 141  
 value (Word8), 144  
 NotBool  
 constructor (Regex), 106  
 notContains  
 value (Char), 21, 22  
 Noteol  
 constructor (Regex), 107  
 NotFound  
 exception (Binarymap), 13  
 exception (Binaryset), 14  
 exception (Gdbm), 36  
 exception (Intmap), 48  
 exception (Intset), 49  
 exception (Polygdbm), 93  
 exception (Splaymap), 117  
 exception (Splayset), 118  
 NotInt  
 exception (Msp), 70  
 notTransparent  
 value (Gdimage), 38, 40  
 NotWriter  
 exception (Gdbm), 36  
 exception (Polygdbm), 93  
 now  
 value (Time), 132  
 nRows  
 value (Array2), 6, 7  
 nth  
 value (List), 53  
 value (NJ93), 80  
 nthtail  
 value (NJ93), 80  
 ntuples  
 value (Mysql), 76, 78  
 value (Postgres), 97, 99  
 Null  
 exception (Mysql), 76  
 exception (Postgres), 97  
 null  
 value (List), 53  
 numItems  
 value (Binarymap), 13  
 value (Binaryset), 14  
 value (Gdbm), 36, 37  
 value (Intmap), 48  
 value (Intset), 49  
 value (Polygdbm), 93, 94  
 value (Polyhash), 95  
 value (Splaymap), 117  
 value (Splayset), 118

o  
 value (General), 41, 43  
 offset  
 value (Date), 27, 28  
 oid  
 constructor (Postgres), 98  
 type (Postgres), 97, 98  
 oi  
 value (Msp), 71, 74  
 ola  
 value (Msp), 71, 74  
 open\_append  
 value (NJ93), 81  
 open\_in  
 value (NJ93), 80  
 value (SML90), 109  
 open\_in\_bin  
 value (NJ93), 81  
 value (NonStdio), 82  
 open\_out  
 value (NJ93), 80  
 value (SML90), 109  
 open\_out\_bin  
 value (NJ93), 81  
 value (NonStdio), 82  
 open\_out\_exe  
 value (NonStdio), 82  
 openAppend  
 value (BinIO), 10, 11  
 value (TextIO), 129, 130  
 openbase  
 value (Mysql), 76, 77  
 value (Postgres), 97, 98  
 opendir  
 value (FileSys), 33  
 openIn  
 value (BinIO), 10  
 value (TextIO), 129  
 openmode  
 type (Gdbm), 36  
 openOut  
 value (BinIO), 10, 11  
 value (TextIO), 129, 130  
 Option  
 exception (Option), 84  
 Option (structure), 84  
 option  
 type (General), 41, 42  
 type (Option), 84  
 value (Msp), 71, 75  
 options  
 value (Mysql), 76, 77  
 value (Postgres), 97, 98  
 orb  
 value (Word), 141  
 value (Word8), 144  
 ord  
 value (Path), 90, 91  
 value (Char), 21  
 value (NJ93), 80  
 value (SML90), 109  
 order  
 type (General), 41, 42  
 ordoF  
 value (NJ93), 80  
 orthodox  
 value (Meta), 61, 62  
 OS (structure), 83  
 OSerr  
 type (AppleScript), 2  
 OSALID  
 type (AppleScript), 2  
 out\_flags  
 type (Socket), 112, 114  
 Out\_of\_memory  
 exception (General), 41  
 output  
 value (BinIO), 10, 11  
 value (TextIO), 129, 130  
 output\_binary\_int  
 value (NonStdio), 82  
 output\_byte  
 value (NonStdio), 82  
 output\_char  
 value (NonStdio), 82  
 output\_value  
 value (NonStdio), 82  
 outputc  
 value (NJ93), 81  
 outputSubstr  
 value (TextIO), 129  
 outstream  
 type (BinIO), 10  
 type (TextIO), 129  
 Overflow  
 exception (General), 41  
 p  
 value (Msp), 70, 73  
 pa  
 value (Msp), 70, 73  
 packString  
 value (Byte), 17  
 padLeft  
 value (StringCvt), 122  
 padRight  
 value (StringCvt), 122, 123  
 ParamMissing  
 exception (Msp), 70  
 parentArc  
 value (Path), 90, 91

- ParseError
  - exception (Parsing), 88
- parseTables
  - type (Parsing), 88
- Parsing (structure), 88–89
- part
  - type (Mosmlcgi), 66
- part\_data
  - value (Mosmlcgi), 66, 67
- part\_field\_integer
  - value (Mosmlcgi), 66, 67
- part\_field\_string
  - value (Mosmlcgi), 66, 67
- part\_field\_strings
  - value (Mosmlcgi), 66, 67
- part\_fieldnames
  - value (Mosmlcgi), 66, 67
- part\_type
  - value (Mosmlcgi), 66
- partition
  - value (List), 53, 54
- passive
  - type (Socket), 112, 113
- Path
  - exception (Path), 90
- Path (structure), 90–92
- peek
  - value (Binarymap), 13
  - value (Binaryset), 14
  - value (Gdbm), 36, 37
  - value (Intmap), 48
  - value (Polygdbm), 93
  - value (Polyhash), 95
  - value (Splaymap), 117
  - value (Splayset), 118
- peekInsert
  - value (Polyhash), 95
- peekVal
  - value (Parsing), 88
- pf\_file
  - type (Socket), 112, 113
- pf\_inet
  - type (Socket), 112, 113
- pi
  - value (Math), 59
- pipe
  - value (Signal), 110
- Polygdbm (structure), 93–94
- Polyhash (structure), 95–96
- port
  - value (Mysql), 76, 77
  - value (Postgres), 97, 98
- pos\_in
  - value (Nonstdio), 82
- pos\_out
  - value (Nonstdio), 82
- position
  - value (Regex), 105, 107
- value (Substring), 124, 126
- Postgres (structure), 97–100
- pow
  - value (Math), 59
- PP (structure), 85–87
- pp\_to\_string
  - value (PP), 85, 86
- ppcounter
  - type (PP), 85
- ppstream
  - type (General), 41, 42
- pre
  - value (Misp), 71, 73
- precision
  - value (Int), 46
- pred
  - value (Char), 21
- print
  - value (NJ93), 80
  - value (TextIO), 129, 131
- printDepth
  - value (Meta), 61
- printLength
  - value (Meta), 61
- printseq
  - value (Misp), 70, 72
- printVal
  - value (Meta), 61
- primap
  - value (Misp), 70, 72
- proc
  - type (Unix), 135
- Process (structure), 101
- presep
  - value (Misp), 70, 72
- quietdec
  - value (Meta), 61, 63
- quit
  - value (Meta), 61
  - value (Signal), 110
- quot
  - value (Int), 46
- quotation
  - value (Meta), 61, 63
- radix
  - type (StringCvt), 122
- Random (structure), 102
- random
  - value (Random), 102
- randomList
  - value (Random), 102
- range
  - value (Random), 102
- rangeList
  - value (Random), 102
- readDir
  - value (Regex), 105, 107
- value (FileSys), 33
- value (StringCvt), 122
- readLink
  - value (FileSys), 33, 34
- Real (structure), 103–104
- real
  - type (General), 41, 42
  - type (Math), 59
  - type (Real), 103
  - value (General), 41, 44
- real\_timer
  - type (Timer), 134
- realFmt
  - type (StringCvt), 122
- realPath
  - value (FileSys), 33, 34
- reap
  - value (Unix), 135
- recvArr
  - value (Socket), 113, 115
- recvArr'
  - value (Socket), 113, 115
- recvArrFrom
  - value (Socket), 113, 115
- recvArrFrom'
  - value (Socket), 113, 115
- recvVec
  - value (Socket), 113, 114
- recvVec'
  - value (Socket), 113, 115
- recvVecFrom
  - value (Socket), 113, 115
- recvVecFrom'
  - value (Socket), 113, 115
- ref
  - constructor (General), 42
  - type (General), 41, 42
- regcomp
  - value (Regex), 105, 106
- Regex
  - exception (Regex), 105
- Regex (structure), 105–108
- regex
  - type (Regex), 105
- regexec
  - value (Regex), 105, 106
- regexecBool
  - value (Regex), 105, 107
- region
  - type (Array2), 6, 7
- register
  - value (Callback), 18, 19
- regmatch
  - value (Regex), 105, 107
- regmatchBool
  - value (Regex), 105, 107
- round
  - value (Regex), 105, 107
- regnec
  - value (Regex), 105, 107
- regnecBool
  - value (Regex), 105, 107
- rem
  - value (Int), 46, 47
- remove
  - value (Binarymap), 13
  - value (FileSys), 33, 34
  - value (Gdbm), 36, 37
  - value (Intmap), 48
  - value (Polygdbm), 93
  - value (Polyhash), 95
  - value (Splaymap), 117
- rename
  - value (FileSys), 33, 34
- reorganize
  - value (Gdbm), 36, 37
- replace
  - value (Regex), 105, 107
- replaceAll
  - value (Regex), 105, 107
- replacer
  - type (Regex), 105
- reset
  - value (Mysql), 76, 77
  - value (Postgres), 97, 99
- resultStatus
  - value (Mysql), 76, 78
  - value (Postgres), 97, 99
- retrieve
  - value (Binaryset), 14
  - value (Intmap), 48
  - value (Splayset), 118
- rev
  - value (List), 53
- revapp
  - value (Binarymap), 13
  - value (Binaryset), 14, 15
  - value (Intmap), 48
  - value (Intset), 49
  - value (NJ93), 80
  - value (Splaymap), 117
  - value (Splayset), 118, 119
- revAppend
  - value (List), 53, 54
- revfold
  - value (NJ93), 80
- rewindDir
  - value (FileSys), 33
- rgb
  - type (GdiImage), 38, 39
  - value (GdiImage), 38, 39
- rmdir
  - value (FileSys), 33
- round
  - value (Regex), 105, 107

value (General), 42, 44  
 value (Real), 103, 104  
 row  
   value (Array2), 6, 7  
 RowMajor  
   constructor (Array2), 6  
 RTLD\_LAZY  
   constructor (Dymlib), 32  
 RTLD\_NOW  
   constructor (Dymlib), 32  
 run  
   value (Mosml), 65  
 runresult  
   type (Mosml), 65  
 sameDesc  
   value (Socket), 112, 115  
 sameSign  
   value (Int), 46, 47  
   value (Real), 103  
 scan  
   value (Bool), 16  
   value (Date), 27, 29  
   value (Int), 46, 47  
   value (Real), 103, 104  
   value (Time), 132, 133  
   value (Word), 141, 142  
   value (Word8), 144, 145  
 scanStream  
   value (TextIO), 129, 130  
 scanString  
   value (StringCvt), 122  
 second  
   value (Date), 27, 28  
 seek\_in  
   value (Nonstdio), 82  
 seek\_out  
   value (Nonstdio), 82  
 segv  
   value (Signal), 110  
 select  
   value (Msp), 71, 75  
   value (Socket), 112, 115  
 sendArr  
   value (Socket), 112, 114  
 sendArr'  
   value (Socket), 112, 114  
 sendArrTo  
   value (Socket), 112, 114  
 sendArrTo'  
   value (Socket), 113, 114  
 sendVec  
   value (Socket), 112, 114  
   value (Socket), 112, 114  
 sendVecTo  
   value (Socket), 112, 114  
 sendVecTo'  
   value (Socket), 112–116

set  
   value (Socket), 113, 114  
   type (Binaryset), 14  
   type (Playlist), 118  
   value (Weak), 138  
 setCookie  
   value (Mosmlcookie), 69  
 setCookies  
   value (Mosmlcookie), 69  
 setTime  
   value (FileSys), 33, 34  
 setTransparent  
   value (Gdimage), 38, 39  
 showquery  
   value (Mysql), 77, 79  
   value (Postgres), 98, 100  
 shutdown  
   value (Int), 112, 114  
   value (Socket), 112  
   type (Socket), 112  
 sign  
   value (Int), 46, 47  
   value (Real), 103  
 Signal (structure), 110–111  
 signal  
   type (Signal), 110  
   type (Unix), 135  
 sin  
   value (Math), 59  
   value (NJ93), 80  
   value (SML90), 109  
 singleton  
   value (Binaryset), 14  
   value (Intset), 49  
   value (Playlist), 118  
 sinh  
   value (Math), 59  
 Size  
   exception (General), 41  
 size  
   value (Gdimage), 38, 39  
   value (String), 120  
   value (Substring), 124, 125  
 skipWS  
   value (StringCvt), 122  
 slice  
   value (Substring), 124, 125  
 SML90 (structure), 109  
 sock  
   type (Socket), 112, 113  
 sock\_addr  
   type (Socket), 112, 113  
 sock\_desc  
   type (Socket), 112  
 sockDesc  
   value (Socket), 112, 115  
 Socket (structure), 112–116

sort  
   value (Arraysort), 9  
   value (Listsort), 56  
 sorted  
   value (Arraysort), 9  
   value (Listsort), 56  
 Span  
   exception (Substring), 124  
 span  
   value (Substring), 124, 126  
 specialfiles  
   value (Help), 45  
 Splaymap (structure), 117  
 Splayset (structure), 118–119  
 splitAt  
   value (Substring), 124, 126  
 splitBaseExt  
   value (Path), 90, 92  
 splitDirFile  
   value (Path), 90, 92  
 splitI  
   value (StringCvt), 122  
   value (Substring), 124, 126  
 splitr  
   value (Substring), 124, 126  
 sqrt  
   value (Math), 59  
   value (NJ93), 80  
   value (SML90), 109  
 startCPUTimer  
   value (Timer), 134  
 startRealTimer  
   value (Timer), 134  
 status  
   type (Process), 101  
   value (Mysql), 76, 77  
   value (Postgres), 97, 99  
 std\_err  
   value (NJ93), 81  
 std\_in  
   value (NJ93), 80  
   value (SML90), 109  
 std\_out  
   value (NJ93), 80  
   value (SML90), 109  
 stderr  
   value (TextIO), 129, 131  
 stdIn  
   value (TextIO), 129, 130  
 stdOut  
   value (TextIO), 129, 131  
 stdoutPrg  
   value (Gdimage), 38, 39  
 stop  
   value (Signal), 110  
 Str  
   constructor (Regex), 107

str  
   value (String), 120  
 stream  
   type (Socket), 112, 113  
 streamsOf  
   value (Unix), 135  
 String (structure), 120–121  
 string  
   type (General), 41, 42  
   type (String), 120  
   value (Gdimage), 38, 40  
   value (Substring), 124  
 StringCvt (structure), 122–123  
 stringToBytes  
   value (Byte), 17  
 stringUp  
   value (Gdimage), 38, 40  
 strong  
   value (Msp), 71, 74  
 style  
   type (Gdimage), 38, 39  
 sub  
   value (Array), 3  
   value (Array2), 6, 7  
   value (CharArray), 24  
   value (CharVector), 25  
   value (DyMarray), 30  
   value (Msp), 71, 74  
   value (String), 120  
   value (Substring), 124, 125  
   value (Vector), 136  
   value (Weak), 138, 139  
   value (Word8Array), 147  
   value (Word8Vector), 148  
 subArray  
   value (DyMarray), 30  
 Subscript  
   exception (General), 41  
   substitute  
   value (Regex), 105, 107  
   substitutel  
   value (Regex), 105, 107  
 Substring  
   exception (NJ93), 80  
   Substring (structure), 124–127  
   substring  
   type (General), 41, 42  
   type (Substring), 124  
   value (NJ93), 80  
   value (String), 120  
   value (Substring), 124  
 succ  
   value (Char), 21  
 success  
   value (Process), 101  
 sup  
   value (Msp), 71, 74

Sus  
   constructor (Regex), 107  
   Susp (structure), 128  
 susp  
   type (Susp), 128  
 symbolEnd  
   value (Parsing), 88  
 symbolStart  
   value (Parsing), 88  
 symbolHandle  
   type (Dynlib), 31  
 SysErr  
   exception (General), 41  
   exception (OS), 83  
 syserror  
   type (General), 41, 42  
   type (OS), 83  
 system  
   value (Process), 101  
 table  
   type (Gdbm), 36  
   type (Polygdbm), 93  
   value (Msp), 71, 74  
 tablea  
   value (Msp), 71, 74  
 tabulate  
   value (Array), 3  
   value (Array2), 6, 7  
   value (CharArray), 24  
   value (CharVector), 25  
   value (Dynarray), 30  
   value (List), 53, 54  
   value (Vector), 136  
   value (Word8Array), 147  
   value (Word8Vector), 148  
 take  
   value (List), 53  
 take1  
   value (StringCvt), 122  
   value (Substring), 124, 125  
 taker  
   value (Substring), 124, 125  
 tan  
   value (Math), 59  
 tanh  
   value (Math), 59, 60  
 td  
   value (Msp), 71, 74  
 tda  
   value (Msp), 71, 74  
 term  
   value (Signal), 110  
 terminate  
   value (Process), 101  
 textArea  
   value (Msp), 71, 75  
 textAreaa  
   value (Msp), 71, 75  
   value (Gdimage), 38, 39  
 toReal  
   value (Time), 132  
 toSeconds  
   value (Time), 132  
 toString  
   value (Bool), 16  
   value (Char), 21, 22  
   value (Date), 27, 28  
   value (Int), 46, 47  
   value (Path), 90, 92  
   value (Real), 103, 104  
   value (String), 120, 121  
   value (Time), 132, 133  
   value (Word), 141, 142  
   value (Word8), 144, 145  
 totalCPUTimer  
   value (Timer), 134  
 totalRealTimer  
   value (Timer), 134  
 totalTime  
   value (Date), 27, 29  
 toUpper  
   value (Char), 21, 22  
 toWord  
   value (Signal), 110  
 Tr  
   constructor (Regex), 107  
 tr  
   value (Msp), 71, 74  
 tra  
   value (Msp), 71, 74  
 transform  
   value (BinarYmap), 13  
   value (Intmap), 48  
   value (Polyhash), 95, 96  
   value (SpLaymap), 117  
 translate  
   value (String), 120, 121  
   value (Substring), 124, 126  
 traversal  
   type (Array2), 6  
 triml  
   value (Substring), 124, 125  
 trimr  
   value (Substring), 124, 125  
 Trs  
   constructor (Regex), 107  
 trunc  
   value (General), 42, 44  
   value (Real), 103, 104  
 truncate  
   value (NU93), 80  
 tstep  
   value (Signal), 110  
 tt  
   value (Msp), 71, 74

ttin  
   value (Signal), 110, 111  
 ttou  
   value (Signal), 110, 111  
 tty  
   value (Mysql), 76, 77  
   value (Postgres), 97, 99  
 ul  
   value (Msp), 71, 74  
 ula  
   value (Msp), 71, 74  
 union  
   value (Binaryset), 14  
   value (Intset), 49  
   value (Splayset), 118  
 unit  
   type (General), 41, 42  
   type (structure), 135  
 unpackString  
   value (Byte), 17  
 unpackStringVec  
   value (Byte), 17  
 unregister  
   value (Callback), 18, 19  
 unzip  
   value (ListPair), 55  
 update  
   value (Array), 3, 4  
   value (Array2), 6, 7  
   value (CharArray), 24  
   value (Dynarray), 30  
   value (Weak), 138, 139  
   value (Word8Array), 147  
   urlencode  
   value (Msp), 72, 75  
 use  
   value (Meta), 61  
 usr1  
   value (Signal), 110  
 usr2  
   value (Signal), 110  
 validVolume  
   value (Path), 90, 91  
 valOf  
   value (Option), 84  
 valuepoly  
   value (Meta), 61, 63  
 var  
   value (Callback), 18, 19  
   value (Dynlib), 31, 32  
 vec2list  
   value (Msp), 70, 72  
 vecDouble  
   value (Mosml), 65  
 vecFloat  
   value (Mosml), 65

- Vector (structure), 136–137
- vector
  - type (BinIO), 10
  - type (CharArray), 24
  - type (CharVector), 25
  - type (General), 41, 42
  - type (TextIO), 129
  - type (Vector), 136
  - type (Word8Array), 147
  - type (Word8Vector), 148
  - value (General), 42, 44
  - verbose
    - value (Meta), 61, 63
- Weak (structure), 138–140
- weak
  - type (Weak), 138
  - value (Weak), 138
- weekDay
  - value (Date), 27, 28
- weekday
  - type (Date), 27
- welcome
  - value (Help), 45
- with\_pp
  - value (PP), 85, 86
- withtable
  - value (Gdbm), 36
  - value (Polydgm), 93
- withtables
  - value (Gdbm), 36
- Word (structure), 141–143
- word
  - type (General), 41, 42
  - type (Word), 141
  - type (Word8), 144
- Word8 (structure), 144–146
- word8
  - type (General), 41, 42
- Word8Array (structure), 147
- Word8Vector (structure), 148
- wordSize
  - value (Word), 141
  - value (Word8), 144
- wseq
  - type (Msp), 70, 72
- xL
  - value (Location), 57
- xLR
  - value (Location), 57
- xorb
  - value (Word), 141
  - value (Word8), 144
- xR
  - value (Location), 57
- xxLR
  - value (Location), 57
- xxRL
  - value (Location), 57, 58
- xy
  - type (GdiImage), 38, 39
- year
  - value (Date), 27, 28
- yearDay
  - value (Date), 27, 28
- yyexit
  - exception (Parsing), 88
- yyparse
  - value (Parsing), 88
- zeroTime
  - value (Time), 132
- zip
  - value (ListPair), 55